

LT4607E

Non-contact Type LED Array for Light Source

Model No.


LT4607E Yellow-green GaP

Features

1. Effective illuminance length : 218mm
2. No. of LED chips : 80pcs.
3. Non-contact type with shrink lens
4. Diameter of cylindrical lens : $\phi 6.0\text{mm}$
5. Outline dimensions : 235.0mm (L) \times 11.25mm (W)

Outline Dimensions

(Unit: mm)



SHARP

■ Absolute Maximum Ratings

(Ta = 25°C)

Parameter	Symbol	LT4607E	Unit
Power dissipation	P	7.3	W
Forward voltage	V _{LED}	13.0	V
Reverse voltage	V _R	16.0	V
Operating temperature	T _{opr}	0 to +60	°C
Storage temperature	T _{stg}	-40 to +75	°C

(Note) The period of continuous full dots illumination shall not exceed 30 seconds. For the purpose of heat dispersion, apply insulating grease to the rear of the substrate and attach it to a heat sink in the way that its whole surface contacts the heat sink.

■ Electro-optical Characteristics


(Ta = 25°C)

Parameter	Symbol	Model No.	Conditions	MIN.	TYP.	MAX.	Unit
Forward current	I _{LED}	LT4607E	V _{LED} = 12V	—	460	—	mA
※1 Effective illuminance length	L	LT4607E	V _{LED} = 12V	218	—	—	mm
※1 Illuminance power deviation	ΔEH	LT4607E	V _{LED} = 12V	—	—	15	%
※1 Effective illuminance width	ΔL	LT4607E	V _{LED} = 12V	—	3.0	—	mm
Peak emission wave length	λ _p	LT4607E	V _{LED} = 12V	—	565	—	nm
Spectrum radiation bandwidth	Δλ	LT4607E	V _{LED} = 12V	—	30	—	nm
※1 ※2 Illuminance	EL	LT4607E	V _{LED} = 12V	980	—	—	Lux
Response frequency	f _c	LT4607E	—	—	4	—	MHz

※1 Measuring method is specified in the next page.

※2 Value obtained within 30 seconds after lightening.


■ Measuring Method (Ta = 25°C, Within 30 seconds after lightening.)




*Slit size of photodetector : 1.1 × 4.9mm

■ Illuminance Distribution Characteristics

• Effective illuminance length: L



• Effective illuminance width: ΔL



• Illuminance power deviation: AEH

$$\Delta EH = \frac{MAX - MIN}{MAX + MIN} \cdot 100$$

