

GP1 S562

Compact Photointerrupter with Holders

■ Features


1. Compact package
2. With a spacer
3. With a hook for temporary installation to PWB

■ Applications

1. Floppy disk drivers
2. VCRs

■ Outline Dimensions

(Unit : mm)



■ Absolute Maximum Ratings

(Ta = 25°C)

Parameter		Symbol	Rating	Unit
Input	Forward current	I _F	50	mA
	*1 Peak forward current	I _{FM}	1	A
	Reverse voltage	V _R	6	V
	Power dissipation	P	75	mW
output	Collector-emitter voltage	V _{CEO}	35	V
	Emitter-collector voltage	V _{ECO}	6	V
	Collector current	I _C	20	mA
Collector power dissipation		P _C	75	mW
Operating temperature		T _{opr}	-25 to +85	°C
Storage temperature		T _{stg}	-40 to +100	°C
*2 Soldering temperature		T _{sol}	260	°C

*1 Pulse width $\leq 100 \mu\text{s}$, Duty ratio : 0.01

*2 For 5 seconds

■ Electro-optical Characteristics

(Ta= 25°C)

Parameter		Symbol	Condition	MIN.	TYP.	MAX.	Unit	
Input	Forward voltage	V_F	$I_F=20\text{mA}$		1.25	1.4	V	
	Peak forward voltage	V_{FM}	$I_{FM}=0.5\text{A}$		3	4	V	
	Reverse current	I_R	$V_R=3\text{V}$			10	μA	
output	Collector dark current	I_{CEO}	$V_{CE}=20\text{V}$	-	1	100	nA	
Transfer characteristics	Collector current	I_C	$V_{CE}=5\text{V}, I_F=20\text{mA}$	1.4	-	8.5	mA	
	Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_F=40\text{mA}, I_C=1.4\text{mA}$			0.4	V	
	Response time	Rise time	t_r	$V_{CE}=2\text{V}, I_C=2\text{mA}$	-	3	15	μs
		Fall time	t_f	$R_L=100\Omega$		4	20	μs

Fig. 1 Forward Current vs. Ambient Temperature




Fig. 2 Collector Power Dissipation vs. Ambient Temperature




Fig. 3 Peak Forward Current vs. Duty Ratio




Fig. 4 Forward Current vs. Forward Voltage




Fig. 5 Collector Current vs. Forward Current




Fig. 6 Collector Current vs. Collector-emitter Voltage




Fig. 7 Collector Current vs. Ambient Temperature




Fig. 8 Collector-emitter Saturation Voltage vs. Ambient Temperature






Fig. 9 Response Time vs. Load Resistance



Test Circuit for Response Time



Photointerrupters



Fig.10 Frequency Response





Fig.11 Collector Dark Current vs. Ambient Temperature



● Please refer to the chapter "Precautions for Use" (Page 78 to 93).