


CMOS 8-bit Single Chip Microcomputer

Piggyback/
evaluator type**Description**

The CXP82700 is a CMOS 8-bit single chip microcomputer of piggyback/evaluator combined type, which is developed for evaluating the function of the CXP82712/82716.

Features

- A wide instruction set (213 instructions) which cover various types of data.
 - 16-bit operation/multiplication and division/boolean bit operation instructions
- Minimum instruction cycle
 - 400ns at 10MHz operation
 - 122 μ s at 32kHz operation
- Applicable EPROM
 - LCC type 27C128, LCC type 27C256
(Maximum 16Kbytes are available)
- Incorporated RAM capacity
 - 448 bytes (LCD display data area included)
- Peripheral functions
 - A/D converter
 - 8-bit, 8-channel, successive approximation method
(Conversion time of 32 μ s/10MHz)
 - Serial interface
 - Incorporated 8-bit and 8-stage FIFO
(Auto transfer for 1 to 8 bytes), 1 circuit 2channels
 - Timer
 - 8-bit timer, 8-bit timer/counter,
19-bit time base timer, 32kHz timer/counter
 - Fluorescent display panel controller/driver
 - Maximum 144 segments display possible
 - 1 to 16-digit dynamic display
 - 24 high voltage drive output port
 - Dimmer function
 - High voltage drive output (40V)
 - On-chip pull-down resistor (Mask option)
 - Hardware key scan function
(Maximum 8 \times 8 key matrix compatible.)
 - Remote control receiving circuit
 - 8-bit pulse measurement counter with on-chip 6-stage FIFO
 - PWM output
 - 8bit, 1channel
- Interruption
 - 13 factors, 13 vectors, multi-interruption possible
- Standby mode
 - SLEEP/STOP
- Package
 - 64-pin ceramic PSDIP




Note) Mask option depends on the type of the CXP82700. Refer to the Products List for details.

Structure

Silicon gate CMOS IC


Sony reserves the right to change products and specifications without prior notice. This information does not convey any license by any implication or otherwise under any patents or other right. Application circuits shown, if any, are typical examples illustrating the operation of the devices. Sony cannot assume responsibility for any problems arising out of the use of these circuits.

Pin Assigment in Piggyback Mode



- Note)**
1. NC (Pin 3) is always connected to VDD.
 2. PH0/TX (Pin 1) is input port during port selection; oscillation output during oscillation selection.

Pin Assignment in Evaluator Mode




- Note)**
1. NC (Pin 3) is always connected to V_{DD}.
 2. PH0/TX (Pin 1) is input port during port selection; oscillation output during oscillation selection.

EPROM Read Timing

($T_a = -20$ to $+75^\circ\text{C}$, $V_{DD} = 4.5$ to 5.5V , $V_{SS} = 0\text{V}$ reference)


Item	Symbol	Pin	Min.	Max.	Unit
Address → data Input delay time	t_{ACC}	A0 to A15 D0 to D7		120	ns
Address → data Hold time	t_{IH}	A0 to A15 D0 to D7	0		ns



Products List

Option item	Products		
	Mask product		Piggyback/evaluator product
	CXP82712	CXP82716	CXP82700-U01S
Package	80-pin plastic SDIP		64-pin ceramic PSDIP
ROM capacity	12Kbytes	16Kbytes	EPROM 16Kbytes
Pull-up resistor for reset pin	Existent/Non-existent		Existent
Pull-down resistor for high voltage drive pin	Existent/Non-existent		Only port for display


Piggyback mode/evaluator mode can be switched as shown below.



Package Outline

Unit: mm

64PIN PSDIP (CERAMIC) 750mil



PACKAGE STRUCTURE

SONY CODE	PSDIP-64C-01
EIAJ CODE	ADIP064-C-0750-A
JEDEC CODE	_____

PACKAGE MATERIAL	CERAMIC
LEAD TREATMENT	GOLD PLATING
LEAD MATERIAL	42 ALLOY
PACKAGE WEIGHT	16.0g