

---

### Silicon PIN Photodiode

---


#### Description

S153P is a high speed and high sensitive PIN photodiode in a hermetically sealed short TO-5 package.

Due to its flat, waterclear glass window the device is sensitive to visible and near infrared radiation. The large active area combined with a flat case gives a high sensitivity at a wide viewing angle.

#### Features

- High photo sensitivity
- Large radiant sensitive area  $A=7.5 \text{ mm}^2$
- Fast response times
- Small junction capacitance
- For photodiode and photovoltaic operation
- Hermetically sealed case
- Wide angle of half sensitivity  $\varphi = \pm 55^\circ$
- Suitable for visible and near infrared radiation
- Suitable to couple with glass fiber



94 8482

#### Applications

Applications requiring high speed and high sensitive PIN photodiodes in hermetically sealed packages.

### Absolute Maximum Ratings

 $T_{amb} = 25^{\circ}\text{C}$ 

Parameter	Test Conditions	Symbol	Value	Unit
Reverse Voltage		$V_R$	50	V
Power Dissipation	$T_{amb} \leq 50^{\circ}\text{C}$	$P_V$	300	mW
Junction Temperature		$T_j$	125	$^{\circ}\text{C}$
Operating Temperature Range		$T_{amb}$	-55...+125	$^{\circ}\text{C}$
Soldering Temperature	$t \leq 5\text{ s}$	$T_{sd}$	260	$^{\circ}\text{C}$
Thermal Resistance Junction/Ambient		$R_{thJA}$	250	K/W

### Basic Characteristics

 $T_{amb} = 25^{\circ}\text{C}$ 

Parameter	Test Conditions	Symbol	Min	Typ	Max	Unit
Breakdown Voltage	$I_R = 100\ \mu\text{A}, E = 0$	$V_{(BR)}$	50			V
Reverse Dark Current	$V_R = 10\ \text{V}, E = 0$	$I_{ro}$		2	30	nA
Diode Capacitance	$V_R = 0\ \text{V}, f = 1\ \text{MHz}, E = 0$	$C_D$		75		pF
Diode Capacitance	$V_R = 3\ \text{V}, f = 1\ \text{MHz}, E = 0$	$C_D$		25	40	pF
Open Circuit Voltage	$E_A = 1\ \text{klx}$	$V_o$		350		mV
Temp. Coefficient of $V_o$	$E_A = 1\ \text{klx}$	$TK_{V_o}$		-2.6		mV/K
Short Circuit Current	$E_A = 1\ \text{klx}$	$I_k$		80		$\mu\text{A}$
Short Circuit Current	$E_e = 1\ \text{mW}/\text{cm}^2, \lambda = 950\ \text{nm}$	$I_k$		47		$\mu\text{A}$
Temp. Coefficient of $I_k$	$E_A = 1\ \text{klx}$	$TK_{I_k}$		0.18		%/K
Reverse Light Current	$E_A = 1\ \text{klx}, V_R = 5\ \text{V}$	$I_{ra}$		85		$\mu\text{A}$
Reverse Light Current	$E_e = 1\ \text{mW}/\text{cm}^2, \lambda = 950\ \text{nm}, V_R = 5\ \text{V}$	$I_{ra}$	40	50		$\mu\text{A}$
Absolute Spectral Sensitivity	$V_R = 5\ \text{V}, \lambda = 900\ \text{nm}$	$s(\lambda)$		0.6		A/W
Angle of Half Sensitivity		$\phi$		$\pm 55$		deg
Wavelength of Peak Sensitivity		$\lambda_p$		900		nm
Range of Spectral Bandwidth		$\lambda_{0.5}$		600...1050		nm
Noise Equivalent Power	$V_R=10\text{V}, \lambda=950\text{nm}$	NEP		$4.2 \times 10^{-14}$		$\text{W}/\sqrt{\text{Hz}}$
Rise Time	$V_R=10\text{V}, R_L=1\text{k}\Omega, \lambda=820\text{nm}$	$t_r$		100		ns
Fall Time	$V_R=10\text{V}, R_L=1\text{k}\Omega, \lambda=820\text{nm}$	$t_f$		100		ns

## Typical Characteristics ( $T_{amb} = 25^{\circ}\text{C}$ unless otherwise specified)




Figure 1 : Reverse Dark Current vs. Ambient Temperature




Figure 2 : Relative Reverse Light Current vs. Ambient Temperature




Figure 3 : Reverse Light Current vs. Irradiance




Figure 4 : Reverse Light Current vs. Illuminance




Figure 5 : Reverse Light Current vs. Reverse Voltage




Figure 6 : Diode Capacitance vs. Reverse Voltage




Figure 7 : Relative Spectral Sensitivity vs. Wavelength





Figure 8 : Relative Radiant Sensitivity vs. Angular Displacement

Dimensions in mm



**We reserve the right to make changes to improve technical design without further notice.**

Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer. Should the buyer use TEMIC products for any unintended or unauthorized application, the buyer shall indemnify TEMIC against all claims, costs, damages, and expenses, arising out of, directly or indirectly, any claim of personal damage, injury or death associated with such unintended or unauthorized use.

TEMIC TELEFUNKEN microelectronic GmbH, P.O.B. 3535, D-74025 Heilbronn, Germany  
 Telephone: 49 (0)7131 67 2831, Fax Number: 49 (0)7131 67 2423