

---

### Silicon NPN Phototransistor


---

#### Description

TEFT4300 is a high speed and high sensitive silicon NPN epitaxial planar phototransistor in a standard T-1 ( $\varnothing$  3 mm) plastic package.

The epoxy package itself is an IR filter, spectrally matched to GaAs IR emitters with  $\lambda_p \geq 900\text{nm}$ .

The plastic lens provides a wide viewing angle of  $\pm 30^\circ$ .



94 8637

#### Features

- High radiant sensitivity
- Fast response times
- T1 ( $\varnothing$  3 mm) plastic package with IR filter
- Additional polarity sign
- Wide viewing angle  $\varphi = \pm 30^\circ$
- Suitable for near infrared radiation
- Matches with TSUS 4300 GaAs infrared emitter

#### Applications

Optical switches  
Counters and sorters  
Interrupters  
Tape and card readers  
Encoders  
Position sensors

### Absolute Maximum Ratings

 $T_{amb} = 25^{\circ}\text{C}$ 

Parameter	Test Conditions	Symbol	Value	Unit
Collector Emitter Voltage		$V_{CEO}$	70	V
Emitter Collector Voltage		$V_{ECO}$	5	V
Collector Current		$I_C$	50	mA
Peak Collector Current	$t_p/T = 0.5, t_p \leq 10 \text{ ms}$	$I_{CM}$	100	mA
Total Power Dissipation	$T_{amb} \leq 55^{\circ}\text{C}$	$P_{tot}$	100	mW
Junction Temperature		$T_j$	100	$^{\circ}\text{C}$
Storage Temperature Range		$T_{stg}$	-55...+100	$^{\circ}\text{C}$
Soldering Temperature	$t \leq 3 \text{ s}, 2 \text{ mm from case}$	$T_{sd}$	260	$^{\circ}\text{C}$
Thermal Resistance Junction/Ambient		$R_{thJA}$	450	K/W

### Basic Characteristics

 $T_{amb} = 25^{\circ}\text{C}$ 

Parameter	Test Conditions	Symbol	Min	Typ	Max	Unit
Collector Emitter Breakdown Voltage	$I_C = 1 \text{ mA}$	$V_{(BR)CEO}$	70			V
Collector Dark Current	$V_{CE} = 20 \text{ V}, E = 0$	$I_{CEO}$		1	200	nA
Collector Emitter Capacitance	$V_{CE} = 5 \text{ V}, f = 1 \text{ MHz}, E=0$	$C_{CEO}$		3		pF
Collector Light Current	$E_e = 1 \text{ mW/cm}^2, \lambda = 950 \text{ nm}, V_{CE} = 5 \text{ V}$	$I_{ca}$	0.8	3.2		mA
Angle of Half Sensitivity		$\varphi$		$\pm 30$		deg
Wavelength of Peak Sensitivity		$\lambda_p$		925		nm
Range of Spectral Bandwidth		$\lambda_{0.5}$		875...1000		nm
Collector Emitter Saturation Voltage	$E_e = 1 \text{ mW/cm}^2, \lambda = 950 \text{ nm}, I_C = 0.1 \text{ mA}$	$V_{CEsat}$			0.3	V
Turn-On Time	$V_S = 5 \text{ V}, I_C = 5 \text{ mA}, R_L = 100 \Omega$	$t_{on}$		2.0		$\mu\text{s}$
Turn-Off Time	$V_S = 5 \text{ V}, I_C = 5 \text{ mA}, R_L = 100 \Omega$	$t_{off}$		2.3		$\mu\text{s}$
Cut-Off Frequency	$V_S = 5 \text{ V}, I_C = 5 \text{ mA}, R_L = 100 \Omega$	$f_c$		180		kHz

## Typical Characteristics ( $T_{amb} = 25^{\circ}\text{C}$ unless otherwise specified)




Figure 1 : Total Power Dissipation vs. Ambient Temperature




Figure 2 : Collector Dark Current vs. Ambient Temperature




Figure 3 : Relative Collector Current vs. Ambient Temperature




Figure 4 : Collector Light Current vs. Irradiance




Figure 5 : Collector Light Current vs. Collector Emitter Voltage






Figure 6 : Collector Emitter Capacitance vs. Collector Emitter Voltage




94 8293

Figure 7 : Turn On/Turn Off Time vs. Collector Current



94 8306


Figure 8 : Relative Spectral Sensitivity vs. Wavelength



94 8303

Figure 9 : Relative Radiant Sensitivity vs. Angular Displacement

## Dimensions in mm



**We reserve the right to make changes to improve technical design without further notice.**  
 Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer. Should the buyer use TEMIC products for any unintended or unauthorized application, the buyer shall indemnify TEMIC against all claims, costs, damages, and expenses, arising out of, directly or indirectly, any claim of personal damage, injury or death associated with such unintended or unauthorized use.

TEMIC TELEFUNKEN microelectronic GmbH, P.O.B. 3535, D-74025 Heilbronn, Germany  
 Telephone: 49 (0)7131 67 2831, Fax Number: 49 (0)7131 67 2423