

Silicon NPN Phototransistor

Description

TEMT370. series are high speed silicon NPN epitaxial planar phototransistors in a miniature PL-CC-2 package for surface mounting on printed boards. Due to their waterclear epoxy the devices are sensitive to visible and near infrared radiation.

Features

- PL-CC-2 SMD package
- Extra wide viewing angle $\varphi = \pm 60^\circ$
- Package notch = collector
- Base terminal not connected
- Fast response times
- Suitable for visible and near infrared radiation
- Matches with TSMS 3700 IR emitter



94 8553

Applications

Miniature switches
Counters and sorters
Interrupters
Tape and card readers
Encoders
Position sensors

Absolute Maximum Ratings

 $T_{amb} = 25^{\circ}\text{C}$

Parameter	Test Conditions	Symbol	Value	Unit
Collector Emitter Voltage		V_{CEO}	70	V
Emitter Collector Voltage		V_{ECO}	5	V
Collector Current		I_C	50	mA
Peak Collector Current	$t_p/T \leq 0.1, t_p \leq 10\mu\text{s}$	I_{CM}	100	mA
Total Power Dissipation	$T_{amb} \leq 55^{\circ}\text{C}$	P_{tot}	100	mW
Junction Temperature		T_j	100	$^{\circ}\text{C}$
Storage Temperature Range		T_{stg}	-55...+100	$^{\circ}\text{C}$
Soldering Temperature	$t \leq 3\text{ s}$	T_{sd}	260	$^{\circ}\text{C}$
Thermal Resistance Junction/Ambient		R_{thJA}	450	K/W

Basic Characteristics

 $T_{amb} = 25^{\circ}\text{C}$

Parameter	Test Conditions	Symbol	Min	Typ	Max	Unit
Collector Emitter Breakdown Voltage	$I_C = 1\text{ mA}$	$V_{(BR)CEO}$	70			V
Collector Dark Current	$V_{CE} = 20\text{ V}, E = 0$	I_{CEO}		1	200	nA
Collector Emitter Capacitance	$V_{CE} = 5\text{ V}, f = 1\text{ MHz}, E=0$	C_{CEO}		3		pF
Angle of Half Sensitivity		ϕ		± 60		deg
Wavelength of Peak Sensitivity		λ_p		830		nm
Range of Spectral Bandwidth		$\lambda_{0.5}$		620...980		nm
Collector Emitter Saturation Voltage	$E_e=1\text{mW/cm}^2, \lambda=950\text{nm}, I_C=0.1\text{mA}$	V_{CEsat}		0.15	0.3	V
Rise Time / Fall Time	$V_S=5\text{V}, I_C=1\text{mA}, \lambda=950\text{nm}, R_L=1\text{k}\Omega$	t_r / t_f		6		μs
Rise Time / Fall Time	$V_S=5\text{V}, I_C=1\text{mA}, \lambda=950\text{nm}, R_L=100\Omega$	t_r / t_f		2		μs
Cut-Off Frequency	$V_S=5\text{V}, I_C=2\text{mA}, R_L=100\Omega$	f_c		180		kHz

Type Dedicated Characteristics

 $T_{amb} = 25^{\circ}\text{C}$

Parameter	Type	Test Conditions	Symbol	Min	Typ	Max	Unit
Collector Light Current	TEMT 3700	$E_e=1\text{mW/cm}^2, \lambda=950\text{nm}, V_{CE}=5\text{V}$	I_{ca}	0.25			mA
	TEMT 3703		I_{ca}	0.25	0.4	0.5	mA
	TEMT 3704		I_{ca}	0.4	0.6	0.8	mA
	TEMT 3705		I_{ca}	0.6			mA

Typical Characteristics ($T_{amb} = 25^{\circ}\text{C}$ unless otherwise specified)




Figure 1 : Total Power Dissipation vs. Ambient Temperature




Figure 2 : Collector Dark Current vs. Ambient Temperature




Figure 3 : Relative Collector Current vs. Ambient Temperature




Figure 4 : Collector Light Current vs. Irradiance




Figure 5 : Collector Light Current vs. Collector Emitter Voltage




Figure 6 : Collector Emitter Capacitance vs. Collector Emitter Voltage

TEMT 370.




Figure 7 : Turn On/Turn Off Time vs. Collector Current




Figure 8 : Relative Spectral Sensitivity vs. Wavelength





Figure 9 : Relative Radiant Sensitivity vs. Angular Displacement

Dimensions in mm



We reserve the right to make changes to improve technical design without further notice.

Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer. Should the buyer use TEMIC products for any unintended or unauthorized application, the buyer shall indemnify TEMIC against all claims, costs, damages, and expenses, arising out of, directly or indirectly, any claim of personal damage, injury or death associated with such unintended or unauthorized use.

TEMIC TELEFUNKEN microelectronic GmbH, P.O.B. 3535, D-74025 Heilbronn, Germany
 Telephone: 49 (0)7131 67 2831, Fax Number: 49 (0)7131 67 2423