


GaAlAs IR Emitting Diode in Hermetically Sealed TO18 Case

Description

TSTA 7500 is a high efficiency infrared emitting diode in GaAlAs on GaAlAs technology in a hermetically sealed TO-18 package. Its flat glass window makes it ideal for use with external optics.

Features

- High radiant power
- Suitable for pulse operation
- Wide angle of half intensity $\phi = \pm 30^\circ$
- Peak wavelength $\lambda_p = 875 \text{ nm}$
- High reliability
- Good spectral matching to Si photodetectors




94 8400

Applications

Radiation source in near infrared range

Dimensions in mm



Absolute Maximum Ratings

 $T_{amb} = 25^{\circ}\text{C}$

Parameter	Test Conditions	Symbol	Value	Unit
Reverse Voltage		V_R	5	V
Forward Current		I_F	100	mA
Peak Forward Current	$t_p/T=0.5, t_p \leq 100 \mu\text{s}$	I_{FM}	200	mA
Surge Forward Current	$t_p \leq 100 \mu\text{s}$	I_{FSM}	2.5	A
Power Dissipation		P_V	170	mW
Power Dissipation	$T_{case} \leq 25^{\circ}\text{C}$	P_V	500	mW
Junction Temperature		T_j	100	$^{\circ}\text{C}$
Storage Temperature Range		T_{stg}	-55...+100	$^{\circ}\text{C}$
Thermal Resistance Junction/Ambient		R_{thJA}	450	K/W
Thermal Resistance Junction/Case		R_{thJC}	150	K/W

Basic Characteristics

 $T_{amb} = 25^{\circ}\text{C}$

Parameter	Test Conditions	Symbol	Min	Typ	Max	Unit
Forward Voltage	$I_F = 100 \text{ mA}, t_p \leq 20 \text{ ms}$	V_F		1.4	1.8	V
Breakdown Voltage	$I_R = 100 \mu\text{A}$	$V_{(BR)}$	5			V
Junction Capacitance	$V_R = 0 \text{ V}, f = 1 \text{ MHz}, E = 0$	C_j		40		pF
Radiant Intensity	$I_F = 100 \text{ mA}, t_p \leq 20 \text{ ms}$	I_e	3.5	6		mW/sr
Radiant Power	$I_F = 100 \text{ mA}, t_p \leq 20 \text{ ms}$	ϕ_e		10		mW
Temp. Coefficient of ϕ_e	$I_F = 100 \text{ mA}$	TK_{ϕ_e}		-0.7		%/K
Angle of Half Intensity		ϕ		± 30		deg
Peak Wavelength	$I_F = 100 \text{ mA}$	λ_p		875		nm
Spectral Bandwidth	$I_F = 100 \text{ mA}$	$\Delta\lambda$		80		nm
Rise Time	$I_F=1.5\text{A}, t_p/T=0.01, t_p \leq 10\mu\text{s}$	t_r		300		ns
Fall Time	$I_F=1.5\text{A}, t_p/T=0.01, t_p \leq 10\mu\text{s}$	t_f		300		ns

Typical Characteristics ($T_{amb} = 25^{\circ}\text{C}$ unless otherwise specified)




Figure 1 : Power Dissipation vs. Ambient Temperature




Figure 2 : Forward Current vs. Ambient Temperature




Figure 3 : Pulse Forward Current vs. Pulse Duration




Figure 4 : Forward Current vs. Forward Voltage




Figure 5 : Relative Forward Voltage vs. Ambient Temperature




Figure 6 : Radiant Intensity vs. Forward Current




Figure 7 : Radiant Power vs. Forward Current




Figure 8 : Rel. Radiant Intensity/Power vs. Ambient Temperature




Figure 9 : Relative Radiant Power vs. Wavelength




Figure 10 : Relative Radiant Intensity vs. Angular Displacement

We reserve the right to make changes to improve technical design without further notice.

Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer. Should the buyer use TEMIC products for any unintended or unauthorized application, the buyer shall indemnify TEMIC against all claims, costs, damages, and expenses, arising out of, directly or indirectly, any claim of personal damage, injury or death associated with such unintended or unauthorized use.

TEMIC TELEFUNKEN microelectronic GmbH, P.O.B. 3535, D-74025 Heilbronn, Germany
Telephone: 49 (0)7131 67 2831, Fax Number: 49 (0)7131 67 2423