
**Standard Application**


C₁ = Optional ceramic (1-5μF)
 C₂ = Optional ceramic (1-5μF)
 C₃ = Required Electrolytic (100μF)

- Wide Input Voltage Range
- 85% Efficiency
- Internal Over-Temperature Protection
- Laser-trimmed Output Voltage
- Soft Start

The Power Trends' PT5040 Series is a 3-terminal Integrated Switching Regulator (ISR) designed for use with +5 volt systems that require an additional regulated +8 to +20 volts with up to 1A of output current. These ISRs are packaged in the 3 pin SIP configuration.

Pin-Out Information

Pin	Function
1	V _{in}
2	GND
3	V _{out}

**Ordering Information**

PT5041□	= +12 Volts
PT5042□	= +15 Volts
PT5044□	= +8 Volts
PT5045□	= +9 Volts
PT5046□	= +10 Volts
PT5047□	= +18 Volts
PT5048□	= +12.6 Volts
PT5049□	= +20 Volts

PT Series Suffix (PT1234X)**Case/Pin Configuration**

Vertical Through-Hole	N
Horizontal Through-Hole	A
Horizontal Surface Mount	C

NOTE: Boost Topology ISRs are not Short-Circuit Protected.

Specifications


Characteristics (T _a =25°C unless noted)	Symbols	Conditions	PT5040 SERIES				
			Min	Typ	Max	Units	
Output Current	I _o	Over V _{in} range	V _o =20V V _o =18V V _o =12V V _o =15V V _o =8V V _o =9V	0.1* 0.1* 0.1* 0.1* 0.1* 0.1*	— — — — — —	0.5 0.6 1.0 0.75 1.5 1.25	A
Current Limit**	I _{cl}	V _{in} = +5V	—	—	1.5 I _o max	—	A
Inrush Current	I _{ir} t _{ir}	V _{in} = +5V @ max I _o On start up	— —	2.5 1	— —	mSec	A
Input Voltage Range	V _{in}	I _o = 0.1 to I _o max	PT5047/5049	4.75	—	(V _o -1V)	V
				4.75	—	14	V
Output Voltage Tolerance	ΔV _o	Over V _{in} Range I _o = I _{max} , T _a =-20°C to shutdown	—	±1.5	±3.0	%V _o	
Line Regulation	Reg _{line}	Over V _{in} range	—	±0.5	±1.0	%V _o	
Load Regulation	Reg _{load}	0.1 ≤ I _o ≤ I _o max	—	±0.5	±1.0	%V _o	
V _o Ripple/Noise	V _n	V _{in} = +5V, I _o =I _o max	—	±2	±5	%V _o	
Transient Response	t _{tr} V _{os}	25% load change V _o over/undershoot	— —	500 3.0	— 5.0	μSec %V _o	
Efficiency	η	V _{in} = +5V, I _o =0.5A, V _o = +12V	—	85	—	%	
Switching Frequency	f _o	Over V _{in} and I _o ranges	V _o <15V V _o ≥15V	500 650	650 800	800 950	kHz kHz
Absolute Maximum Operating Temperature Range	T _a	—	—	-20	—	+85	°C
Recommended Operating Temperature Range	T _a	Free Air Convection, (40-60LFM) Over V _{in} and I _o ranges	V _o <15V V _o ≥15V	-20 -20	— —	70*** 55***	°C °C
Thermal Resistance	θ _{ja}	Free Air Convection (40-60LFM)	—	40	—	—	°C/W
Storage Temperature	T _s	—	—	-40	—	+125	°C
Mechanical Shock		Per Mil-STD-883D, Method 2002.3 1 msec, Half Sine, mounted to a fixture	—	500	—	—	G's
Mechanical Vibration		Per Mil-STD-883D, Method 2007.2, 20-2000 Hz, Soldered in a PC Board	—	5	—	—	G's
Weight		—	—	4.5	—	—	grams

* ISR will operate down to no load with reduced specifications.








** Boost topology ISRs are not short circuit protected.

*** See SOA Curves.

PT5041, +12.0 VDC (See Note 1)



PT5042, +15.0 VDC (See Note 1)



Note 1: All data listed in the above graphs has been developed from actual products tested at 25°C. This data is considered typical data for the ISR.