

Data Sheet

Card Transponder



Specifications:

Part number	RI-TRP-R4FF	RI-TRP-W4FF
Functionality	Read Only	Read/Write
Memory (Bits)	64	80*
Memory (Pages)	1	1
Operating Frequency	134.2 kHz	
Modulation	FSK (Frequency Shift Keying) 134.2 kHz / 123.2 kHz	
Transmission Principle	HDX (Half Duplex)	
Power Source	Powered from the reader signal (batteryless)	
Typical Reading Range	≤ 100 cm**	
Typical Programming Range	---	30 % of specified reading range
Typical Reading Time	70 ms	
Typical Programming Time	---	309 ms
Typical Programming Cycles	---	100,000
Operating Temperature	-25 to +50°C (According to ISO 7810)	
Storage Temperature	-25 to +50°C (According to ISO 7810)	
Case Material	PVC (Polyvinylchloride), white, without print	
Chemical Protection	According to ISO 7810	
EMC	Programmed code is not affected by normal electromagnetic interference or x-rays	
Signal Penetration	Transponder can be read through virtually all non-metallic material	
Dimensions	85.5 mm ± 0.4 mm * 54 mm ± 0.4 mm * 1.3 mm ± 0.1 mm	
Weight	12 g	

* We recommend that you split each 80 bit page into 64 user programmable bits plus a 16 bit wide CRC CCITT Block Check Character as is done by TI-RFID LF readers.

** Depending on RF regulation in country of use, the Reader Antenna configuration used, and the environmental conditions.

For more information, contact the sales office or distributor nearest you. This contact information can be found on our web site at: <http://www.ti-rfid.com>

Texas Instruments reserves the right to change its products and services at any time without notice. TI provides customer assistance in various technical areas, but does not have full access to data concerning the uses and applications of customers products. Therefore, TI assumes no responsibility for customer product design or for infringement of patents and/or the rights of third parties, which may result from assistance provided by TI.