

Ordering Information

Commercial Breakers	Precision Breakers
2-40 Amps X - X - I * Configuration CA CM CDA CDM Amp Rating 2, 3, 4, 5, 6, 8, 10, 12 1/2, 15, 17 1/2, 20, 25, 30, 35, 40	2-10 Amps X - X Configuration PSM-N PSM PSA Amp Rating 2, 3, 4, 5, 6, 8, 10
2-50 Amps X - X - X Configuration 6790 Operation 1 - Manual 2 - Automatic Amp Rating 2, 3, 4, 5, 6, 8, 10, 12 1/2, 15, 17 1/2, 20, 25, 30, 35, 40, 45, 50	12 1/2-35 Amps X - X Configuration PSM-N PSM PSA Amp Rating 12 1/2, 15, 17 1/2, 20, 25, 30, 35
12 1/2-60 Amps X - X - X - I * Configuration 7851 Stud Length (Approx) 18 (0.310") 37 (0.455") 13 (0.610") Amp Rating 12 1/2, 15, 17 1/2, 20, 25, 30, 35, 40, 50, 60 7854 18 (0.310") 26 (0.455") 15 (0.610") 12 1/2, 15, 17 1/2, 20, 25, 30, 35, 40, 50, 60	2-40 Amps X - X - I * Configuration PDA PDM Amp Rating 2, 3, 4, 5, 6, 8, 10, 12 1/2, 15, 17 1/2, 20, 25, 30, 35, 40
35-150 Amps X - X - I * Configuration 6766-19 Amp Rating 35, 40, 45, 50, 60, 70, 80, 90, 105, 120, 135, 150	35-150 Amps X - X - I * Configuration PDLA PDLM Amp Rating 35, 40, 45, 50, 60, 70, 80, 90, 105, 120, 135, 150
35-150 Amps X - X - ** Configuration SDLA SDLM Amp Rating 35, 40, 45, 50, 60, 70, 80, 90, 105, 120, 135, 150 **Options 1 - Self locking nuts 2 - No terminal hardware 3 - Self locking nuts and no terminal hardware	175 & 200 Amps X - X Configuration 7855-6 7855-7 Amp Rating 175, 200

* Optional - Denotes mounting nuts

^{**} Leave blank (omit) for standard product without options