


General Purpose Strain Gages - Shear/Torque Pattern

GAGE PATTER	IN DATA					
•		-		GAGE DESIGNATI See Note		
- hallen		to the second se	-	L2A-XX-062LV- C2A-XX-062LV	-120 120 ± 0.6%	
	actual size	4		DESCRIPTION	N 90° torque gage.	Pb-free RoHS COMPLIANT
GAGE DIMENSIONS		Legend: ES = Each Section S = Section (S1 = Sec 1)		CP = Complete PatterninchM = Matrixmillimeter		
Gage Length	Overall Length	Grid Width	Ove	erall Width	Matrix Length	Matrix Width
0.062 ES	0.214 CP	0.050 ES	0	.215 CP	0.255	0.265
1.52 ES	5.44 CP	1.27 ES	Ę	5.46 CP	6.48	6.73

GAGE SERIES DATA See Gage Series data sheet for complete specifications.				
Series	Description	Strain Range	e Temperature Range	
L2A	Encapsulated constantan gages with preattache	ribbon leads. ±3%	-100° to +250°F [-75° to +120°C]	
C2A	Encapsulated constantan gages with preattache	ready-to-use cables. ±3%	-60° to +180°F [-50° to +80°C]	





Vishay Precision Group

Disclaimer

All product specifications and data are subject to change without notice.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay Precision Group"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay Precision Group disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay Precision Group's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay Precision Group.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay Precision Group products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay Precision Group for any damages arising or resulting from such use or sale. Please contact authorized Vishay Precision Group personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.