




Diaphragm Patterns - Circular

Transducer-Class® Strain Gages

GAGE PATTERN	Actual size shown. Enlarged when necessary for definition.		GAGE DESIGNATION See Note 1	RES. IN OHMS	STANDARD CREEP CODE	ENCAPSULATION OPTION AVAILABLE
	DIMENSIONS	inch millimeter				

				Similar to a 182JB/JC pattern.			
PATTERN DIAMETER	CIRCULAR TRIM DIAMETER†	MIN. DIAPHRAGM DIAMETER	MATRIX SIZE-(SQUARE)				
0.182	0.200	0.210	0.23				
4.62	5.08	5.3	5.8				
MATRIX SIZE	0.23 L x 0.23 W		5.8 L x 5.8 W		EA-XX-S067F-350 N2A-XX-S067F-350	350 ± 1.0% 350 ± 1.0%	F* F* E3

				Similar to a 228JB/JC pattern.			
PATTERN DIAMETER	CIRCULAR TRIM DIAMETER†	MIN. DIAPHRAGM DIAMETER	MATRIX SIZE-(SQUARE)				
0.228	0.250	0.260	0.30	EA-XX-S102H-350 N2A-XX-S102H-350	350 ± 1.0% 350 ± 1.0%	H* H*	
5.79	6.35	6.6	7.6	N2K-XX-S066H-350/DP TK-XX-S066H-350/DP	350 ± 1.0% 350 ± 1.0%	H* H*	
MATRIX SIZE	0.30 L x 0.30 W		7.6 L x 7.6 W		SK-XX-S066H-350	350 ± 2.0%	H* E2 E2 E2


				Similar to a 364JB/JC pattern.			
PATTERN DIAMETER	CIRCULAR TRIM DIAMETER†	MIN. DIAPHRAGM DIAMETER	MATRIX SIZE-(SQUARE)				
0.364	0.400	0.410	0.46	EA-XX-S050P-350 N2A-XX-S050P-350	350 ± 0.5% 350 ± 0.5%	P* P*	
9.25	10.16	10.4	11.7	N2K-XX-S060P-350/DP TK-XX-S060P-350/DP	350 ± 0.5% 350 ± 0.5%	P* P*	
MATRIX SIZE	0.46 L x 0.46 W		11.7 L x 11.7 W		SK-XX-S060P-350	350 ± 0.5%	P* E2 E2 E2

*Only creep code available for this gage type.

Note 1: Products shown in bold are not RoHS compliant.

Transducer-Class® Strain Gages

GAGE PATTERN	Actual size shown. Enlarged when necessary for definition.	GAGE DESIGNATION See Note 1	RES. IN OHMS	STANDARD CREEP CODE	ENCAPSU- LATION OPTION AVAILABLE
	DIMENSIONS				

				Similar to a 455JB/JC pattern.			
PATTERN DIAMETER	CIRCULAR TRIM DIAMETER†	MIN. DIAPHRAGM DIAMETER	MATRIX SIZE- (SQUARE)	EA-XX-S046R-350	350 ± 0.5%	R*	E2
0.455	0.500	0.510	0.58	EA-XX-S070R-10C	1000 ± 0.5%	R*	E2
11.56	12.70	13.0	14.7	N2A-XX-S046R-350	350 ± 0.5%	R*	E2
				N2A-XX-S070R-10C	1000 ± 0.5%	R*	E2
MATRIX SIZE	0.58 L x 0.58 W	14.7 L x 14.7 W		N2K-XX-S073R-350/DP	350 ± 0.5%	R*	E2
				TK-XX-S073R-350/DP	350 ± 0.5%	R*	E2
				SK-XX-S073R-350	350 ± 1.0%	R*	

†Option SP70, factory trimmed to this dimension ± 0.005 in (0.13mm) is available on the EA-, N2A-, and N2K-Series diaphragm gages.

*Only creep code available for this gage type.

Note 1: Products shown in bold are not RoHS compliant.

Disclaimer

All product specifications and data are subject to change without notice.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay Precision Group"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay Precision Group disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay Precision Group's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay Precision Group.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay Precision Group products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay Precision Group for any damages arising or resulting from such use or sale. Please contact authorized Vishay Precision Group personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.