



MATERIAL SAFETY DATA SHEET



SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT: EPY-500 Part B

April 13, 2010

Vishay Measurements Group, Inc.
Post Office Box 27777
Raleigh, NC 27611

919-365-3800

CHEMTREC 1-800-424-9300 (U.S.)
703-527-3887 (Outside U.S.)

NOTE: CHEMTREC numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.

SECTION 2: HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

CAS NUMBER	CHEMICAL IDENTITY	%
89-32-7	Pyromellitic Dianhydride	<87
14807-96-6	Magnesium Silicate Talc	<23
89-05-4	1,2,4,5-Benzenetetracarboxylic Acid	1-5
14808-60-7	Quartz (Crystalline Silica)	0.1-1.0

SECTION 3: HEALTH HAZARD DATA

Routes of Entry:

Inhalation: YES Skin: YES Ingestion: Accidental

Health Hazards (Acute and Chronic): Repeated exposure may cause injury to the respiratory tract. Long term inhalation of crystalline silica dusts may cause lung disease (silicosis).

Carcinogenicity:
NTP: See note
IARC Monographs: See note
OSHA Regulated: Not listed

NOTE: Crystalline silica has been classified as a probable human carcinogen by IARC.

Signs and Symptoms of Exposure:

INHALATION: May cause allergic respiratory reaction.

EYE CONTACT: Dust should be considered slightly to moderately irritating.

SKIN CONTACT: Causes skin irritation.

INGESTION: May cause gastro-intestinal irritation.

Conditions Generally Aggravated by Exposure: Pre-existing upper respiratory disorders.

SECTION 4: EMERGENCY AND FIRST AID PROCEDURES
--

INHALATION: Move victim out of exposure area immediately. If breathing is difficult give oxygen. If not breathing, give artificial respiration. Consult a physician immediately.

EYE CONTACT: Immediately flush eyes with plenty of water for at least 15 minutes. Consult a physician immediately.

SKIN CONTACT: Immediately flush skin with soap and plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Wash and thoroughly clean contaminated clothing and shoes before reuse. Consult a physician.

INGESTION: If swallowed, consult a physician. Never give anything by mouth to an unconscious person.

SECTION 5: FIRE AND EXPLOSION HAZARD DATA
--

Flash Point (Method Used): >200°F (93.3°C)

Flammable limits: LEL: Not determined UEL: Not determined

Extinguishing Media: Foam, carbon dioxide, dry chemical and vaporizing water mists have all been found suitable for use on fires of moderate size.

Special Firefighting Procedures: Use self-contained breathing apparatus and protective clothing. Remove all ignition sources. Keep personnel not involved with emergency activities away and upwind of fire. Do not use a solid water stream as it may scatter and spread fire. Water may be used to cool closed containers.

Unusual Fire and Explosion Hazards: Dust may form explosive mixtures in air. The pressure in sealed containers can increase under the influence of fire. Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Steps to be taken if material is released or spilled: Remove all sources of ignition. Ventilate area. Sweep or vacuum and place into closable container for disposal, avoiding dusty conditions. Wear protective equipment during cleanup.

SECTION 7: EXPOSURE CONTROLS -- PERSONAL PROTECTION

Respiratory Protection: Wear an appropriate, properly-fitted respirator (NISOH/MSHA approved) during and after application unless air monitoring demonstrated that vapor/mist levels are below applicable limits.

Ventilation: Use with adequate ventilation. Provide general dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below the applicable exposure limit.

Protective Gloves: Impervious type gloves are required.

Eye Protection: Use safety eyewear designed to protect against splash of liquids.

Other Protective Clothing or Equipment: Impervious clothing as needed to minimize skin contact.

Work / Hygienic Practices: Wash thoroughly after use and before eating, drinking or smoking. Emergency eyewash and safety shower should be available.

SECTION 8: HANDLING AND STORAGE

Precautions to be taken in handling and storing: Do not store above 120°F (48.9°C). Keep closure tight and container upright to prevent leakage. Store container out of sunlight and away from heat, sparks, and flames. Store only in well-ventilated areas.

Other Precautions: Containers may be hazardous when empty. Empty containers may retain product residue (vapor, liquid, or solid).

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point:	752°F (>400°C)
Vapor Pressure (mmHg):	N/A
Vapor Density (Air = 1):	N/A
Specific Gravity (H₂O = 1):	1.81
Melting Point:	Not known
Evaporation Rate (BuAc = 1):	N/A
Volatile Organic Compounds:	0%
Solubility in Water:	Slightly soluble in water

Appearance and Odor: White to tan colored powder; odorless.

SECTION 10: STABILITY AND REACTIVITY DATA

Stability: Stable under normal conditions of use and storage.

Conditions to Avoid: Open flame, sparks, or high temperature.

Incompatibility (Materials to Avoid): Acids and bases. Strong oxidizing agents.

Hazardous Decomposition or By-products: Carbon dioxide, carbon monoxide and toxic vapors.

Hazardous Polymerization: Will not occur.

SECTION 11: TOXICOLOGICAL INFORMATION

Pyromellitic Dianhydride

OSHA PEL:	3 mg/m ³ (Respirable dust)
ACGIH TLV:	3 mg/m ³ (Respirable dust)
OTHER:	LD ₅₀ (ORAL-MOUSE) 2.4 mg/kg

Quartz

OSHA PEL:	0.1 mg/m ³ TWA (Respirable dust)
ACGIH TLV:	0.05
OTHER:	N/E

Magnesium Silicate Talc

OSHA PEL:	N/E
ACGIH TLV:	2.0 mg/m ³
OTHER:	

1,2,4,5-Benzenetetracarboxylic Acid

OSHA PEL:	N/E
ACGIH TLV:	N/E
OTHER:	N/E

SECTION 12: DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose of in accordance with all local, state and federal regulations.

SECTION 13: TRANSPORTATION INFORMATION

SHIPPING NAME

CLASS

UN NUMBER

Not Required -- Non-hazardous for transportation.

SECTION 14: REGULATORY INFORMATION

SECTION 313 SUPPLIER NOTIFICATION:

This product contains a toxic chemical or chemicals (as listed below) subject to the reporting requirements of Section 313 Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR Part 372.

CAS NUMBER

CHEMICAL NAME

% BY WEIGHT

None Listed

TSCA NOTIFICATION:

All components of this product are listed in the Toxic Substance Control Act Chemical Substance Inventory (TSCA).

CALIFORNIA PROPOSITION 65 STATUS

WARNING: This product contains a chemical known to the State of California to cause cancer.

SECTION 15: OTHER INFORMATION

To the best of our knowledge, the information provided above meets the requirements of the United States Occupational Safety and Health Act and regulations established under 29 CFR 1910.1200 (g)(2)(c)(1)-(4) for a mixture of hazardous chemicals which has not been tested as a whole. The data provided on this Material Safety Data Sheet is from manufacturers of the original components. Micro-Measurements specifically disclaims any and all form of liability and/or responsibility for the application of this product.