# **EMEME** Micro-Measurements



# **Strain Gage Cement**



### OTHER ACCESSORIES USED IN AN H CEMENT INSTALLATION:

- CSM Degreaser or GC-6 Isopropyl Alcohol
- Silicon-Carbide Paper
- M-Prep Conditioner A
- M-Prep Neutralizer 5A
- GSP-1 Gauze Sponges
- GT-11 Camel's Hair Brush
- SPT-1 Double Blade Spatula
- H Cement Thinner

#### **DESCRIPTION**

Single-part ceramic cement/coating. Excellent electrical-insulation properties, even at +1600°F [+870°C]. Good adhesion to most metals.

### **CHARACTERISTICS**

## **Operating Temperature Range:**

-452° to +1600°F [-269° to +870°C].

#### **Elongation Capabilities:**

0.5% at +75°F [+24°C].

#### Shelf Life:

Minimum 1 year at +75°F [+24°C].

#### Pot Life:

Minimum 1 year at +75°F [+24°C].

#### **Temperature Coefficient of Expansion**

7.0ppm/°F [13ppm/°C].

### **Cure Requirements:**

#### Precoat:

Air-dry 30 minutes at +75°F [+24°C], then 30 minutes at +200°F [95°C] followed by 30 minutes at 350°F [177°C].

## **Final Coat:**

Air-dry 30 minutes at  $+75^{\circ}F$  [ $+24^{\circ}C$ ], then 30 minutes at  $+200^{\circ}F$  [ $95^{\circ}C$ ] followed by 30 minutes at  $350^{\circ}F$  [ $177^{\circ}C$ ], and final 1 hour at  $+600^{\circ}F$  [ $+315^{\circ}C$ ].

# **PACKAGING OPTIONS**

#### Kits:

1 bottle [1oz/30ml] Cement

H Cement Kit A: 2 bottles [1oz/30ml] Cement

- 1 bottle [0.5oz/15ml] Thinner
- 1 bottle [2oz/60ml] Conditioner A
- 1 bottle [2oz/60ml] Neutralizer 5A
- 1 package 100-count CSP-1 Cotton Swabs
- 1 package 200-count GSP-1 Gauze

**Sponges** 

12 sheets [2in x 4.5in/50mm x 115mm] of 400-grit Silicon-Carbide Paper

H Cement Kit B: Same as H Cement Kit A except 6 bottles [1oz/30ml] Cement

www.micro-measurements.com

For technical questions, contact: <u>micro-measurements@vishaypg.com</u>

Document Number: 11108 Revision: 24-Jun-10

# **Legal Disclaimer Notice**



Vishay Precision Group

# **Disclaimer**

All product specifications and data are subject to change without notice.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay Precision Group"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay Precision Group disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay Precision Group's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay Precision Group.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay Precision Group products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay Precision Group for any damages arising or resulting from such use or sale. Please contact authorized Vishay Precision Group personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Document Number: 63999 www.vishaypg.com Revision: 22-Feb-10