

MATERIAL SAFETY DATA SHEET



SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT: Neutra-Sol April 14, 2010

Vishay Measurements Group, Inc. Post Office Box 27777 Raleigh, NC 27611

919-365-3800

CHEMTREC 1-800-424-9300 (U.S.)

703-527-3887 (Outside U.S.)

NOTE: CHEMTREC numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.

SECTION 2: HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

CAS NUMBER	CHEMICAL IDENTITY	%
1336-21-6	Ammonium Hydroxide	<0.02
7601-54-9	Trisodium Phosphate	< 0.05
1303-96-4	Sodium Tetraborate Pentahydrate	<0.01
7732-18-5	Distilled Water	99.92

SECTION 3: HEALTH HAZARD DATA

Routes of Entry:

Inhalation: Yes Skin: Yes Ingestion: Accidental

Health Hazards (Acute and Chronic): Ammonium hydroxide is irritating and corrosive to body tissues and a sensitized person may react to even dilute solutions.

Carcinogenicity: NTP: Not listed

IARC Monographs: Not listed OSHA Regulated: Not listed

DOCUMENT NO.: 14087 PAGE 1 OF 5 REVISION: H

Neutra-Sol MSDS (Continued)

Signs and Symptoms of Exposure:

INHALATION: May cause headache, coughing, and possible lung damage (edema and difficulty in breathing). Excessive inhalation of vapors is irritating to the mucous membranes of the respiratory tract.

EYE CONTACT: May cause possible burning and reddening. Liquid contact to the eye can be severely damaging and can result in the loss of vision.

SKIN CONTACT: May cause irritation, reddening, and possible burns.

INGESTION: May cause possible burning sensation. Ingestion is corrosive to the digestive tract.

Conditions Generally Aggravated by Exposure: Preclude from exposure anyone with eye or pulmonary disease.

SECTION 4: EMERGENCY AND FIRST AID PROCEDURES

INHALATION: Remove to fresh air. If breathing is difficult have a trained person administer oxygen. Keep warm and at rest, and contact physician promptly.

EYE CONTACT: Immediately flush with plenty of water for at least 15 minutes while holding the eyelids open. Contact physician, preferably an ophthalmologist.

SKIN CONTACT: Flush with plenty of water while removing contaminated clothing. Wash affected area with soap and water. Launder contaminated clothing before reuse. Seek medical aid if irritation persists.

INGESTION: If conscious, promptly give lots of water, dilute vinegar, or citrus juice to drink, followed by milk. Do <u>NOT</u> induce vomiting. Contact physician.

SECTION 5: FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used): None

Flammable limits: LEL: NA UEL: NA

Extinguishing Media: Will not support combustion.

Special Firefighting Procedures: Use media appropriate to surrounding fire conditions. Use cold water spray to control vapors and cool fire exposed containers.

Unusual Fire and Explosion Hazards: When heated, material will emit anhydrous ammonia vapor which necessitates respiratory and eye protection for firefighting. Use protective clothing.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Steps to be taken if material is released or spilled: Ventilate area. Take up with absorbent material. Neutralize with dilute acid. Flush spill area with plenty of water.

SECTION 7: EXPOSURE CONTROLS -- PERSONAL PROTECTION

Respiratory Protection: For air contaminants above TLV or permissible limits use NIOSH approved respirator for organic vapors.

Ventilation:

Local Exhaust: Keep below TLV Mechanical: Keep below TLV

Special: NA Other: NA

Protective Gloves: Neoprene or rubber gloves are recommended.

Eye Protection: Full face shield or chemical safety goggles are recommended.

Other Protective Clothing or Equipment: Rubber apron is recommended. Safety shower and eyewash should be available in work area.

Work / Hygienic Practices: Use good housekeeping practices. Wash thoroughly after use.

SECTION 8: HANDLING AND STORAGE

Precautions to be taken in handling and storing: Store below 80°F (27°C) in dry place. Keep containers tightly sealed.

Other Precautions: Avoid breathing vapors and direct contact.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point: 212°F (100°C) **Vapor Pressure (mmHg)**: 760 mgHg at 100°C

Vapor Density (Air = 1): 1.0 Specific Gravity ($H_2O = 1$): 1.0

Melting Point: 32°F (0°C)

Evaporation Rate (BuAc = 1): <1
Volatile Organic Compounds: 0%
Solubility in Water: 100%

Appearance and Odor: Colorless liquid; mild ammonia odor.

SECTION 10: STABILITY AND REACTIVITY DATA

Stability: Stable.

Conditions to Avoid: Adding Sodium Hydroxide to this material and/or heating will volatize ammonia.

Incompatibility (Materials to Avoid): Acids, peroxides, metallic copper, tin, zinc, and their alloys, halogenated

compounds.

Hazardous Decomposition or By-products: None known.

Hazardous Polymerization: Will not occur.

SECTION 11: TOXICOLOGICAL INFORMATION

Ammonium Hydroxide

OSHA PEL: 35 ppm (STEL) ACGIH TLV: 35 ppm (STEL)

OTHER: NA

Trisodium Phosphate

OSHA PEL: Not established ACGIH TLV: Not established OTHER: Not established

Sodium Tetraborate Pentahydrate

OSHA PEL: Not established ACGIH TLV: 1 mg/m³
OTHER: NA

Distilled Water

OSHA PEL: Not established ACGIH TLV: Not established OTHER: Not established

SECTION 12: DISPOSAL CONSIDERATIONS

Waste Disposal Method: Neutralize absorbent material with dilute acid. Dispose of in accordance with local, state and federal regulations.

SECTION 13.	 TRANSPORTATION INFORM 	MATION
. 2E(*11(7)) 1.5	I KANSPUKTATION INFORT	VIAIILII

SHIPPING NAME

CLASS PACKING GROUP UN NUMBER

Corrosive Liquids, N.O.S.
(Ammonium Hydroxide)

8 III 1760

SECTION 14: REGULATORY INFORMATION

SECTION 313 SUPPLIER NOTIFICATION:

This product contains a toxic chemical or chemicals (as listed below) subject to the reporting requirements of Section 313 Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR Part 372.

CAS NUMBER CHEMICAL NAME % BY WEIGHT

None

TSCA NOTIFICATION:

All components of this product are listed in the Toxic Substance Control Act Chemical Substance Inventory (TSCA).

SECTION 15: OTHER INFORMATION

To the best of our knowledge, the information provided above meets the requirements of the United States Occupational Safety and Health Act and regulations established under 29 CFR 1910.1200 (g)(2)(c)(1)-(4) for a mixture of hazardous chemicals which has not been tested as a whole. The data provided on this Material Safety Data Sheet is from manufacturers of the original components. Micro-Measurements specifically disclaims any and all form of liability and/or responsibility for the application of this product.