



MATERIAL SAFETY DATA SHEET



SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT: RTV 3140

April 13, 2010

Vishay Measurements Group, Inc.
Post Office Box 27777
Raleigh, NC 27611

919-365-3800

CHEMTREC 1-800-424-9300 (U.S.)
703-527-3887 (Outside U.S.)

NOTE: CHEMTREC numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.

SECTION 2: HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

CAS NUMBER	CHEMICAL IDENTITY	%
1185-55-3	Methyltrimethoxysilane	5-10
68909-20-6	Trimethylated silica	10-30
70131-67-8	Dimethyl siloxane, hydroxy-terminated	>60.0

NOTE: Methyl alcohol forms on contact with water or humid air.

SECTION 3: HEALTH HAZARD DATA

Routes of Entry:

Inhalation: YES Skin: YES Ingestion: Accidental

Health Hazards (Acute and Chronic): Product generates methyl alcohol which may cause blindness and damage to the nervous system.

Carcinogenicity:
NTP: Not Known
IARC Monographs: Not Known
OSHA Regulated: Not Known

NOTE: When heated to temperatures above 355°F (180°C) in the presence of air, product can form formaldehyde vapors. Formaldehyde is a potential cancer hazard, a known skin and respiratory sensitizer; and an irritant to the eyes, nose, throat, skin, and digestive system. Safe handling conditions may be maintained by keeping vapor concentrations within the OSHA Permissible Exposure Limit for formaldehyde.

Signs and Symptoms of Exposure:

INHALATION: Vapor may irritate nose and throat. Vapor over-exposure may cause drowsiness. Product generates methyl alcohol which may cause blindness and damage to nervous system.

EYE CONTACT: Direct contact may cause mild irritation.

SKIN CONTACT: No significant irritation expected from a single short-term exposure. Repeated or prolonged exposure may cause irritation.

INGESTION: Product generates methyl alcohol which may cause blindness and possibly death if swallowed. Low ingestion hazard in normal use.

Conditions Generally Aggravated by Exposure: No known applicable information.

SECTION 4: EMERGENCY AND FIRST AID PROCEDURES
--

INHALATION: Remove to fresh air. Get medical attention if ill effects persist.

EYE CONTACT: Immediately flush with water for 15 minutes.

SKIN CONTACT: Wash affected area with soap and water.

INGESTION: Get medical attention.

NOTE: Treat as methyl alcohol poisoning.

SECTION 5: FIRE AND EXPLOSION HAZARD DATA
--

Flash Point (Method Used): >214°F (>101.1°C)

Flammable limits: LEL: Not determined UEL: Not determined

Extinguishing Media: On large fires use dry chemical, foam or water spray. On small fires use carbon dioxide, dry chemical or water spray. Water can be used to cool fire exposed containers.

Special Firefighting Procedures: Self-contained breathing apparatus and protective clothing should be worn in fighting fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool.

Unusual Fire and Explosion Hazards: None.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Steps to be taken if material is released or spilled: Determine whether to evacuate or isolate the area according to your local emergency plan. Observe all personal protection recommendations. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent. Clean area as appropriate since some silicone materials, even in small quantities, may present a slip hazard. Final cleaning may require use of steam, solvents or detergents. Dispose of saturated absorbent or cleaning materials appropriately, since spontaneous heating may occur. Local, state and federal laws may apply to releases and disposal of this material, as well as those materials and items employed in the clean up of releases. Observe all applicable local, state, and federal waste management regulations.

SECTION 7: EXPOSURE CONTROLS -- PERSONAL PROTECTION

Respiratory Protection: Use respiratory protection unless adequate local exhaust ventilation is provided or air sampling data shows exposures are within recommended exposure guidelines. If a respirator is needed, a self-contained breathing apparatus (SCBA) or other air-supplied respirator is recommended.

Ventilation: Local exhaust is recommended.

Protective Gloves: No special protection needed.

Eye Protection: Use proper protection - safety glasses as a minimum.

Other Protective Clothing or Equipment: None required.

Work / Hygienic Practices: Wash thoroughly after use and before eating, drinking or smoking.

NOTE: These precautions are for room temperature handling. Use at elevated temperature, or aerosol/spray applications, may require added precautions.

SECTION 8: HANDLING AND STORAGE

Precautions to be taken in handling and storing: Keep container closed and store away from water or moisture.

Other Precautions: Use with adequate ventilation. Product evolves flammable methyl alcohol when exposed to water or humid air. Provide ventilation during use to control exposure guidelines or use air-supplied or self-contained breathing apparatus. Do not breathe vapor. Keep container closed. Avoid eye contact. Do not take internally.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES
--

Boiling Point:	>150°F (65°C)
Vapor Pressure (mmHg):	Not determined
Vapor Density (Air = 1):	Not determined
Specific Gravity (H₂O = 1):	1.05
Melting Point:	Not applicable
Evaporation Rate (BuAc = 1):	Not known
Volatile Organic Compounds:	Not determined
Solubility in Water:	None

Appearance and Odor: Translucent white liquid; slight odor.

SECTION 10: STABILITY AND REACTIVITY DATA
--

Stability: Stable.

Conditions to Avoid: None.

Incompatibility (Materials to Avoid): Oxidizing material can cause a reaction. Water, moisture, or humid air may cause methyl alcohol vapors to form.

Hazardous Decomposition or By-products: Thermal breakdown of this product during fire or very high heat conditions may evolve the following hazardous decomposition products: Carbon oxides and traces of incompletely burned carbon compounds. Silicon dioxide. Formaldehyde. Metal Oxides. Nitrogen oxides.

Hazardous Polymerization: Will not occur.

SECTION 11: TOXICOLOGICAL INFORMATION
--

Methyltrimethoxysilane

OSHA PEL:	N/E
ACGIH TLV:	N/E
OTHER:	50 ppm TWA recommended by Dow Corning.

Trimethylated silica

OSHA PEL:	N/E
ACGIH TLV:	N/E
OTHER:	5 mg/m ³ (as dust) recommended by Dow Corning.

Dimethyl siloxane, hydroxy-terminated

OSHA PEL: N/E
ACGIH TLV: N/E
OTHER: N/E

NOTE: Methyl Alcohol forms on contact with water or humid air. Provide adequate ventilation to control exposures within guidelines of OSHA PEL: TWA 200 ppm and ACGIH TLV-Skin: TWA 200 ppm, STEL 250 ppm.

SECTION 12: DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose of in accordance with local, state and federal regulations.

SECTION 13: TRANSPORTATION INFORMATION

SHIPPING NAME	CLASS	UN NUMBER
---------------	-------	-----------

Not required -- Non-hazardous for transportation.

SECTION 14: REGULATORY INFORMATION

SECTION 313 SUPPLIER NOTIFICATION:

This product contains a toxic chemical or chemicals (as listed below) subject to the reporting requirements of Section 313 Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR Part 372.

CAS NUMBER	CHEMICAL NAME	% BY WEIGHT
------------	---------------	-------------

None Listed.

TSCA NOTIFICATION:

All chemical substances in this material are included on or exempted from listing on the Toxic Substance Control Act Chemical Substance Inventory (TSCA).

SECTION 15: OTHER INFORMATION

To the best of our knowledge, the information provided above meets the requirements of the United States Occupational Safety and Health Act and regulations established under 29 CFR 1910.1200 (g)(2)(c)(1)-(4) for a mixture of hazardous chemicals which has not been tested as a whole. The data provided on this Material Safety Data Sheet is from manufacturers of the original components. Micro-Measurements specifically disclaims any and all form of liability and/or responsibility for the application of this product.