

Ultra High Precision Bulk Metal[®] Z-Foil Surface Mount Power Resistor in TO-220 Configuration with TCR of ± 0.05 ppm/ $^{\circ}$ C, PCR of 4 ppm/W and Load Life Stability of ± 0.005 % (50 ppm)



INTRODUCTION

The Z-Foil technology provides a significant reduction of the resistive component's sensitivity to ambient temperature variations (TCR) and applied power changes (PCR).

Model VPR221SZ is a 4 lead kelvin connected surface mount device which provides high rated power, excellent load life stability, low temperature coefficient (TCR) and low power coefficient (PCR) - all in one resistor. ± 0.05 ppm/ $^{\circ}$ C absolute TCR removes error due to temperature gradients.

By taking advantage of the overall stability and reliability of Bulk Metal[®] Z-Foil resistors, designers can significantly reduce circuit errors and greatly improve overall circuit performances.

Our application engineering department is available to advise and make recommendations. For non-standard technical requirements and special applications, please contact us.

TABLE 1 - TCR AND TOLERANCE

RESISTANCE RANGE (Ω)	TIGHTEST RESISTANCE TOLERANCE	TYPICAL TCR AND MAX. SPREAD ⁽¹⁾
0.5 to < 1	± 0.05 %	± 0.2 ppm/ $^{\circ}$ C ± 2.8 ppm/ $^{\circ}$ C
1 to < 10	± 0.02 %	± 0.2 ppm/ $^{\circ}$ C ± 2.3 ppm/ $^{\circ}$ C
10 to 500	± 0.01 %	± 0.2 ppm/ $^{\circ}$ C ± 1.8 ppm/ $^{\circ}$ C

Notes

⁽¹⁾ MIL-range (- 55 $^{\circ}$ C to + 125 $^{\circ}$ C, + 25 $^{\circ}$ C ref.)

- Contact applications engineering for other available values

* Pb containing terminations are not RoHS compliant, exemptions may apply

FEATURES

- Temperature coefficient of resistance (TCR): ± 0.05 ppm/ $^{\circ}$ C typical (0 $^{\circ}$ C to + 60 $^{\circ}$ C)
 ± 0.2 ppm/ $^{\circ}$ C typical (- 55 $^{\circ}$ C to + 125 $^{\circ}$ C, + 25 $^{\circ}$ C ref.) (see table 1)
- Tolerance: to ± 0.01 %
- Power coefficient "ΔR due to self heating": 4 ppm/W typical
- Rated power: 8 W chassis mounted (MIL-PRF-39009)
- Load life stability: to ± 0.005 % at 25 $^{\circ}$ C for 2000 h, at 1.5 W
- Resistance range: 0.5 Ω to 500 Ω
- Foil resistors are not restricted to standard values; specific "as requested" values can be supplied at no extra cost or delivery (e.g. 100R2345 vs. 100R)
- Electrostatic discharge (ESD) up to 25 000 V
- Short time overload ≤ 0.001 % (10 ppm)
- Non-inductive, non-capacitive design
- Rise time: 1 ns effectively no ringing
- Current noise: 0.010 μ V_{RMS}/V of applied voltage (< - 40 dB)
- Thermal EMF: 0.05 μ V/ $^{\circ}$ C typical
- Voltage coefficient < 0.1 ppm/V
- Non-inductive: < 0.08 μ H
- Non hot spot design
- Thermal stabilization time < 1 s (nominal value achieved within 10 ppm of steady state value)
- Terminal finish: lead (Pb)-free or tin/lead alloy
- Compliant to RoHS directive 2002/95/EC
- Prototype quantities available in just 5 working days or sooner. For more information, please contact foil@vishaypg.com
- For better performances please contact us



RoHS*
COMPLIANT

FIGURE 1 - SCHEMATICS




FIGURE 2 - POWER DERATING CURVE




FIGURE 3 - TRIMMING TO VALUES
(conceptual illustration)




FIGURE 4 - TYPICAL RESISTANCE/TEMPERATURE CURVE
(for more details see table 1)




FIGURE 5 - VPR221SZ FORMING DIMENSIONS in inches (millimeters)




FIGURE 6 - VPR221SZ DIMENSIONS in inches (millimeters)




FIGURE 7 - LAND PATTERN DIMENSIONS in inches (millimeters)




TABLE 2 - SPECIFICATIONS

Power Rating at + 25 °C	8 W or 3 A ⁽¹⁾ on heat sink ⁽²⁾ 1.5 W in free air Further derating not necessary.
Current Noise	< 0.010 $\mu\text{V}_{\text{RMS}}/\text{V}$ of applied voltage (- 40 dB)
High Frequency Operation Rise Time Inductance (L) ⁽³⁾ Capacitance (C)	0.2 ns at 1 W 0.1 μH maximum: 0.03 μH typical 1.0 pF maximum: 0.5 pF typical
Voltage Coefficient ⁽⁴⁾	< 0.1 ppm/V
Operating Temperature Range	- 55 °C to + 150 °C
Maximum Working Voltage	300 V, not to exceed power rating
Thermal EMF ⁽⁵⁾	0.15 $\mu\text{V}/^\circ\text{C}$ maximum (lead effect)
Weight	1.2 g maximum

Notes

(1) Whichever is lower

(2) Heat sink chassis dimensions are requirements per MIL-R-39009/1B:

DIMENSIONS	inches	mm
L	6.00	152.4
W	4.00	101.6
H	2.00	50.8
T	0.04	1.0

(3) Inductance (L) mainly due to the leads

(4) The resolution limit of existing test requirement (within the measurement capability of the equipment, "essentially zero")

(5) $\mu\text{V}/^\circ\text{C}$ relates to EMF due to lead temperature difference

TABLE 3 - PERFORMANCE SPECIFICATIONS ⁽¹⁾ MIL-PRF 39009


TEST OR CONDITION	MIL-PRF 39009	TYPICAL ΔR	MAXIMUM ΔR
Low temperature storage 24 h at - 55 °C	$\pm 0.3 \% + 0.01 \Omega$	$\pm 0.001 \% (10 \text{ ppm})$	$\pm 0.002 \% (20 \text{ ppm})$
Dielectric withstanding voltage 300 V_{AC} at Atm	$\pm 0.2 \% + 0.01 \Omega$	$\pm 0.001 \% (10 \text{ ppm})$	$\pm 0.002 \% (20 \text{ ppm})$
Dielectric withstanding voltage 200 V_{AC} at Brm	$\pm 0.2 \% + 0.01 \Omega$	$\pm 0.001 \% (10 \text{ ppm})$	$\pm 0.002 \% (20 \text{ ppm})$
Insulation resistance	$> 10^4 \text{ M}\Omega$		$> 10^4 \text{ M}\Omega$
Low temperature operation	$\pm 0.3 \% + 0.01 \Omega$	$\pm 0.002 \% (20 \text{ ppm})$	$\pm 0.008 \% (80 \text{ ppm})$
Short time overload 5 x rated power for 5 s (in air)	$\pm 0.3 \% + 0.01 \Omega$	$\pm 0.001 \% (10 \text{ ppm})$	$\pm 0.002 \% (20 \text{ ppm})$
Moisture resistance + 65 °C to - 10 °C, 90 RH to 98 RH, 10 days	$\pm 0.5 \% + 0.01 \Omega$	$\pm 0.005 \% (50 \text{ ppm})$	$\pm 0.015 \% (150 \text{ ppm})$
Terminal strength	$\pm 0.2 \% + 0.01 \Omega$	$\pm 0.001 \% (10 \text{ ppm})$	$\pm 0.002 \% (20 \text{ ppm})$
Load life 8 W at + 25 °C, 2000 h with heat sink	$\pm 1.0 \% + 0.01 \Omega$	$\pm 0.005 \% (50 \text{ ppm})$	$\pm 0.015 \% (150 \text{ ppm})$
Load life 1.5 W at + 25 °C for 2000 h in free air	$\pm 1.0 \% + 0.01 \Omega$	$\pm 0.005 \% (50 \text{ ppm})$	$\pm 0.015 \% (150 \text{ ppm})$
High temperature exposure + 150 °C	$\pm 1.0 \% + 0.05 \Omega$	$\pm 0.005 \% (50 \text{ ppm})$	$\pm 0.01 \% (100 \text{ ppm})$

Note

(1) Measurement error $\pm 0.001 \%$

TABLE 4 - GLOBAL PART NUMBER INFORMATION (1)

NEW GLOBAL PART NUMBER: Y2123420R220T9L (preferred part number format)



FOR EXAMPLE: ABOVE GLOBAL ORDER Y2123 420R220 T 9 L:

TYPE: VPR221SZ
 VALUE: 420.22 Ω
 ABSOLUTE TOLERANCE: ± 0.01 %
 TERMINATION: lead (Pb)-free
 PACKAGING: bulk

HISTORICAL PART NUMBER: VPR221SZ T 420R22 TCR0.2 T B (will continue to be used)

VPR221SZ	T	420R22	TCR0.2	T	B
MODEL	TERMINATION T = lead (Pb)-free none = tin/lead	OHMIC VALUE 420.22 Ω	TCR CHARACTERISTIC TCR0.2	ABSOLUTE TOLERANCE T = ± 0.01 % Q = ± 0.02 % A = ± 0.05 % B = ± 0.1 % C = ± 0.25 % D = ± 0.5 % F = ± 1.0 %	PACKAGING B = bulk T = tape and reel

Note

(1) For non-standard requests, please contact application engineering

Disclaimer

All product specifications and data are subject to change without notice.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay Precision Group"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay Precision Group disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay Precision Group's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay Precision Group.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay Precision Group products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay Precision Group for any damages arising or resulting from such use or sale. Please contact authorized Vishay Precision Group personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.