

## Weight Controller/Indicator



### DESCRIPTION

VT 400 Weight Controllers provide weighing and control functions for industrial process systems.

Two opto-isolated control outputs, a choice of up to two serial interfaces (RS-232 and RS-485) and an analog output (optional) allow full communication with higher level PCs or PLCs. Up to 30 units can be interconnected through the RS-485 network.

The standard VT 400 panel mount enclosure is rated IP40. However, it can be upgraded with an IP54 front panel cover (optional).

### FEATURES

- Inventory and batching control terminal
- High sample rate, up to 70 samples per second
- Up to two serial ports with printing and networking (one standard)
- Analog output (optional)
- Two opto-isolated weight setpoints
- Large 6 digit LED display
- Alibi (Flash) memory for last 10,000 transactions
- OIML R-76 approved to 10000d
- Panel mount IP40 enclosure
- IP54 front panel cover (optional)
- Input power 24VDC


### APPLICATIONS

- Process weighing
- Inventory control

### OPTIONS

- Analog output
- RS-485 port
- Second RS-232 port

### CONFIGURATION



**SPECIFICATIONS**

**PERFORMANCE**

Resolution: selectable up to 990,000 dd  
 Conversion Speed: 3 - 70 samples per second (selectable)  
 Sensitivity: 0.4µV/Vsi for approved scales, 0.1µV/Vsi for non-approved scales.  
 Full Scale Range: -0.25 to 1.75mV/V [-1.25mV to 8.75mV] or -0.25 to 3.75mV/V [-1.25mV to 18.75mV]  
 Linearity: 0.002% of full scale  
 Long Term Stability: 0.005% of full scale per year  
 Excitation: +5V alternating polarity or +5VDC (selectable), with sense (6 wires)  
 Number of Cells: Up to 10, 350 ohm load cells  
 Filter: FIR automatically adjusted to conversion speed, rolling average.  
 Offset Drift: < 2ppm/°C  
 Span Drift: < 2ppm/°C  
 A/D Converter Type: Sigma-Delta, ratiometric  
 Count By: x1, x2, x5, x10, x50  
 Decimal Point: between any digits of the weight display  
 Calibration Methods: dead load and span, or data sheets calibration, via the mV/V output values of the load cell.  
 Weighing Functions: automatic zero tracking, motion detection, auto-zero on power-up, zero tare, multiple test functions.  
 Memory Allocation: calibration data EEPROM (32kb), Flash tally-roll (Alibi) memory capable of 10,000 weight registrations (64kb)

**ENVIRONMENTAL**

Operating Temp: -10°C to +40°C [14°F to 104°F]  
 Storage Temp: -10°C to +70°C [-4°F to 158°F]  
 Relative Humidity: 40-90% RH, non-condensing

**DISPLAY AND KEYBOARD**

Display: 6 digit, 7 segment, LED  
 Digital Height: 14mm [0.55in.]  
 Status Enunciators: no motion, zero, tare in use, net, setpoint in operation  
 Weight Digits: 4, 5 or 6 (setup selectable)  
 Keyboard: 6 membrane keys, with tactile feedback

**ELECTRICAL**

Voltage: 24VDC  
 Current: 500mA

**ISOLATED ANALOG OUTPUT (OPTIONAL)**

Resolution: 16 bit DAC  
 Voltage Output: 0.02-10V  
 Current: 0-20mA or 4-20mA  
 Linearity: 0.01% (or better) of full scale  
 Thermal Stability: 50ppm/°C typical

**INPUTS & OUTPUTS**

(x1) Logic Input: 9-24VDC, negative common, opto-isolated to 2.5KV.  
 (x2) Logic Output: 24VDC±10%, positive common, max current 100mA, opto-isolated to 2.5KV, programmable as weight setpoints

**SERIAL COMMUNICATION**

Serial Output #1: RS-232, non-programmable  
 Baud Rate: 2400 baud, full duplex  
 Applications: continuous, print (on demand), alibi print  
 Serial Output #2: RS-232 or RS-485 setup programmable  
 Baud Rate: 2400 - 57800 baud, half duplex  
 Applications: EDP and master-slave protocols, continuous output, remote printer, weight output

**ENCLOSURE**

Heavy duty plastic enclosure:  
 Dimensions: 144x72x132mm LxHxD [5.7x2.8x5in. LxHxD]  
 Mounting: panel mount  
 Protection: IP40 standard, optional front panel cover - IP54  
 Wiring Connections: mini D-type connectors

**APPROVALS (ACCURACY CLASS III/IIIL)**

OIML R-76: 10000d single or dual interval  
 EU-type approval no. DK0199.62

Transducers is continually seeking to improve product quality and performance. Specifications may change accordingly.

## Disclaimer

All product specifications and data are subject to change without notice.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay Precision Group"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay Precision Group disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay Precision Group's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay Precision Group.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay Precision Group products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay Precision Group for any damages arising or resulting from such use or sale. Please contact authorized Vishay Precision Group personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.