


Photovoltaic Solar Cell Protection Schottky Rectifier, 15 A


FEATURES

- 150 °C T_J operation
- Low forward voltage drop
- High frequency operation
- Guard ring for enhanced ruggedness and long term reliability
- High purity, high temperature epoxy encapsulation for enhanced mechanical strength and moisture resistance
- Lead (Pb)-free plating
- Compliant to RoHS directive 2002/95/EC
- Designed and qualified for industrial level


**RoHS
COMPLIANT**
DESCRIPTION

The VS-150SQ... axial leaded Schottky rectifier series has been optimized for very low forward voltage drop, with moderate leakage. The proprietary barrier technology allows for reliable operation up to 150 °C junction temperature. Typical applications are in switching power supplies, converters, freewheeling diodes, and reverse battery protection.

$T_J \leq 200$ °C for use in solar cell box as a bypass diode for protection, using DC forward current without reverse bias.

PRODUCT SUMMARY

$I_{F(AV)}$	15 A
V_R	30 V to 45 V

MAJOR RATINGS AND CHARACTERISTICS

SYMBOL	CHARACTERISTICS	VALUES	UNITS
$I_{F(AV)}$	DC	15	A
V_{RRM}		30 to 45	V
I_{FSM}	$t_p = 5 \mu s$ sine	2150	A
V_F	15 Apk, $T_J = 125$ °C	0.48	V
T_J	Range ⁽¹⁾	- 55 to 150	°C

Note

(1) $T_J \leq 200$ °C for DC current without reverse voltage

VOLTAGE RATINGS

PARAMETER	SYMBOL	VS-150SQ030	VS-150SQ035	VS-150SQ040	VS-150SQ045	UNITS
Maximum DC reverse voltage	V_R	30	35	40	45	V
Maximum working peak reverse voltage	V_{RWM}					

ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	TEST CONDITIONS	VALUES	UNITS
Maximum average forward current See fig. 5	$I_{F(AV)}$	For DC solar application $T_C = 172$ °C ($T_J = 200$ °C)	15	A
Maximum peak one cycle non-repetitive surge current See fig. 7	I_{FSM}	5 μs sine or 3 μs rect. pulse 10 ms sine or 6 ms rect. pulse	2150 340	
Non-repetitive avalanche energy	E_{AS}	$T_J = 25$ °C, $I_{AS} = 1.8$ A, $L = 7.4$ mH	12	mJ
Repetitive avalanche current	I_{AR}	Current decaying linearly to zero in 1 μs Frequency limited by, T_J maximum $V_A = 1.5 \times V_R$ typical	1.8	A

ELECTRICAL SPECIFICATIONS					
PARAMETER	SYMBOL	TEST CONDITIONS		VALUES	UNITS
Maximum forward voltage drop See fig. 1	$V_{FM}^{(1)}$	15 A	$T_J = 25\text{ }^\circ\text{C}$	0.54	V
		30 A		0.67	
		15 A	$T_J = 125\text{ }^\circ\text{C}$	0.48	
		30 A		0.62	
		15 A	$T_J = 200\text{ }^\circ\text{C}$	0.46	
		30 A		0.61	
Maximum reverse leakage current See fig. 2	I_{RM}	$T_J = 25\text{ }^\circ\text{C}$	$V_R = \text{Rated } V_R$	1.75	mA
		$T_J = 125\text{ }^\circ\text{C}$		70	
Maximum junction capacitance	C_T	$V_R = 5\text{ }V_{DC}$, (test signal range 100 kHz to 1 MHz), $25\text{ }^\circ\text{C}$		900	pF
Typical series inductance	L_S	Measured lead to lead 5 mm from body		10.0	nH
Maximum voltage rate of change	dV/dt	Rated V_R		10 000	V/ μs

Note


(1) Pulse width < 300 μs , duty cycle < 2 %

THERMAL - MECHANICAL SPECIFICATIONS					
PARAMETER	SYMBOL	TEST CONDITIONS		VALUES	UNITS
Maximum junction temperature range	$T_J^{(1)}$			- 55 to 150	$^\circ\text{C}$
Maximum storage temperature range	T_{Stg}			- 55 to 150	
Maximum thermal resistance, junction to lead	R_{thJL}	DC operation; 1/8" lead length		8.0	$^\circ\text{C}/\text{W}$
	$R_{thJL}^{(2)}$			4.0	
Typical thermal resistance, junction to air	R_{thJA}			44	
Approximate weight				1.4	g
				0.049	oz.
Marking device		Case style DO-204AR (JEDEC)		150SQ030	
				150SQ035	
				150SQ040	
				150SQ045	

Notes


(1) $T_J = 200\text{ }^\circ\text{C}$ for DC solar application without reverse voltage time $\leq 1\text{ h}$

(2) Applicable when used in junction box at $I_F = 12\text{ A}$, $T_{box} = 77\text{ }^\circ\text{C}$




93098_01

Fig. 1 - Maximum Forward Voltage Drop Characteristics




93098_03

Fig. 3 - Typical Junction Capacitance vs. Reverse Voltage




93098_02

Fig. 2 - Typical Values of Reverse Current vs. Reverse Voltage



93098_04

Fig. 4 - Maximum Allowable Case Temperature vs. Average Forward Current



93098_05

Fig. 5 - Maximum Non-Repetitive Surge Current




Fig. 6 - Unclamped Inductive Test Circuit

ORDERING INFORMATION TABLE

Device code	VS-	150	S	Q	045	TR
	1	2	3	4	5	6
	1	2	3	4	5	6
	1	2	3	4	5	6
	1	2	3	4	5	6
	1	2	3	4	5	6
	1	2	3	4	5	6

1 - HPP product suffix
2 - 150 = Current x 10
3 - S = DO-204AR
4 - Q = Schottky Q.. series
5 - Voltage ratings ————
6 - • TR = Tape and reel package (1500 pcs)
 • None = Box package (300 pcs)

030 = 30 V
035 = 35 V
040 = 40 V
045 = 45 V

LINKS TO RELATED DOCUMENTS	
Dimensions	www.vishay.com/doc?95243
Part marking information	www.vishay.com/doc?95325
Packaging information	www.vishay.com/doc?95332



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.