



"Full Bridge" IGBT MTP (Warp Speed IGBT), 50 A


MTP

PRODUCT SUMMARY	
V_{CES}	600 V
I_C DC	69 A
$V_{CE(on)}$	2.22 V

FEATURES

- Generation 4 warp speed IGBT technology
- HEXFRED® antiparallel diodes with ultrasoft reverse recovery
- Very low conduction and switching losses
- Optional SMT thermistor
- Al_2O_3 DBC
- Very low stray inductance design for high speed operation
- Speed 8 kHz to 60 kHz > 20 kHz hard switching, > 200 kHz resonant mode
- UL approved file E78996 
- Compliant to RoHS directive 2002/95/EC
- Designed and qualified for industrial level


RoHS
COMPLIANT

BENEFITS

- Optimized for welding, UPS and SMPS applications
- Low EMI, requires less snubbing
- Direct mounting to heatsink
- PCB solderable terminals
- Very low junction to case thermal resistance

ABSOLUTE MAXIMUM RATINGS				
PARAMETER	SYMBOL	TEST CONDITIONS	MAX.	UNITS
Collector to emitter voltage	V_{CES}		600	V
Continuous collector current	I_C	$T_C = 25\text{ }^\circ\text{C}$	69	A
		$T_C = 80\text{ }^\circ\text{C}$	46	
Pulsed collector current	I_{CM}		200	
Peak switching current	I_{LM}		200	
Diode continuous forward current	I_F	$T_C = 100\text{ }^\circ\text{C}$	25	
Peak diode forward current	I_{FM}		200	
Gate to emitter voltage	V_{GE}		± 20	V
RMS isolation voltage	V_{ISOL}	Any terminal to case, $t = 1$ minute	2500	
Maximum power dissipation per single IGBT	P_D	$T_C = 25\text{ }^\circ\text{C}$	195	W
		$T_C = 100\text{ }^\circ\text{C}$	78	

ELECTRICAL SPECIFICATIONS ($T_J = 25\text{ }^\circ\text{C}$ unless otherwise noted)						
PARAMETER	SYMBOL	TEST CONDITIONS	MIN.	TYP.	MAX.	UNITS
Collector to emitter breakdown voltage	$V_{(BR)CES}$	$V_{GE} = 0\text{ V}$, $I_C = 250\text{ }\mu\text{A}$	600	-	-	V
Temperature coefficient of breakdown voltage	$\Delta V_{(BR)CES}/\Delta T_J$	$V_{GE} = 0\text{ V}$, $I_C = 4\text{ mA}$ ($25\text{ }^\circ\text{C}$ to $125\text{ }^\circ\text{C}$)	-	+ 0.6	-	V/ $^\circ\text{C}$
Collector to emitter saturation voltage	$V_{CE(on)}$	$V_{GE} = 15\text{ V}$, $I_C = 25\text{ A}$	-	2.22	3.14	V
		$V_{GE} = 15\text{ V}$, $I_C = 50\text{ A}$	-	2.43	3.25	
		$V_{GE} = 15\text{ V}$, $I_C = 25\text{ A}$, $T_J = 150\text{ }^\circ\text{C}$	-	1.65	1.93	
		$V_{GE} = 15\text{ V}$, $I_C = 50\text{ A}$, $T_J = 150\text{ }^\circ\text{C}$	-	2.08	2.45	
Gate threshold voltage	$V_{GE(th)}$	$V_{CE} = V_{GE}$, $I_C = 250\text{ }\mu\text{A}$	3	-	6	
Temperature coefficient of threshold voltage	$\Delta V_{GE(th)}/\Delta T_J$	$V_{CE} = V_{GE}$, $I_C = 250\text{ }\mu\text{A}$ ($25\text{ }^\circ\text{C}$ to $125\text{ }^\circ\text{C}$)	-	- 17	-	mV/ $^\circ\text{C}$
Transconductance	g_{fe}	$V_{CE} = 100\text{ V}$, $I_C = 25\text{ A}$, $PW = 80\text{ }\mu\text{s}$	-	43	-	S
Zero gate voltage collector current	$I_{CES} (1)$	$V_{GE} = 0\text{ V}$, $V_{CE} = 600\text{ V}$, $T_J = 25\text{ }^\circ\text{C}$	-	-	250	μA
		$V_{GE} = 0\text{ V}$, $V_{CE} = 600\text{ V}$, $T_J = 150\text{ }^\circ\text{C}$	-	-	10	mA
Gate to emitter leakage current	I_{GES}	$V_{GE} = \pm 20\text{ V}$	-	-	± 250	nA
Diode forward voltage drop	V_{FM}	$I_C = 25\text{ A}$	-	1.36	1.64	V
		$I_C = 50\text{ A}$	-	1.57	1.93	
		$I_C = 25\text{ A}$; $T_J = 150\text{ }^\circ\text{C}$	-	1.19	1.42	
		$I_C = 50\text{ A}$; $T_J = 150\text{ }^\circ\text{C}$	-	1.48	1.80	

Note

(1) I_{CES} includes also opposite leg overall leakage

SWITCHING CHARACTERISTICS ($T_J = 25\text{ }^\circ\text{C}$ unless otherwise specified)						
PARAMETER	SYMBOL	TEST CONDITIONS	MIN.	TYP.	MAX.	UNITS
Total gate charge (turn-on)	Q_g	$I_C = 25\text{ A}$ $V_{CC} = 480\text{ V}$ $V_{GE} = 15\text{ V}$	-	175	263	nC
Gate to emitter charge (turn-on)	Q_{ge}		-	27	41	
Gate to collector charge (turn-on)	Q_{gc}		-	71	107	
Turn-on switching loss	E_{on}	$R_g = 5\text{ }\Omega$, $I_C = 25\text{ A}$ $V_{CC} = 480\text{ V}$ $V_{GE} = \pm 15\text{ V}$, $T_J = 25\text{ }^\circ\text{C}$	-	0.13	0.20	mJ
Turn-off switching loss	E_{off}		-	0.42	0.62	
Total switching loss	E_{tot}		-	0.55	0.82	
Turn-on switching loss	E_{on}	$R_g = 5\text{ }\Omega$, $I_C = 25\text{ A}$ $V_{CC} = 480\text{ V}$ $V_{GE} = \pm 15\text{ V}$, $T_J = 125\text{ }^\circ\text{C}$	-	0.39	0.59	
Turn-off switching loss	E_{off}		-	0.49	0.74	
Total switching loss	E_{tot}		-	0.88	1.32	
Input capacitance	C_{ies}	$V_{GE} = 0\text{ V}$ $V_{CC} = 30\text{ V}$ $f = 1.0\text{ MHz}$	-	3610	5415	pF
Output capacitance	C_{oes}		-	714	1071	
Reverse transfer capacitance	C_{res}		-	58	87	
Diode reverse recovery time	t_{rr}	$V_R = 200\text{ V}$; $I_C = 25\text{ A}$; $di/dt = 200\text{ A}/\mu\text{s}$	-	50	-	ns
Diode peak reverse current	I_{rr}		-	4.5	-	A
Diode Recovery charge	Q_{rr}		-	112	-	nC
Diode peak rate of fall of recovery during t_b	$di_{(rec)}/dt$		-	250	-	A/ μs



THERMAL AND MECHANICAL SPECIFICATIONS						
PARAMETER	SYMBOL	TEST CONDITIONS	MIN.	TYP.	MAX.	UNITS
Operating junction temperature range	T_J		- 40	-	150	°C
Storage temperature range	T_{Stg}		- 40	-	125	
Junction to case	R_{thJC} <small>IGBT</small> <small>Diode</small>		-	-	0.64	°C/W
				-	-	
Case to sink per module	R_{thCS}	Heatsink compound thermal conductivity = 1 W/mK	-	0.06	-	
Clearance ⁽¹⁾		External shortest distance in air between 2 terminals	5.5	-	-	mm
Creepage ⁽¹⁾		Shortest distance along external surface of the insulating material between 2 terminals	8	-	-	
Weight			66			g

Note

⁽¹⁾ Standard version only i.e. without optional thermistor




Fig. 1 - Maximum Collector Current vs. Case Temperature




Fig. 2 - Typical Collector to Emitter Voltage vs. Junction Temperature




Fig. 3 - Maximum Transient Thermal Impedance, Junction to Case (IGBT)




Fig. 4 - Maximum Transient Thermal Impedance, Junction to Case (Diode)




Fig. 5 - Typical Capacitance vs. Collector to Emitter Voltage




Fig. 7 - Typical Switching Losses vs. Gate Resistance




Fig. 6 - Typical Gate Charge vs. Gate to Emitter Voltage




Fig. 8 - Typical Switching Losses vs. Junction Temperature




Fig. 9 - Typical Switching Losses vs. Collector to Emitter Current




Fig. 12 - Typical Reverse Recovery Time vs. dI_F/dt




Fig. 10 - Turn-Off SOA




Fig. 13 - Typical Reverse Recovery Current vs. dI_F/dt




Fig. 11 - Maximum Forward Voltage Drop vs. Instantaneous Forward Current




Fig. 14 - Typical Stored Charge vs. dI_F/dt

25MT060WFAPbF



Vishay High Power Products "Full Bridge" IGBT MTP
(Warp Speed IGBT), 50 A




Fig. 15 - Typical $dI_{(rec)M}/dt$ vs. dI_F/dt





Fig. 16 - Electrical diagram

ORDERING INFORMATION TABLE

Device code	25	MT	060	W	F	A	PbF
	①	②	③	④	⑤	⑥	⑦

- 1** - Current rating (25 = 25 A)
- 2** - Essential part number
- 3** - Voltage code (060 = 600 V)
- 4** - Speed/type (W = Warp IGBT)
- 5** - Circuit configuration (F = Full bridge)
- 6** - A = Al₂O₃ DBC substrate
- 7** - PbF = Lead (Pb)-free

CIRCUIT CONFIGURATION



LINKS TO RELATED DOCUMENTS

Dimensions	www.vishay.com/doc?95245
------------	--



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.