

Precision Linear Transducers, Conductive Plastic, up to 150 mm



FEATURES

- Measurement range 12.5 mm to 150 mm
- High accuracy $\pm 1\%$ down to $\pm 0.1\%$
- Long life
- Essentially infinite resolution
- Very small dimension: External diameter = 9.52 mm



The 38 L is a very compact model especially designed for precise measurement of short travels.

ELECTRICAL SPECIFICATIONS	
Theoretical Electrical Travel (TET)	From 12.5 mm to 150 mm see table 1
Actual Electrical Travel (AET)	$AET = TET + 1 \text{ mm}$
Independent Linearity (over TET)	$\leq \pm 1\%$ - $\leq \pm 0.5\%$ $\leq \pm 0.25\%$ for $E \geq 25 \text{ mm}$ $\leq \pm 0.1\%$ for $E \geq 50 \text{ mm}$
Repeatability	$\leq 0.01\%$
Ohmic Values (R_T)	From $400 \Omega/\text{cm}$ to $2 \text{ k}\Omega/\text{cm}$
Resistance Tolerance at 20°C	$\pm 20\%$
Wiper Current	Recommended: a few μA - 1 mA max. (continuous)
Load Resistance	Minimum $10^3 \times R_T$
Insulation Resistance	$\geq 1000 \text{ M}\Omega$, $500 \text{ V}_{\text{DC}}$
Dielectric Strength	$\geq 500 \text{ V}_{\text{RMS}}$, 50 Hz

MECHANICAL SPECIFICATIONS	
Mechanical Travel (MT)	$MT = TET + 3 \pm 1 \text{ mm}$
Housing	Anodized aluminum
Operating Force	0.35 N typical
Termination	3 wires PTFE AWG 28 length: 300 mm
Wiper	Precious metal multifinger

PERFORMANCE	
Operating Life	25 million cycles typical/ $1 \text{ Hz}/T^\circ = 20^\circ\text{C} \pm 5^\circ\text{C}/80\% \text{ TET}$
Temperature Range	-55°C to $+125^\circ\text{C}$
Sine Vibration on 3 Axes	1.5 mm peak to peak or 15 g - 10 Hz - 2000 Hz
Mechanical Shocks on 3 Axes	50 g - 11 ms - half sine

DIMENSIONS in millimeters, general tolerance ± 1 mm





TABLE 1

SIZE	TET	MT	A
38 L0.5	12.5	15.5	43.5
38 L01	25	28	56
38 L02	50	53	81
38 L03	75	78	106
38 L04	100	103	131
38 L05	125	128	156
38 L06	150	153	181

ELECTRICAL CONNECTIONS



TET = THEORETICAL ELECTRICAL TRAVEL
AET = ACTUAL ELECTRICAL TRAVEL
MT = MECHANICAL TRAVEL

ORDERING INFORMATION/DESCRIPTION

REC	38	L	0.5	C	102	W...	e1
SERIES	MODEL	NUMBER OF TRACKS	ELECTRICAL TRAVEL	LINEARITY	OHMIC VALUE	MODIFICATIONS	LEAD FINISH
		L = 1 track	0.5 = 12.5 mm 1 = 25 mm 2 = 50 mm 3 = 75 mm 4 = 100 mm 5 = 125 mm 6 = 150 mm	A: $\pm 1\%$ B: $\pm 0.5\%$ C: $\pm 0.25\%$ D: $\pm 0.1\%$	First 2 digits are significant numbers 3rd digit indicates number of zeros	Special feature code number	Sn Ag Cu

SAP PART NUMBERING GUIDELINES

RE	38 L	0.5	C	102	W...
SERIES	MODEL	TET	LINEARITY	OHMIC VALUE	SPECIAL FEATURES



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.