



INFRARED EMITTERS

830 nm, 850 nm, and 870 nm



FEATURES

- Radiant intensity up to 600 mW/sr at 100 mA
- Broad option of viewing angles from $\pm 60^\circ$ to $\pm 3^\circ$
- Up to 5x longer life than competing devices

BENEFITS

- Reduce the number of emitters required to produce equivalent optical power – longer range and better resolution
- Extremely fast switching times for high-speed applications
- 4x the radiant intensity of competing devices

APPLICATIONS

- Illumination for closed circuit TV (night vision) and CMOS image sensors
- Wireless audio transmission in concert halls, museums, and home theatre surround sound systems
- Emergency response remote control of traffic lights
- Emitter for 3DTV active glasses synchronization



FARTHER WITH FEWER

Reduce the number of infrared emitters by up to half while achieving the same resolution and range by using Vishay's infrared emitters for night time **illumination** in closed circuit television (CCTV), security camera, and CMOS image sensor applications. For **data transmission** in museums, concert halls, and other public venues these emitters feature switching times from 10 to 20 ns, meeting the requirements for high-modulation operation and supporting data transmission rates of up to 16 Mbit/sec.

MINIMIZE DEGRADATION

Applications rely on the emitter to maintain performance over time. Designers can not afford to use an emitter that rapidly degrades. Vishay has the lowest degradation when tested against the other leading infrared emitters. The lowest degradation means the best emitters, the longest life.

Part Number	Angle of Half Intensity (°)	Intensity (mW/sr)		Degradation (%)
		0 hours	4000 hours	
Vishay TSHG5210	± 10	230	225	2 %
Vishay TSHG5410	± 18	80	79	2 %
Competitor A	± 8	171	145	15 %
Competitor B	± 12	107	96	10 %
Competitor C	± 10	130	98	25 %

PORTFOLIO



Peak Wavelength (nm)	Part Number	Package	Radiant Intensity ¹ (mW/sr)	Angle of Half Intensity (°)	Rise, Fall Time (ns)
830	TSHG5510	5 mm (T1 ³ / ₄)	32	± 38	15
	TSHG8200	5 mm (T1 ³ / ₄)	180	± 10	20
	TSHG8400	5 mm (T1 ³ / ₄)	70	± 22	20
	VSMG2720	PLCC2	14	± 60	15
850	TSHG5210	5 mm (T1 ³ / ₄)	230	± 10	20
	TSHG5410	5 mm (T1 ³ / ₄)	90	± 18	20
	TSHG6400	5 mm (T1 ³ / ₄)	70	± 22	20
	VSLY5850 ²	5 mm (T1 ³ / ₄)	600	± 3	10
	VSMY1850X01 ²	0805	12	± 60	10
	VSMY2850GX01 ²	Gullwing	100	± 10	10
	VSMY2850RGX01 ²	Reverse Gullwing	100	± 10	10
	VSMY3850X01 ²	PLCC2	17	± 60	15
870	TSFF5210	5 mm (T1 ³ / ₄)	180	± 10	15
	TSFF5410	5 mm (T1 ³ / ₄)	70	± 22	
	TSFF5510	5 mm (T1 ³ / ₄)	32	± 38	
	VSMF4720	PLCC2	16	± 60	

¹I_F=100 mA

² Target specification. Product release pending.

DISCLAIMER All product specifications and data are subject to change without notice. Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product. Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications. Product names and markings noted herein may be trademarks of their respective owners.

Build **Vishay** into your **Design**