



## VARISTORS (MOV)



### FEATURES

- Low leakage current
- Wide voltage range and energy ratios
- Low stand-by power
- Very good surge current handling capabilities
- Very good clamping voltage characteristics
- CSA, VDE, CECC, UL1414, and UL 1449 edition 3 approvals
- RoHS-compliant

### APPLICATIONS



- Power supplies
- Electronic lamp ballasts
- Inductive load switching: motors, coils, actuators, transformers, etc.
- Spark suppression
- General protection against induced lightning transients



# VARISTORS (MOV)

VARISTORS

SELECTOR GUIDE

Product	Part Number	V <sub>RMS</sub> Max (V)	V <sub>DC</sub> Max (V)	V <sub>DC</sub> @ 1 mA (V)	I <sub>max</sub> @ 8/20 μs Non-Repetitive (A)	E <sub>max</sub> @ 10/1000 μs (J)	P <sub>max</sub> (mW)	Ref. Diameter (mm)	Applications	
<b>Standard Series</b> 	<b>VDRS</b>									
	05	14 to 460	18 to 615	22 to 750	100 to 400	0.5 to 21	100	5	For transient and overvoltage protection in: <ul style="list-style-type: none"> <li>• Consumer electronics</li> <li>• Power supplies</li> <li>• Lamp ballasts</li> <li>• Industrial equipment</li> </ul>	
	07	14 to 460	18 to 615	22 to 750	250 to 1200	1.7 to 63	250	7		
	10	14 to 550	18 to 745	22 to 910	500 to 2500	4.3 to 98	400	10		
	14	14 to 550	18 to 745	22 to 910	1000 to 4500	5.4 to 160	600	14		
	20	14 to 680	18 to 895	22 to 1100	2000 to 6500	8.0 to 496	1000	20		
<b>High-Surge Series</b> 	<b>VDRH</b>									
	05	11 to 460	14 to 615	18 to 750	250 to 800	0.7 to 29	100	5		
	07	11 to 510	14 to 670	18 to 820	500 to 1750	1.5 to 60	250	7		
	10	11 to 680	14 to 895	18 to 1100	1000 to 3500	2.6 to 155	400	10		
	14	11 to 680	14 to 895	18 to 1100	2000 to 6000	5.2 to 310	600	14		
	20	11 to 680	14 to 895	18 to 1100	3000 to 10000	13 to 620	1000	20		

For detailed information see datasheet: <http://www.vishay.com/doc?29081>  
<http://www.vishay.com/doc?29082>



One of the World's Largest Manufacturers of  
**Discrete Semiconductors and Passive Components**

Build **Vishay** into your **Design**

[www.vishay.com](http://www.vishay.com)

**DISCLAIMER** All product specifications and data are subject to change without notice. Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product. Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications. Product names and markings noted herein may be trademarks of their respective owners.