


Input Rectifier Diode, 60 A



TO-247AC modified



DESCRIPTION/FEATURES

The 60EPS16PbF rectifier High Voltage Series has been optimized for very low forward voltage drop, with moderate leakage. The glass passivation technology used has reliable operation up to 150 °C junction temperature.



RoHS*
COMPLIANT

Typical applications are in input rectification and these products are designed to be used with Vishay HPP switches and output rectifiers which are available in identical package outlines.

This product has been designed and qualified for industrial level and lead (Pb)-free.

PRODUCT SUMMARY

| | |
|---------------|--------|
| V_F at 60 A | 1.07 V |
| I_{FSM} | 950 A |
| V_{RRM} | 1600 V |

MAJOR RATINGS AND CHARACTERISTICS

| SYMBOL | CHARACTERISTICS | VALUES | UNITS |
|-------------|----------------------------|-------------|-------|
| $I_{F(AV)}$ | Sinusoidal waveform | 60 | A |
| V_{RRM} | | 1600 | V |
| I_{FSM} | | 950 | A |
| V_F | 60 A, $T_J = 25\text{ °C}$ | 1.07 | V |
| T_J | | - 40 to 150 | °C |

VOLTAGE RATINGS

| PART NUMBER | V_{RRM} , MAXIMUM PEAK REVERSE VOLTAGE V | V_{RSM} , MAXIMUM NON-REPETITIVE PEAK REVERSE VOLTAGE V | I_{RRM} AT 150 °C mA |
|-------------|---|--|---------------------------|
| 60EPS16PbF | 1600 | 1700 | 1 |

ABSOLUTE MAXIMUM RATINGS

| PARAMETER | SYMBOL | TEST CONDITIONS | VALUES | UNITS |
|---|---------------|--|--------|-------------------|
| Maximum average forward current | $I_{F(AV)}$ | $T_C = 118\text{ °C}$, 180° conduction half sine wave | 60 | A |
| Maximum peak one cycle non-repetitive surge current | I_{FSM} | 10 ms sine pulse, rated V_{RRM} applied | 950 | |
| | | 10 ms sine pulse, no voltage reapplied | 1100 | |
| Maximum I^2t for fusing | I^2t | 10 ms sine pulse, rated V_{RRM} applied | 4512 | A ² s |
| | | 10 ms sine pulse, no voltage reapplied | 6300 | |
| Maximum $I^2\sqrt{t}$ for fusing | $I^2\sqrt{t}$ | $t = 0.1$ to 10 ms, no voltage reapplied | 63 000 | A ² √s |

* Pb containing terminations are not RoHS compliant, exemptions may apply

60EPS16PbF High Voltage Series



Vishay High Power Products Input Rectifier Diode, 60 A

| ELECTRICAL SPECIFICATIONS | | | | | |
|---------------------------------|-------------|--|-------------------------------|--------|------------------|
| PARAMETER | SYMBOL | TEST CONDITIONS | | VALUES | UNITS |
| Maximum forward voltage drop | V_{FM} | 30 A, $T_J = 25\text{ }^\circ\text{C}$ | | 1.0 | V |
| | | 60 A, $T_J = 25\text{ }^\circ\text{C}$ | | 1.07 | |
| Forward slope resistance | r_t | $T_J = 150\text{ }^\circ\text{C}$ | | 3.96 | $\text{m}\Omega$ |
| Threshold voltage | $V_{F(TO)}$ | | | 0.74 | V |
| Maximum reverse leakage current | I_{RM} | $T_J = 25\text{ }^\circ\text{C}$ | $V_R = \text{Rated } V_{RRM}$ | 0.1 | mA |
| | | $T_J = 150\text{ }^\circ\text{C}$ | | 1.0 | |

| THERMAL - MECHANICAL SPECIFICATIONS | | | | | |
|---|----------------|--------------------------------------|--|-------------|---------------------------|
| PARAMETER | SYMBOL | TEST CONDITIONS | | VALUES | UNITS |
| Maximum junction and storage temperature range | T_J, T_{Stg} | | | - 40 to 150 | $^\circ\text{C}$ |
| Maximum thermal resistance, junction to case | R_{thJC} | DC operation | | 0.35 | $^\circ\text{C}/\text{W}$ |
| Maximum thermal resistance, junction to ambient | R_{thJA} | | | 40 | |
| Typical thermal resistance, case to heatsink | R_{thCS} | Mounting surface, smooth and greased | | 0.2 | |
| Approximate weight | | | | 6 | g |
| | | | | 0.21 | oz. |
| Mounting torque | minimum | | | 6.0 (5) | kgf · cm (lbf · in) |
| | maximum | | | 12 (10) | |
| Marking device | | Case style TO-247AC modified (JEDEC) | | 60EPS16 | |



60EPS16PbF High Voltage Series

Input Rectifier Diode, 60 A Vishay High Power Products




Fig. 1 - Current Rating Characteristics




Fig. 4 - Forward Power Loss Characteristics




Fig. 2 - Current Rating Characteristics




Fig. 5 - Maximum Non-Repetitive Surge Current




Fig. 3 - Forward Power Loss Characteristics




Fig. 6 - Maximum Non-Repetitive Surge Current

60EPS16PbF High Voltage Series

Vishay High Power Products Input Rectifier Diode, 60 A




Fig. 7 - Forward Voltage Drop Characteristics




Fig. 8 - Thermal Impedance Z_{thJC} Characteristics



60EPS16PbF High Voltage Series

Input Rectifier Diode, 60 A Vishay High Power Products

ORDERING INFORMATION TABLE

| Device code | 60 | E | P | S | 16 | PbF |
|-------------|----|--|---|---|----|-----|
| | ① | ② | ③ | ④ | ⑤ | ⑥ |
| 1 | - | Current rating (60 = 60 A) | | | | |
| 2 | - | Circuit configuration: E = Single diode | | | | |
| 3 | - | Package: P = TO-247AC modified | | | | |
| 4 | - | Type of silicon: S = Standard recovery rectifier | | | | |
| 5 | - | Voltage rating (16 = 1600 V) | | | | |
| 6 | - | • None = Standard production • PbF = Lead (Pb)-free | | | | |

| LINKS TO RELATED DOCUMENTS | |
|----------------------------|---|
| Dimensions | http://www.vishay.com/doc?95253 |
| Part marking information | http://www.vishay.com/doc?95255 |



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.