


SC-89: 6-LEAD (SOT-666)


| Dim | MILLIMETERS* | | | INCHES | | |
|----------------------------|--------------|------|------|-----------|-------|-------|
| | Min | Nom | Max | Min | Nom | Max |
| A | 0.56 | — | 0.60 | 0.022 | — | 0.024 |
| A3 | 0.13 | 0.17 | 0.18 | 0.005 | 0.006 | 0.007 |
| b | 0.17 | — | 0.25 | 0.006 | — | 0.010 |
| b1 | — | 0.27 | 0.34 | — | 0.011 | 0.013 |
| D | 1.50 | 1.66 | 1.70 | 0.059 | 0.065 | 0.067 |
| E | 1.50 | 1.65 | 1.70 | 0.059 | 0.065 | 0.067 |
| E1 | 1.10 | 1.20 | 1.30 | 0.043 | 0.047 | 0.051 |
| e | 0.50 BSC | | | 0.020 BSC | | |
| e₁ | 0.20 | — | — | 0.008 | — | — |
| L1 | 0.11 | 0.19 | 0.26 | 0.004 | 0.007 | 0.010 |
| L2 | 0.10 | 0.23 | 0.30 | 0.004 | 0.009 | 0.012 |
| L3 | 0.05 | 0.10 | — | 0.002 | 0.004 | — |
| θ | 8° | 10° | 12° | 8° | 10° | 12° |

ECN: S-52444—Rev. D, 28-Nov-05
DWG: 5891

*Use millimeters as the primary measurement