




QFN-16 LEAD (3 X 3)



NOTES:

1. All dimensions are in millimeters.
2. N is the total number of terminals.
3. Dimension b applies to metallized terminal and is measured between 0.25 and 0.30 mm from terminal tip.
4. Coplanarity applies to the exposed heat sink slug as well as the terminal.
5. The pin #1 identifier may be either a mold or marked feature, it must be located within the zone indicated.

Dim	VARIATION 1						VARIATION 2					
	MILLIMETERS			INCHES			MILLIMETERS			INCHES		
	Min	Nom	Max	Min	Nom	Max	Min	Nom	Max	Min	Nom	Max
A	0.80	0.90	1.00	0.031	0.035	0.039	0.80	0.90	1.00	0.031	0.035	0.039
b	0.18	0.23	0.30	0.007	0.009	0.012	0.18	0.25	0.30	0.007	0.010	0.012
D	3.00 BSC			0.118 BSC			3.00 BSC			0.118 BSC		
D2	1.00	1.15	1.25	0.039	0.045	0.049	1.55	1.70	1.80	0.061	0.067	0.071
E	3.00 BSC			0.118 BSC			3.00 BSC			0.118 BSC		
E2	1.00	1.15	1.25	0.039	0.045	0.049	1.55	1.70	1.80	0.061	0.067	0.071
e	0.50 BSC			0.020 BSC			0.50 BSC			0.020 BSC		
L	0.30	0.40	0.50	0.012	0.016	0.020	0.30	0.40	0.50	0.012	0.016	0.020

ECN: S-32625—Rev. B, 29-Dec-03
DWG: 5899