



Si2303BDS vs. Si2303ADS

Description: P-Channel, 30 V (D-S) MOSFET

Package: SOT-23

Pin Out: Identical

Part Number Replacements:

Si2303BDS-T1 Replaces Si2303ADS-T1

Si2303BDS-T1-E3 (Lead (Pb)-free version) Replaces Si2303ADS-T1

ABSOLUTE MAXIMUM RATINGS $T_A = 25\text{ }^\circ\text{C}$, unless otherwise noted				
Parameter	Symbol	Si2303BDS	Si2303ADS	Unit
Drain-Source Voltage	V_{DS}	- 30	- 30	V
Gate-Source Voltage	V_{GS}	± 20	± 20	
Continuous Drain Current	$T_A = 25\text{ }^\circ\text{C}$	I_D	- 1.64	A
	$T_A = 70\text{ }^\circ\text{C}$		- 1.31	
Pulsed Drain Current	I_{DM}	- 10	- 10	
Continuous Source Current (MOSFET Diode Conduction)	I_S	- 0.75	- 0.75	
Power Dissipation	$T_A = 25\text{ }^\circ\text{C}$	P_D	0.9	W
	$T_A = 70\text{ }^\circ\text{C}$		0.57	
Operating Junction and Storage Temperature Range	T_j and T_{stg}	- 55 to 150	- 55 to 150	$^\circ\text{C}$
Maximum Junction-to-Ambient	R_{thJA}	175	175	$^\circ\text{C/W}$

SPECIFICATIONS $T_J = 25\text{ }^\circ\text{C}$, unless otherwise noted								
Parameter	Symbol	Si2303BDS			Si2303ADS			Unit
		Min	Typ	Max	Min	Typ	Max	
Static								
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	- 30			- 30			V
Gate-Threshold Voltage	$V_{G(th)}$	- 1.0		- 3.0	- 1.0		- 3.0	
Gate-Body Leakage	I_{GSS}			± 100			± 100	nA
Zero Gate Voltage Drain Current	I_{DSS}			- 1			- 1	μA
On-State Drain Current	$V_{GS} = - 10\text{ V}$ $I_{D(on)}$	- 6			- 6			A
Drain-Source On-Resistance	$V_{GS} = - 10\text{ V}$	$r_{DS(on)}$	0.150	0.200		0.190	0.240	Ω
	$V_{GS} = - 4.5\text{ V}$		0.285	0.380		0.230	0.460	
Forward Transconductance	g_{fs}		2.0			2.4		S
Diode Forward Voltage	V_{SD}		- 0.85	- 1.2		- 0.8	- 1.2	V
Dynamic								
Total Gate Charge	Q_g		4.3	10		4.5	10	nC
Gate-Source Charge	Q_{gs}		0.8			0.9		
Gate-Drain Charge	Q_{gd}		1.3			0.9		
Input Capacitance	C_{iss}		180			260		pF
Output Capacitance	C_{oss}		50			66		
Reverse Transfer Capacitance	C_{rss}		35			35		
Switching								
Turn-On Time	$t_{d(on)}$		55	80		6	20	ns
	t_r		40	60		10	20	
Turn-Off Time	$t_{d(off)}$		10	20		15	35	
	t_f		10	20		7	20	

Specification comparisons are supplied as a courtesy to compare two devices and do not constitute a commercial product datasheet or any guarantee of identical performance. Designers should refer to the appropriate datasheets of the same number for guaranteed specification limits.