



Si5441BDC vs. Si5441DC

Description: P-Channel, 2.5 V (G-S) MOSFET

Package: 1206-8 ChipFET®

Pin Out: Identical

Part Number Replacements:

Si5441BDC-T1-E3 Replaces Si5441DC-T1-E3

Si5441BDC-T1 Replaces Si5441DC-T1

ABSOLUTE MAXIMUM RATINGS $T_A = 25\text{ }^\circ\text{C}$, unless otherwise noted				
Parameter	Symbol	Si5441BDC	Si5441DC	Unit
Drain-Source Voltage	V_{DS}	- 20	- 20	V
Gate-Source Voltage	V_{GS}	± 12	± 12	
Continuous Drain Current	$T_A = 25\text{ }^\circ\text{C}$	- 6.1	- 5.3	A
	$T_A = 70\text{ }^\circ\text{C}$	- 4.4	- 3.8	
Pulsed Drain Current	I_{DM}	- 20	- 20	
Continuous Source Current (MOSFET Diode Conduction)	I_S	- 2.1	- 2.1	
Power Dissipation	$T_A = 25\text{ }^\circ\text{C}$	2.5	2.5	W
	$T_A = 70\text{ }^\circ\text{C}$	1.3	1.3	
Operating Junction and Storage Temperature Range	T_J and T_{stg}	- 55 to 150	- 55 to 150	$^\circ\text{C}$
Maximum Junction-to-Ambient	R_{thJA}	50	50	$^\circ\text{C}/\text{W}$

SPECIFICATIONS $T_J = 25\text{ }^\circ\text{C}$, unless otherwise noted									
Parameter	Symbol	Si5441BDC			Si5441DC			Unit	
		Min	Typ	Max	Min	Typ	Max		
Static									
Gate-Threshold Voltage	$V_{GS(th)}$	- 0.6		- 1.4	- 0.6		NS	V	
Gate-Body Leakage	I_{GSS}			± 100			± 100	nA	
Zero Gate Voltage Drain Current	I_{DSS}			- 1			- 1	μA	
On-State Drain Current	$V_{GS} = - 4.5\text{ V}$	$I_{D(on)}$	- 20		- 20			A	
Drain-Source On-Resistance	$V_{GS} = - 4.5\text{ V}$	$r_{DS(on)}$		0.036	0.045		0.046	0.055	Ω
	$V_{GS} = - 3.6\text{ V}$			0.042	0.052		0.050	0.060	
	$V_{GS} = - 2.5\text{ V}$			0.065	0.080		0.070	0.083	
Forward Transconductance		g_{fs}		12			12	S	
Diode Forward Voltage		V_{SD}		- 0.8	- 1.2		- 0.8	- 1.2	V
Dynamic									
Total Gate Charge		Q_g		11.5	22		11	22	nC
Gate-Source Charge		Q_{gs}		2.2			3.0		
Gate-Drain Charge		Q_{gd}		3.7			2.5		
Gate Resistance		R_g		10			NS		Ω
Switching									
Turn-On Time		$t_{d(on)}$		15	25		20	30	ns
		t_r		50	75		35	55	
Turn-Off Time		$t_{d(off)}$		50	75		65	100	
		t_f		50	75		45	70	
Source-Drain Reverse Recovery Time		t_{rr}		30	60		30	60	

Specification comparisons are supplied as a courtesy to compare two devices and do not constitute a commercial product datasheet or any guarantee of identical performance. Designers should refer to the appropriate datasheets of the same number for guaranteed specification limits.