



## SUD50N03-09P vs. SUD50N03-10CP

**Description:** N-Channel, 30 V (D-S) MOSFET  
**Package:** TO-252  
**Pin Out:** Identical

### Part Number Replacements

SUD50N03-09P-E3 Replaces SUD50N03-10CP-E3  
 SUD50N03-09P Replaces SUD50N03-10CP

<b>ABSOLUTE MAXIMUM RATINGS</b> ( $T_A = 25\text{ }^\circ\text{C}$ , unless otherwise noted)					
Parameter	Symbol	SUD50N03-09P	SUD50N03-10CP	Unit	
Drain-Source Voltage	$V_{DS}$	30	30	V	
Gate-Source Voltage	$V_{GS}$	$\pm 20$	$\pm 20$		
Continuous Drain Current	$I_D$	$T_C = 25\text{ }^\circ\text{C}$	63	62	A
		$T_C = 100\text{ }^\circ\text{C}$	44.5	44	
Pulsed Drain Current	$I_{DM}$	50	100		
Continuous Source Current (MOSFET Diode Conduction)	$I_S$	10	20		
Power Dissipation	$P_D$	$T_A = 25\text{ }^\circ\text{C}$	7.5	8.3	W
		$T_C = 25\text{ }^\circ\text{C}$	65.2	71	
Operating Junction and Storage Temperature Range	$T_J$ and $T_{stg}$	- 55 to 175	- 55 to 175	$^\circ\text{C}$	
Maximum Junction-to-Ambient	$R_{thJA}$	20	18	$^\circ\text{C/W}$	

<b>SPECIFICATIONS</b> ( $T_J = 25\text{ }^\circ\text{C}$ , unless otherwise noted)									
Parameter	Symbol	SUD50N03-09P			SUD50N03-10CP			Unit	
		Min	Typ	Max	Min	Typ	Max		
<b>Static</b>									
Gate-Threshold Voltage	$V_{GS(th)}$	1		3	1			V	
Gate-Body Leakage	$I_{GSS}$			$\pm 100$			$\pm 100$	nA	
Zero Gate Voltage Drain Current	$I_{DSS}$			1			1	$\mu\text{A}$	
On-State Drain Current	$I_{D(on)}$	50			50			A	
Drain-Source On-Resistance	$V_{GS} = 10\text{ V}$	$r_{DS(on)}$		0.0076	0.0095		0.008	0.010	$\Omega$
	$V_{GS} = 4.5\text{ V}$			0.0115	0.014		0.0105	0.012	
Forward Transconductance	$g_{fs}$	20			20	60		S	
Diode Forward Voltage	$V_{SD}$		1.2	1.5		0.85	12	V	
<b>Dynamic</b>									
Total Charge	$Q_g$		11	16		13	19	nC	
Gate-Source Charge	$Q_{gs}$		7.5			4.5			
Gate-Drain Charge	$Q_{gd}$		5.0			4.0			
Gate Resistance	$R_g$	0.5	1.5	2.1	1	1.7	3.5	$\Omega$	
<b>Switching</b>									
Turn-On Time	$t_{d(on)}$		9	15		10	15	ns	
	$t_r$		80	120		160	240		
Turn-Off Time	$t_{d(off)}$		22	35		30	45		
	$t_f$		8	12		55	85		
Source-Drain Reverse Recovery Time	$t_{rr}$		35	70		80	110		

NS denotes parameter not specified

Specification comparisons are supplied as a courtesy to compare two devices and do not constitute a commercial product datasheet or any guarantee of identical performance. Designers should refer to the appropriate datasheets of the same number for guaranteed specification limits.