



## SUD50N03-06AP vs. SUD50N03-07

**Description:** N-Channel, 30 V (D-S) MOSFET  
**Package:** TO-252  
**Pin Out:** Identical

### Part Number Replacements

SUD50N03-06AP-E3 Replaces SUD50N03-07-E3

SUD50N03-06AP-E3 Replaces SUD50N03-07

<b>ABSOLUTE MAXIMUM RATINGS</b> ( $T_A = 25\text{ }^\circ\text{C}$ , unless otherwise noted)				
Parameter	Symbol	SUD50N03-06AP	SUD50N03-07	Unit
Drain-Source Voltage	$V_{DS}$	30	30	V
Gate-Source Voltage	$V_{GS}$	$\pm 20$	$\pm 20$	
Continuous Drain Current	$I_D$	$T_A = 25\text{ }^\circ\text{C}$	30	20
		$T_A = 70\text{ }^\circ\text{C}$	25	NS
		$T_A = 100\text{ }^\circ\text{C}$	NS	14
Pulsed Drain Current	$I_{DM}$	100	100	A
Continuous Source Current (MOSFET Diode Conduction)	$I_S$	6.7	20	
Power Dissipation	$P_D$	$T_A = 25\text{ }^\circ\text{C}$	10	5
		$T_C = 25\text{ }^\circ\text{C}$	83	136
Operating Junction and Storage Temperature Range	$T_J$ and $T_{stg}$	- 55 to 175	- 55 to 175	$^\circ\text{C}$
Maximum Junction-to-Ambient	$R_{thJA}$	15	30	$^\circ\text{C}/\text{W}$
Maximum Junction-to-Case	$R_{thJC}$	1.8	1.1	

<b>SPECIFICATIONS</b> ( $T_J = 25\text{ }^\circ\text{C}$ , unless otherwise noted)								
Parameter	Symbol	SUD50N03-06AP			SUD50N03-07			Unit
		Min	Typ	Max	Min	Typ	Max	
<b>Static</b>								
Gate-Threshold Voltage	$V_{GS(th)}$	1.2		2.4	1	2	3	V
Gate-Body Leakage	$I_{GSS}$			$\pm 100$			$\pm 100$	nA
Zero Gate Voltage Drain Current	$I_{DSS}$			1			1	$\mu\text{A}$
On-State Drain Current	$V_{GS} = 10\text{ V}$ $I_{D(on)}$	50			50			A
Drain-Source On-Resistance	$V_{GS} = 10\text{ V}$ $r_{DS(on)}$		0.0046	0.0057			0.007	$\Omega$
	$V_{GS} = 4.5\text{ V}$		0.0062	0.0078			0.010	
Forward Transconductance	$g_{fs}$		70		20			S
Diode Forward Voltage	$V_{SD}$		0.9	1.5		1.2	1.5	V
<b>Dynamic</b>								
Total Charge	$Q_g$		62	NS		70	130	nC
Gate-Source Charge	$Q_{gs}$		11			16		
Gate-Drain Charge	$Q_{gd}$		9			10		
Gate Resistance	$R_g$	NS	0.9	1.4	0.5		3.1	$\Omega$
<b>Switching</b>								
Turn-On Time	$t_{d(on)}$		12	18		14	30	ns
	$t_r$		10	15		11	20	
Turn-Off Time	$t_{d(off)}$		30	45		60	120	
	$t_f$		8	12		15	40	
Source-Drain Reverse Recovery Time	$t_{rr}$		65	100		55	100	

NS denotes parameter not specified

Specification comparisons are supplied as a courtesy to compare two devices and do not constitute a commercial product datasheet or any guarantee of identical performance. Designers should refer to the appropriate datasheets of the same number for guaranteed specification limits.