


Glass Passivated Junction Plastic Controlled Avalanche Rectifier



* Glass-plastic encapsulation technique is covered by Patent No. 3,996,602 of 1976; brazed-lead assembly by Patent No. 3,930,306 of 1976 and glass composition by Patent No. 3,752,701 of 1973

DO-204AC (DO-15)
FEATURES

- Superrectifier structure for high reliability application
- Cavity-free glass-passivated junction
- Controlled avalanche characteristics
- Low forward voltage drop
- Low leakage current, I_R less than 0.1 μA
- High forward surge capability
- Meets environmental standard MIL-S-19500
- Solder dip 260 °C, 40 s
- Component in accordance to RoHS 2002/95/EC and WEEE 2002/96/EC


**RoHS
COMPLIANT**
PRIMARY CHARACTERISTICS

$I_{F(AV)}$	1.5 A
V_{RRM}	400 V to 800 V
P_{RM}	500 W
I_{FSM}	50 A
I_R	5.0 μA
V_F	1.1 V
T_J max.	175 °C

TYPICAL APPLICATIONS

For use in general purpose rectification of power supplies, inverters, converters and freewheeling diodes application.

MECHANICAL DATA

Case: DO-204AC, molded epoxy over glass body

Epoxy meets UL 94V-0 flammability rating

Terminals: Matte tin plated leads, solderable per J-STD-002 and JESD22-B102

E3 suffix for consumer grade, meets JESD 201 class 1A whisker test, HE3 suffix for high reliability grade (AEC Q101 qualified), meets JESD 201 class 2 whisker test

Polarity: Color band denotes cathode end

MAXIMUM RATINGS ($T_A = 25$ °C unless otherwise noted)

PARAMETER	SYMBOL	AGP15-400	AGP15-600	AGP15-800	UNIT
Maximum recurrent peak reverse voltage	V_{RRM}	400	600	800	V
Maximum RMS voltage	V_{RMS}	280	420	560	V
Maximum DC blocking voltage	V_{DC}	400	600	800	V
Maximum peak power dissipation in the avalanche region 20 μs Pulse	P_{RM}	500			W
Maximum average forward rectified current 0.375" (9.5 mm) Lead Lengths at $T_A = 55$ °C	I_{AV}	1.5			A
Peak forward surge current 8.3 ms single half sine-wave superimposed on rated load	I_{FSM}	50			A
Maximum full load reverse current, full cycle average 0.375" (9.5 mm) lead length at $T_A = 55$ °C	$I_{R(AV)}$	100			μA
Operating and storage temperature range	T_J, T_{STG}	- 65 to + 175			°C



ELECTRICAL CHARACTERISTICS ($T_A = 25\text{ }^\circ\text{C}$ unless otherwise noted)						
PARAMETER	TEST CONDITIONS	SYMBOL	AGP15-400	AGP15-600	AGP15-800	UNIT
Minimum avalanche breakdown voltage	100 μA	V_{BR}	450	675	880	V
Maximum avalanche breakdown voltage	100 μA	V_{BR}	750	1000	1200	V
Maximum instantaneous forward voltage	1.5 A	V_F	1.1			V
Maximum reverse current at rated DC blocking voltage		I_R	5.0			μA
Typical reverse recovery time	$I_F = 0.5\text{ A}$, $I_R = 1.0\text{ A}$, $t_{rr} = 0.25\text{ A}$	t_{rr}	2.0			μs
Typical junction capacitance	4.0 V, 1 MHz	C_J	15			pF

THERMAL CHARACTERISTICS ($T_A = 25\text{ }^\circ\text{C}$ unless otherwise noted)					
PARAMETER	SYMBOL	AGP15-400	AGP15-600	AGP15-800	UNIT
Typical thermal resistance ⁽¹⁾	$R_{\theta JA}$	25			$^\circ\text{C/W}$

Note:

(1) Thermal resistance from junction to ambient at 0.375" (9.5 mm) lead length, P.C.B. mounted

ORDERING INFORMATION (Example)				
PREFERRED P/N	UNIT WEIGHT (g)	PREFERRED PACKAGE CODE	BASE QUANTITY	DELIVERY MODE
AGP15-400-E3/54	0.425	54	4000	13" diameter paper tape and reel
AGP15-400-E3/73	0.425	73	2000	Ammo pack packaging
AGP15-400HE3/54 ⁽¹⁾	0.425	54	4000	13" diameter paper tape and reel
AGP15-400HE3/73 ⁽¹⁾	0.425	73	2000	Ammo pack packaging

Note:

(1) Automotive grade AEC Q101 qualified

RATINGS AND CHARACTERISTICS CURVES

($T_A = 25\text{ }^\circ\text{C}$ unless otherwise noted)




Figure 1. Maximum Forward Current Derating Curve




Figure 2. Typical Instantaneous Forward Characteristics




Figure 3. Maximum Non-repetitive Peak Forward Surge Current




Figure 5. Typical Reverse Leakage Characteristics





Figure 4. Maximum Non-repetitive Reverse Avalanche Power Dissipation

PACKAGE OUTLINE DIMENSIONS in inches (millimeters)

DO-204AC (DO-15)





Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.