


Solid Tantalum Surface Mount Capacitors

TANTAMOUNT® Conformal Coated, Extended Range, Military, MIL-PRF-55365/13 Qualified


FEATURES

- Weibull Failure Rates B, C, T
- Tape and Reel available per EIA 481
- Termination finishes available; Gold Plate, Solder Plated, and Hot Solder Dipped


RoHS*
COMPLIANT

PERFORMANCE CHARACTERISTICS
Operating Temperature: - 55 °C to + 125 °C
(Above 85 °C, voltage derating is required)

Capacitance Range: 0.33 µF to 330 µF
Capacitance Tolerance: ± 5 %, ± 10 %, ± 20 %
Voltage Rating: 4 V_{DC} to 35 V_{DC}

ORDERING INFORMATION								
CWR16	D	B	335	K	B	A	A	/TR
TYPE	VOLTAGE	TERMINATION FINISH	CAPACITANCE	CAPACITANCE TOLERANCE	FAILURE RATE %/1000 h	CASE CODE	SURGE CURRENT (OPTIONAL)	PACKAGING
	C = 4 V D = 6 V F = 10 V H = 15 V J = 20 V K = 25 V M = 35 V	B = Gold H = Solder Plated C = Hot Solder Dipped	This is expressed in picofarads. The first two digits are the significant figures. The third is the number of zeros to follow.	J = ± 5 % K = ± 10 % M = ± 20 %	B = 0.1 C = 0.01 T = 0.01 ⁽¹⁾	A B C D E F G H	A = 10 cycles at + 25 °C B = 10 cycles at - 55 °C and + 85 °C C = 10 cycles at - 55 °C and + 85 °C (before Weibull Grading) Z = No surge current	Blank = Bulk, standard /HR = Halfreel, 7" (178 mm) reel /TR = 7" (178 mm) reel

Note

(1) T level capacitors are recommended for space applications

DIMENSIONS in inches [millimeters]							
CASE CODE	L	W	H	P	T ₁	T ₂ (MAX.)	
A	0.100 ± 0.015 [2.54 ± 0.38]	0.050 ± 0.015 [1.27 ± 0.38]	0.050 ± 0.015 [1.27 ± 0.38]	0.030 ± 0.005 [0.76 ± 0.13]	0.005 [0.13]	0.015 [0.38]	
B	0.150 ± 0.015 [3.81 ± 0.38]	0.050 ± 0.015 [1.27 ± 0.38]	0.050 ± 0.015 [1.27 ± 0.38]	0.030 ± 0.005 [0.76 ± 0.13]	0.005 [0.13]	0.015 [0.38]	
C	0.200 ± 0.015 [5.08 ± 0.38]	0.050 ± 0.015 [1.27 ± 0.38]	0.050 ± 0.015 [1.27 ± 0.38]	0.030 ± 0.005 [0.76 ± 0.13]	0.005 [0.13]	0.015 [0.38]	
D	0.150 ± 0.015 [3.81 ± 0.38]	0.100 ± 0.015 [2.54 ± 0.38]	0.050 ± 0.015 [1.27 ± 0.38]	0.030 ± 0.005 [0.76 ± 0.13]	0.005 [0.13]	0.015 [0.38]	
E	0.200 ± 0.015 [5.08 ± 0.38]	0.100 ± 0.015 [2.54 ± 0.38]	0.050 ± 0.015 [1.27 ± 0.38]	0.030 ± 0.005 [0.76 ± 0.13]	0.005 [0.13]	0.015 [0.38]	
F	0.220 ± 0.015 [5.59 ± 0.38]	0.135 ± 0.015 [3.43 ± 0.38]	0.070 ± 0.015 [1.78 ± 0.38]	0.030 ± 0.005 [0.76 ± 0.13]	0.005 [0.13]	0.015 [0.38]	
G	0.265 ± 0.015 [6.73 ± 0.38]	0.110 ± 0.015 [2.79 ± 0.38]	0.110 ± 0.015 [2.79 ± 0.38]	0.050 ± 0.005 [1.27 ± 0.13]	0.005 [0.13]	0.015 [0.38]	
H	0.285 ± 0.015 [7.24 ± 0.38]	0.150 ± 0.015 [3.81 ± 0.38]	0.110 ± 0.015 [2.79 ± 0.38]	0.050 ± 0.005 [1.27 ± 0.13]	0.005 [0.13]	0.015 [0.38]	

Note

When solder coated terminations are required, add 0.015" [0.38 mm] to termination dimension tolerance

* Pb containing terminations are not RoHS compliant, exemptions may apply

RATINGS AND CASE CODES							
μF	4 V	6 V	10 V	15 V	20 V	25 V	35 V
0.33							A
0.47						A	
0.68					A		
1.0				A	A	B	
1.5				A	B		
2.2			A	A	B	D	
3.3	A	A	A	B	D	E	
4.7	A	A	B, C	B, C, D	E		
6.8	A	B	B, C, D	D, E	E	F	G
10	B	B	B, C, D, E	D, E	E, F		H
15	B	B, D, E	D, E	E, F	F	G	H
22	B, D	D, E	E	F	G	G, H	
33	D, E	E	F	F, G	H	H	
47	E	F	F, G	G, H	H		
68	E	F, G	G	G, H			
100	F	G	G, H	H			
150	G	G	H				
220	H	H	H				
330	H	H					

STANDARD RATINGS									
CAPACITANCE (μF)	CASE CODE	PART NUMBER	MAX. DCL (μA) AT			MAX. DF (%) AT			MAX. ESR AT + 25 °C 100 kHz (Ω)
			+ 25 °C	+ 85 °C	+ 125 °C	+ 25 °C	+ 85 °C + 125 °C	- 55 °C	
4 V _{DC} AT + 85 °C, 2.7 V _{DC} AT + 125 °C									
3.3	A	CWR16C(1)335(2)(3)A(4)	1	10	12	6	8	8	12
4.7	A	CWR16C(1)475(2)(3)A(4)	1	10	12	6	8	8	12
6.8	A	CWR16C(1)685(2)(3)A(4)	1	10	12	6	8	8	12
10	B	CWR16C(1)106(2)(3)B(4)	1	10	12	8	10	10	8
15	B	CWR16C(1)156(2)(3)B(4)	1	10	12	8	10	10	8
22	B	CWR16C(1)226(2)(3)B(4)	1	10	12	8	10	10	8
22	D	CWR16C(1)226(2)(3)D(4)	1	10	12	8	10	12	4
33	D	CWR16C(1)336(2)(3)D(4)	2	20	24	8	10	12	4
33	E	CWR16C(1)336(2)(3)E(4)	2	20	24	8	10	12	3
47	E	CWR16C(1)476(2)(3)E(4)	2	20	24	8	10	12	3
68	E	CWR16C(1)686(2)(3)E(4)	3	30	36	8	10	12	3
100	F	CWR16C(1)107(2)(3)F(4)	4	40	48	10	12	12	2
150	G	CWR16C(1)157(2)(3)G(4)	6	60	72	10	12	12	1
220	H	CWR16C(1)227(2)(3)H(4)	8	80	96	10	12	12	1
330	H	CWR16C(1)337(2)(3)H(4)	10	100	120	10	12	12	0.9

Notes

- (1) = Termination Finish: B, C, H
(2) = Capacitance Tolerance: J, K, M
(3) = Failure Rate: B, C, T
(4) = Surge Current: A, B, C, Z



Solid Tantalum Surface Mount Capacitors
TANTAMOUNT® Conformal Coated, Extended Range,
Military, MIL-PRF-55365/13 Qualified

Vishay Sprague

STANDARD RATINGS									
CAPACITANCE (µF)	CASE CODE	PART NUMBER	MAX. DCL (µA) AT			MAX. DF (%) AT			MAX. ESR AT + 25 °C 100 kHz (Ω)
			+ 25 °C	+ 85 °C	+ 125 °C	+ 25 °C	+ 85 °C + 125 °C	- 55 °C	
6 V_{DC} AT + 85 °C, 4 V_{DC} AT + 125 °C									
3.3	A	CWR16D(1)335(2)(3)A(4)	1	10	12	6	8	8	12
4.7	A	CWR16D(1)475(2)(3)A(4)	1	10	12	6	8	8	12
6.8	B	CWR16D(1)685(2)(3)B(4)	1	10	12	6	8	8	8
10	B	CWR16D(1)106(2)(3)B(4)	1	10	12	6	8	8	8
15	B	CWR16D(1)156(2)(3)B(4)	1	10	12	8	10	10	8
15	D	CWR16D(1)156(2)(3)D(4)	1	10	12	8	10	12	5
15	E	CWR16D(1)156(2)(3)E(4)	1	10	12	8	10	12	3
22	D	CWR16D(1)226(2)(3)D(4)	1	10	12	6	8	8	5
22	E	CWR16D(1)226(2)(3)E(4)	2	20	24	8	10	12	3.5
33	E	CWR16D(1)336(2)(3)E(4)	2	20	24	6	8	8	3.5
47	F	CWR16D(1)476(2)(3)F(4)	3	30	36	8	10	12	3.5
68	F	CWR16D(1)686(2)(3)F(4)	4	40	48	10	12	12	1.5
68	G	CWR16D(1)686(2)(3)G(4)	4	40	48	10	12	12	1
100	G	CWR16D(1)107(2)(3)G(4)	6	60	72	10	12	12	1.1
150	G	CWR16D(1)157(2)(3)G(4)	10	100	120	10	12	12	1.1
220	H	CWR16D(1)227(2)(3)H(4)	10	100	120	10	12	12	0.9
330	H	CWR16D(1)337(2)(3)H(4)	20	200	240	10	12	12	0.9
10 V_{DC} AT + 85 °C, 7 V_{DC} AT + 125 °C									
2.2	A	CWR16F(1)225(2)(3)A(4)	1	10	12	6	8	8	12
3.3	A	CWR16F(1)335(2)(3)A(4)	1	10	12	6	8	8	12
4.7	B	CWR16F(1)475(2)(3)B(4)	1	10	12	6	8	8	8
4.7	C	CWR16F(1)475(2)(3)C(4)	1	10	12	6	8	8	5.5
6.8	B	CWR16F(1)685(2)(3)B(4)	1	10	12	6	8	8	8
6.8	C	CWR16F(1)685(2)(3)C(4)	1	10	12	6	8	8	5.5
6.8	D	CWR16F(1)685(2)(3)D(4)	1	10	12	6	8	8	5
10	B	CWR16F(1)106(2)(3)B(4)	1	10	12	8	10	10	8
10	C	CWR16F(1)106(2)(3)C(4)	1	10	12	6	8	8	5.5
10	D	CWR16F(1)106(2)(3)D(4)	1	10	12	6	8	8	4
10	E	CWR16F(1)106(2)(3)E(4)	1	10	12	6	8	8	3.5
15	D	CWR16F(1)156(2)(3)D(4)	1	10	12	6	8	8	5
15	E	CWR16F(1)156(2)(3)E(4)	2	20	24	8	10	10	3
22	E	CWR16F(1)226(2)(3)E(4)	3	30	36	8	10	10	2
33	F	CWR16F(1)336(2)(3)F(4)	3	30	36	8	10	10	1.5
47	F	CWR16F(1)476(2)(3)F(4)	4	40	48	10	12	12	1.5
47	G	CWR16F(1)476(2)(3)G(4)	4	40	48	10	12	12	1
68	G	CWR16F(1)686(2)(3)G(4)	6	60	72	10	12	12	1.1
100	G	CWR16F(1)107(2)(3)G(4)	10	100	120	10	12	12	1.1
100	H	CWR16F(1)107(2)(3)H(4)	10	100	120	10	12	12	0.9
150	H	CWR16F(1)157(2)(3)H(4)	15	150	180	10	12	12	0.9
220	H	CWR16F(1)227(2)(3)H(4)	20	200	240	10	12	12	0.9

Notes

- (1) = Termination Finish: B, C, H
- (2) = Capacitance Tolerance: J, K, M
- (3) = Failure Rate: B, C, T
- (4) = Surge Current: A, B, C, Z

Solid Tantalum Surface Mount Capacitors
 TANTAMOUNT® Conformal Coated, Extended Range,
 Military, MIL-PRF-55365/13 Qualified

STANDARD RATINGS									
CAPACITANCE (µF)	CASE CODE	PART NUMBER	MAX. DCL (µA) AT			MAX. DF (%) AT			MAX. ESR AT + 25 °C 100 kHz (Ω)
			+ 25 °C	+ 85 °C	+ 125 °C	+ 25 °C	+ 85 °C + 125 °C	- 55 °C	
15 V_{DC} AT + 85 °C, 10 V_{DC} AT + 125 °C									
1	A	CWR16H(1)105(2)(3)A(4)	1	10	12	6	8	8	15
1.5	A	CWR16H(1)155(2)(3)A(4)	1	10	12	6	8	8	15
2.2	A	CWR16H(1)225(2)(3)A(4)	1	10	12	6	8	8	15
3.3	B	CWR16H(1)335(2)(3)B(4)	1	10	12	6	8	8	9
4.7	B	CWR16H(1)475(2)(3)B(4)	1	10	12	6	8	8	5
4.7	C	CWR16H(1)475(2)(3)C(4)	1	10	12	6	8	8	5.5
4.7	D	CWR16H(1)475(2)(3)D(4)	1	10	12	6	8	8	6
6.8	D	CWR16H(1)685(2)(3)D(4)	1	10	12	6	8	8	6
6.8	E	CWR16H(1)685(2)(3)E(4)	1	10	12	8	10	12	3
10	D	CWR16H(1)106(2)(3)D(4)	2	20	24	6	8	8	6
10	E	CWR16H(1)106(2)(3)E(4)	2	20	24	6	8	8	4
15	E	CWR16H(1)156(2)(3)E(4)	2	20	24	6	8	8	4
15	F	CWR16H(1)156(2)(3)F(4)	2	20	24	8	10	10	3
22	F	CWR16H(1)226(2)(3)F(4)	3	30	36	8	10	10	3
33	F	CWR16H(1)336(2)(3)F(4)	5	50	60	6	8	8	3
33	G	CWR16H(1)336(2)(3)G(4)	6	60	72	8	10	10	1.1
47	G	CWR16H(1)476(2)(3)G(4)	10	100	120	8	10	10	1.1
47	H	CWR16H(1)476(2)(3)H(4)	10	100	120	8	10	10	0.9
68	G	CWR16H(1)686(2)(3)G(4)	10	100	120	8	10	10	1.1
68	H	CWR16H(1)686(2)(3)H(4)	10	100	120	8	10	10	0.9
100	H	CWR16H(1)107(2)(3)H(4)	15	150	180	10	12	12	0.9
20 V_{DC} AT + 85 °C, 13 V_{DC} AT + 125 °C									
0.68	A	CWR16J(1)684(2)(3)A(4)	1	10	12	6	8	8	15
1	A	CWR16J(1)105(2)(3)A(4)	1	10	12	6	8	8	15
1.5	B	CWR16J(1)155(2)(3)B(4)	1	10	12	6	8	8	9
2.2	B	CWR16J(1)225(2)(3)B(4)	1	10	12	6	8	8	9
3.3	D	CWR16J(1)335(2)(3)D(4)	1	10	12	6	8	8	6
4.7	E	CWR16J(1)475(2)(3)E(4)	1	10	12	6	8	8	6
6.8	E	CWR16J(1)685(2)(3)E(4)	2	20	24	6	8	8	5
10	E	CWR16J(1)106(2)(3)E(4)	2	20	24	6	8	8	5
10	F	CWR16J(1)106(2)(3)F(4)	2	20	24	6	8	8	3
15	F	CWR16J(1)156(2)(3)F(4)	3	30	36	6	8	8	3
22	G	CWR16J(1)226(2)(3)G(4)	4	40	48	8	10	10	2.5
33	H	CWR16J(1)336(2)(3)H(4)	6	60	72	8	10	10	0.9
47	H	CWR16J(1)476(2)(3)H(4)	10	100	120	8	10	10	0.9
25 V_{DC} AT + 85 °C, 17 V_{DC} AT + 125 °C									
0.47	A	CWR16K(1)474(2)(3)A(4)	1	10	12	6	8	8	15
1	B	CWR16K(1)105(2)(3)B(4)	1	10	12	6	8	8	10
2.2	D	CWR16K(1)225(2)(3)D(4)	1	10	12	6	8	8	6
3.3	E	CWR16K(1)335(2)(3)E(4)	1	10	12	6	8	8	4
6.8	F	CWR16K(1)685(2)(3)F(4)	2	20	24	6	8	8	3
15	G	CWR16K(1)156(2)(3)G(4)	4	40	48	6	8	8	1.4
22	G	CWR16K(1)226(2)(3)G(4)	6	60	72	6	8	8	1.4
22	H	CWR16K(1)226(2)(3)H(4)	6	60	72	6	8	8	0.9
33	H	CWR16K(1)336(2)(3)H(4)	10	100	120	8	10	10	0.9
35 V_{DC} AT + 85 °C, 23 V_{DC} AT + 125 °C									
0.33	A	CWR16M(1)334(2)(3)A(4)	1	10	12	6	8	8	22
6.8	G	CWR16M(1)685(2)(3)G(4)	3	30	36	6	8	8	1.5
10	H	CWR16M(1)106(2)(3)H(4)	4	40	48	8	10	10	0.9
15	H	CWR16M(1)156(2)(3)H(4)	6	60	72	6	8	8	0.9

Notes


- (1) = Termination Finish: B, C, H
- (2) = Capacitance Tolerance: J, K, M
- (3) = Failure Rate: B, C, T
- (4) = Surge Current: A, B, C, Z

Solid Tantalum Surface Mount Capacitors
TANTAMOUNT[®] Conformal Coated, Extended Range,
 Military, MIL-PRF-55365/13 Qualified

TAPE AND REEL PACKAGING in inches [millimeters]

Note

• Metric dimensions will govern. Dimensions in inches are rounded and for reference only.



Notes

- (1) A_0, B_0, K_0 are determined by the maximum dimensions to the ends of the terminals extending from the component body and/or the body dimensions of the component. The clearance between the ends of the terminals or body of the component to the sides and depth of the cavity (A_0, B_0, K_0) must be within 0.002" (0.05 mm) minimum and 0.020" (0.50 mm) maximum. The clearance allowed must also prevent rotation of the component within the cavity of not more than 20 degrees.
- (2) Tape with components shall pass around radius "R" without damage. The minimum trailer length may require additional length to provide "R" minimum for 12 mm embossed tape for reels with hub diameters approaching N minimum.
- (3) This dimension is the flat area from the edge of the sprocket hole to either outward deformation of the carrier tape between the embossed cavities or to the edge of the cavity whichever is less.
- (4) This dimension is the flat area from the edge of the carrier tape opposite the sprocket holes to either the outward deformation of the carrier tape between the embossed cavity or to the edge of the cavity whichever is less.
- (5) The embossed hole location shall be measured from the sprocket hole controlling the location of the embossement. Dimensions of embossement location shall be applied independent of each other.
- (6) B_1 dimension is a reference dimension tape feeder clearance only.

Solid Tantalum Surface Mount Capacitors
TANTAMOUNT® Conformal Coated, Extended Range,
 Military, MIL-PRF-55365/13 Qualified

CARRIER TAPE DIMENSIONS in inches [millimeters]							
CWR06/CWR16							
CASE CODE	TAPE SIZE	B ₁ (max.)	D ₁ (min.)	F	P ₁	T ₂ (max.)	W
A	8 mm	0.179 [4.55]	0.039 [1.0]	0.138 ± 0.002 [3.5 ± 0.05]	0.157 ± 0.004 [4.0 ± 0.1]	0.098 [2.5]	0.315 ± 0.004 [8.0 ± 0.10]
B, C, D, E	12 mm	0.323 [8.2]	0.059 [1.5]	0.217 ± 0.002 [5.5 ± 0.05]	0.157 ± 0.004 [4.0 ± 0.1]	0.256 [6.5]	0.472 ± 0.012 [12.0 ± 0.30]
F	12 mm Double pitch	0.323 [8.2]	0.059 [1.5]	0.217 ± 0.002 [5.5 ± 0.05]	0.315 ± 0.004 [8.0 ± 0.10]	0.256 [6.5]	0.472 ± 0.012 [12.0 ± 0.30]
G, H	16 mm	0.476 [12.1]	0.059 [1.5]	0.295 ± 0.004 [7.5 ± 0.1]	0.315 ± 0.004 [8.0 ± 0.10]	0.315 [8.0]	0.642 Max. [16.3] Max.

STANDARD PACKAGING QUANTITY			
SERIES	CASE CODE	QUANTITY (PCS/REEL)	
		7" REEL	HALF REEL
CWR06/CWR16	A, B, C, D, E	2500	1250
	F	1000	500
	G, H	600	300

PAD DIMENSIONS in inches [millimeters]			
			
CWR06/CWR16			
CASE CODE	WIDTH (A)	PAD METALLIZATION (B)	SEPARATION (C)
A	0.065 [1.6]	0.50 [1.3]	0.040 [1.0]
B	0.065 [1.6]	0.70 [1.8]	0.055 [1.4]
C	0.065 [1.6]	0.70 [1.8]	0.120 [3.0]
D	0.115 [2.9]	0.70 [1.8]	0.070 [1.8]
E	0.115 [2.9]	0.70 [1.8]	0.120 [3.0]
F	0.150 [3.8]	0.70 [1.8]	0.140 [3.6]
G	0.125 [3.2]	0.70 [1.8]	0.170 [4.3]
H	0.165 [4.2]	0.90 [2.3]	0.170 [4.3]

POWER DISSIPATION		
SERIES	CASE CODE	MAXIMUM PERMISSIBLE POWER DISSIPATION AT + 25 °C (W) IN FREE AIR
CWR06/CWR16	A	0.06
	B, C	0.075
	D, E	0.085
	F	0.11
	G	0.12
	H	0.15



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.