



Electrolyte Selector Guide

COATED CHIPS					
TYPE	CAPACITANCE RANGE (μF)	VOLTAGE (V)	TEMPERATURE RANGE	CASE SIZE	STANDARD OR SPECIFICATION
595D	0.1 to 1500	4 to 50	- 55 °C to + 125 °C	A, B, C, D, G, H, M, R, S, T	Similar to EIA, Maximum CV, 0805 Size
594D	1.0 to 1500	4 to 50	- 55 °C to + 125 °C	B, C, D, R	Low ESR
592D	1.0 to 3300	4 to 35	- 55 °C to + 125 °C	A, B, C, D, R, S, X	Low Profile; Maximum CV
591D	1.0 to 1000	4 to 35	- 55 °C to + 125 °C	A, B, C, D, R	Low Profile; Low ESR
572D	2.2 to 220	4 to 35	- 55 °C to + 125 °C	A, B, P, Q, S, T	Low Profile; Maximum CV; Single-Sided Anode
597D	22 to 1500	4 to 50	- 55 °C to + 125 °C	E, F, R, V	Multi-Anode; Ultra Low ESR
695D	0.1 to 270	4 to 50	- 55 °C to + 125 °C	A, B, D, E, F, G, H	MIL-C-556365/4
CWR06	0.1 to 100	4 to 50	- 55 °C to + 125 °C	A, B, C, D, E, F, G, H	MIL-C-556365/4
195D	0.1 to 330	2 to 50	- 55 °C to + 125 °C	A, B, C, D, E, F, G, H, R, S, V, X, Y, Z	Conformal US and European Case Sizes
194D	0.1 to 150	4 to 50	- 55 °C to + 125 °C	A, B, C, D, E, F, G, H	MIDGET® Conformal
CC/EC	0.1 to 220	4 to 50	- 55 °C to + 125 °C	A, B, C, D, E, F, G, H	CCEC, 3801/006/008-CTC2
T95	0.1 to 680	4 to 50	- 55 °C to + 125 °C	A, B, C, D, R, V, X, Y, Z	Hi-Rel COTS; Standard and Low ESR
T96	10 to 680	4 to 50	- 55 °C to + 125 °C	R	Hi-Rel COTS, Built-In Fuse
T97	15 to 1500	4 to 63	- 55 °C to + 125 °C	E, F, R, V, Z	Ultra Low ESR, Hi-Rel COTS
T98	15 to 1500	4 to 63	- 55 °C to + 125 °C	E, F, R, V, Z	Ultra Low ESR, Hi-Rel COTS; Built-In Fuse

MOLDED CHIPS					
TYPE	CAPACITANCE RANGE (μF)	VOLTAGE (V)	TEMPERATURE RANGE	CASE SIZE	STANDARD OR SPECIFICATION
292D	1.0 to 47	3 to 20	- 55 °C to + 125 °C	P, R	Lead Frameless, 0805 size
293D	0.1 to 680	4 to 50	- 55 °C to + 125 °C	A, B, C, D, E, P	Standard Type 793DX = CECC 30801-005 CTC3 = CECC 30801-009 CTC4 = CECC 30801-011 793DE = CECC 30801-801
593D	0.47 to 680	4 to 50	- 55 °C to + 125 °C	A, B, C, D, E	Low ESR, 100 % Surged (B, C, D, E)
298D	1 to 47	4 to 16	- 55 °C to + 125 °C	M, S	0805, 0603 sizes
TR3	0.47 to 680	4 to 50	- 55 °C to + 125 °C	A, B, C, D, E	Low ESR, 100 % Surged (B, C, D, E)
T83	0.1 to 330	4 to 50	- 55 °C to + 125 °C	A, B, C, D, E	Molded Hi-Rel COTS
893D	1.0 to 220	6.3 to 50	- 55 °C to + 125 °C	C, D, E	Built - In Fuse
CWR11	0.1 to 100	4 to 50	- 55 °C to + 125 °C	A, B, C, D	MIL-PRF-5536518
TH3	0.33 to 100	10 to 50	- 55 °C to + 150 °C	A, B, C, D, E	Molded Extended Temperature
TP3	0.1 to 470	4 to 50	- 55 °C to + 125 °C	A, B, C, D, E	Molded High Performance
TF3	0.47 to 470	4 to 50	- 55 °C to + 125 °C	A, B, C, D, E	Built-In Fuse
TR8	0.68 to 220	2.5 to 50	- 55 °C to + 125 °C	M, P	L-Shaped, Face Down Terminations, Leadframeless