

High Current, Surface Mount Inductors



STANDARD ELECTRICAL SPECIFICATIONS			
IND. AT 1 kHz (μH)	DCR MAX. (Ω)	RATED CURRENT MAX. (A)	INCREMENTAL CURRENT APPROX. (A)
1.0	0.015	5.11	4.41
1.2	0.016	4.93	4.11
1.5	0.017	4.63	3.66
1.8	0.022	4.27	3.22
2.2	0.031	3.61	2.62
2.7	0.038	3.18	2.40
3.3	0.045	2.94	2.13
3.9	0.062	2.57	2.05
4.7	0.083	2.17	1.93
5.6	0.091	2.08	1.79
6.8	0.101	1.94	1.62
8.2	0.118	1.83	1.50
10.0	0.126	1.74	1.36
12.0	0.170	1.50	1.26
15.0	0.228	1.29	1.11
18.0	0.306	1.13	1.05
22.0	0.336	1.05	0.96
27.0	0.389	0.98	0.86
33.0	0.440	0.92	0.75
39.0	0.490	0.86	0.72
47.0	0.646	0.74	0.68
56.0	0.845	0.65	0.64
68.0	1.040	0.61	0.58
82.0	1.240	0.56	0.51
100.0	1.440	0.48	0.42
120.0	2.180	0.45	0.40
150.0	2.900	0.38	0.37
180.0	3.280	0.36	0.33
220.0	3.650	0.34	0.28
270.0	4.400	0.29	0.26
330.0	5.070	0.27	0.23
390.0	5.900	0.23	0.20
470.0	7.670	0.22	0.19
560.0	8.850	0.21	0.17
680.0	10.20	0.18	0.15
820.0	11.58	0.17	0.14
1000.0	12.97	0.16	0.13

FEATURES

- Flame retardant encapsulant (UL 94 V-0)
- Completely encapsulated winding provides superior environmental protection and moisture resistance
- High current unit in surface mount package printed with model, inductance value and date code
- Compatible with infrared or conventional reflow soldering methods
- Pick and place compatible
- Compliant to RoHS directive 2002/95/EC



APPLICATIONS

Excellent power line noise filters, filters for switching regulated power supplies, dc-to-dc converters, SCR and Triac controls and RFI suppression.

ELECTRICAL SPECIFICATIONS

Inductance: Measured at 1 V with no DC current

Inductance Tolerance: ± 15 %

Incremental Current: The typical current at which the inductance will be decreased by 5 % from its initial zero DC value

Operating Temperature: - 55 °C to + 125 °C (no load); - 55 °C to + 85 °C (at full rated current)


MECHANICAL SPECIFICATIONS

Core: High resistivity ferrite core

Encapsulant: Epoxy

Terminals: 100 % Sn over Ni

DIMENSIONS in inches [millimeters]




PART MARKING

- Model
- Inductance value
- Date code

DESCRIPTION

IHSM-3825	3.9 μH	± 15 %	ER	e3
MODEL	INDUCTANCE VALUE	INDUCTANCE TOLERANCE	PACKAGE CODE	JEDEC LEAD (Pb)-FREE STANDARD

GLOBAL PART NUMBER





Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.