


R-C Thermal Model Parameters

DESCRIPTION

The parametric values in the R-C thermal model have been derived using curve-fitting techniques. R-C values for the electrical circuit in the Foster/tank and Cauer/filter configurations are included. When implemented in P-SPICE, these values have matching characteristic curves to the single-pulse transient thermal impedance curves for the MOSFET.

These RC values can be used in the P-SPICE simulation to evaluate the thermal behavior of the MOSFET junction temperature under a defined power profile. These techniques are described in application note AN609, "Thermal Simulation of Power MOSFETs on the P-SPICE Platform".

R-C THERMAL MODEL FOR TANK CONFIGURATION



R-C VALUES FOR TANK CONFIGURATION			
THERMAL RESISTANCE (°C/W)			
Junction to	Ambient	Case	Foot
RT1	N/A	40.0980 m	N/A
RT2	N/A	102.2031 m	N/A
RT3	N/A	56.7832 m	N/A
RT4	N/A	140.9157 m	N/A
THERMAL CAPACITANCE (Joules/°C)			
Junction to	Ambient	Case	Foot
CT1	N/A	4.2063 m	N/A
CT2	N/A	28.6902 m	N/A
CT3	N/A	385.0887 m	N/A
CT4	N/A	84.6591 m	N/A


Note

- N/A indicates not applicable

This document is intended as a SPICE modeling guideline and does not constitute a commercial product datasheet. Designers should refer to the appropriate datasheet of the same number for guaranteed specification limits.



R-C THERMAL MODEL FOR FILTER CONFIGURATION



R-C VALUES FOR FILTER CONFIGURATION			
THERMAL RESISTANCE (°C/W)			
Junction to	Ambient	Case	Foot
RF1	N/A	61.0101 m	N/A
RF2	N/A	97.6357 m	N/A
RF3	N/A	78.9037 m	N/A
RF4	N/A	102.4505 m	N/A
THERMAL CAPACITANCE (Joules/°C)			
Junction to	Ambient	Case	Foot
CF1	N/A	3.6933 m	N/A
CF2	N/A	16.7189 m	N/A
CF3	N/A	12.2273 m	N/A
CF4	N/A	89.0793 m	N/A

Note

- N/A indicates not applicable

