


R-C Thermal Model Parameters

DESCRIPTION

The parametric values in the R-C thermal model have been derived using curve-fitting techniques. R-C values for the electrical circuit in the Foster/tank and Cauer/filter configurations are included. When implemented in P-SPICE, these values have matching characteristic curves to the single-pulse transient thermal impedance curves for the MOSFET.

These RC values can be used in the P-SPICE simulation to evaluate the thermal behavior of the MOSFET junction temperature under a defined power profile. These techniques are described in application note AN609, "Thermal Simulation of Power MOSFETs on the P-SPICE Platform".

R-C THERMAL MODEL FOR TANK CONFIGURATION



R-C VALUES FOR TANK CONFIGURATION			
THERMAL RESISTANCE (°C/W)			
Junction to	Ambient	Case	Foot
RT1	N/A	31.7384 m	N/A
RT2	N/A	141.3339 m	N/A
RT3	N/A	71.3964 m	N/A
RT4	N/A	45.5313 m	N/A
THERMAL CAPACITANCE (Joules/°C)			
Junction to	Ambient	Case	Foot
CT1	N/A	4.6873 m	N/A
CT2	N/A	68.0898 m	N/A
CT3	N/A	28.7045 m	N/A
CT4	N/A	1.5589	N/A


Note

- N/A indicates not applicable

This document is intended as a SPICE modeling guideline and does not constitute a commercial product datasheet. Designers should refer to the appropriate datasheet of the same number for guaranteed specification limits.



R-C THERMAL MODEL FOR FILTER CONFIGURATION



R-C VALUES FOR FILTER CONFIGURATION			
THERMAL RESISTANCE (°C/W)			
Junction to	Ambient	Case	Foot
RF1	N/A	30.9003 m	N/A
RF2	N/A	101.8109 m	N/A
RF3	N/A	115.6899 m	N/A
RF4	N/A	41.5989 m	N/A
THERMAL CAPACITANCE (Joules/°C)			
Junction to	Ambient	Case	Foot
CF1	N/A	2.7820 m	N/A
CF2	N/A	12.9709 m	N/A
CF3	N/A	45.7452 m	N/A
CF4	N/A	1.3404	N/A

Note

- N/A indicates not applicable

