


## Surface Mount TRANSZORB<sup>®</sup> Transient Voltage Suppressors



PRIMARY CHARACTERISTICS	
$V_{WM}$	3.3 V
$P_{PPM}$	100 W
$I_{FSM}$	25 A
$T_J$ max.	150 °C

### TYPICAL APPLICATIONS

Use in sensitive electronics protection against voltage transients induced by inductive load switching and lighting on ICs, MOSFET, signal lines of sensor units specifically for protecting 3.3 V supplied sensitive equipment against transient overvoltages.

### FEATURES

- Very low profile - typical height of 0.65 mm
- Ideal for automated placement
- Oxide planar chip junction
- Uni-directional polarity only
- Peak pulse power: 100 W (10/1000  $\mu$ s)
- ESD capability: 15 kV (air), 8 kV (contact)
- Meets MSL level 1, per J-STD-020C, LF maximum peak of 260 °C
- AEC-Q101 qualified
- Compliant to RoHS directive 2002/95/EC and in accordance to WEEE 2002/96/EC
- **Halogen-free according to IEC 61249-2-21 definition**



**RoHS**  
COMPLIANT  
HALOGEN  
FREE

### MECHANICAL DATA

**Case:** MicroSMP

Molding compound meets UL 94 V-0 flammability rating  
Base P/N-M3 - halogen-free and RoHS compliant, commercial grade

Base P/NHM3 - halogen-free and RoHS compliant, AEC-Q101 qualified

**Terminals:** Matte tin plated leads, solderable per J-STD-002 and JESD 22-B102

M3 suffix meets JESD 201 class 1A whisker test, HM3 suffix meets JESD 201 class 2 whisker test

**Polarity:** Color band denotes the cathode end

MAXIMUM RATINGS ( $T_A = 25$ °C unless otherwise noted)			
PARAMETER	SYMBOL	VALUE	UNIT
Peak pulse power dissipation	$P_{PPM}^{(1)(2)}$	100	W
Peak pulse current with a 10/1000 $\mu$ s waveform (fig. 1)	$I_{PPM}$	13.7	A
Peak pulse current with a 8/20 $\mu$ s waveform (fig. 1)	$I_{PPM}$	75	A
Non repetitive peak forward surge current 8.3 ms single half sine-wave	$I_{FSM}^{(2)}$	25	A
Power dissipation $T_L = 120$ °C	$P_D^{(2)}$	1.0	W
Operating junction and storage temperature range	$T_J, T_{STG}$	- 55 to + 150	°C

#### Notes

(1) Non-repetitive current pulse, per fig. 1

(2) Mounted on 6.0 mm x 6.0 mm copper pads to each terminal

ELECTRICAL CHARACTERISTICS ( $T_A = 25$ °C unless otherwise noted)											
DEVICE TYPE	DEVICE MARKING CODE	MIN. BREAKDOWN VOLTAGE $V_{BR}$ AT IT		MAX. REVERSE LEAKAGE CURRENT $I_R$ AT $V_{WM}$		MAX. CLAMPING VOLTAGE AT $V_C$ AT $I_{PPM}(10/1000 \mu s)$		MAX. CLAMPING VOLTAGE AT $V_C$ AT $I_{PPM}(8/20 \mu s)$		TYPICAL TEMPERATURE COEFFICIENT OF $V_{BR}$	TYP. JUNCTION CAPACITANCE $C_J$ AT 0 V (1 MHz)
		V	mA	$\mu$ A	V	V	A	V	A	(10 <sup>-4</sup> /°C)	pF
MSP3V3	KC	4.1	1.0	200	3.3	7.3	13.7	11.0	75	- 5.3	850

THERMAL CHARACTERISTICS ( $T_A = 25\text{ }^\circ\text{C}$ unless otherwise noted)			
PARAMETER	SYMBOL	VALUE	UNIT
Typical thermal resistance	$R_{\theta JA}^{(1)}$	125	$^\circ\text{C/W}$
	$R_{\theta JL}^{(1)}$	30	

**Note**

(1) Thermal resistance from junction to ambient and junction to lead mounted on P.C.B. with 6.0 mm x 6.0 mm copper pad areas.  $R_{\theta JL}$  is measured at the terminal of cathode band.

IMMUNITY TO STATIC ELECTRICAL DISCHARGE TO THE FOLLOWING STANDARDS ( $T_A = 25\text{ }^\circ\text{C}$ unless otherwise noted)					
STANDARD	TEST TYPE	TEST CONDITIONS	SYMBOL	CLASS	VALUE
AEC-Q101-001	Human body model (contact mode)	$C = 100\text{ pF}$ , $R = 1.5\text{ kW}$	$V_C$	H3B	$> 8\text{ kV}$
IEC 61000-4-2 (2)	Human body model (air discharge mode) (1)	$C = 150\text{ pF}$ , $R = 150\text{ W}$		4	$> 15\text{ kV}$

**Notes**

(1) Immunity to IEC 61000-4-2 air discharge mode has a typical performance  $> 30\text{ kV}$   
 (2) System ESD standard

ORDERING INFORMATION (Example)				
PREFERRED P/N	UNIT WEIGHT (g)	PREFERRED PACKAGE CODE	BASE QUANTITY	DELIVERY MODE
MSP3V3-M3/89A	0.006	89A	4500	7" diameter plastic tape and reel
MSP3V3HM3/89A (1)	0.006	89A	4500	7" diameter plastic tape and reel

**Note**

(1) AEC-Q101 qualified

**RATINGS AND CHARACTERISTICS CURVES**

( $T_A = 25\text{ }^\circ\text{C}$  unless otherwise noted)




Fig. 1 - Pulse Waveform




Fig. 2 - Peak Pulse Power Rating Curve




Fig. 3 - Relative Variation of Leakage Current vs. Junction Temperature




Fig. 5 - Typical Junction Capacitance




Fig. 4 - Typical Peak Forward Voltage Drop vs. Peak Forward Current





Fig. 6 - Typical Transient Thermal Impedance

**PACKAGE OUTLINE DIMENSIONS** in inches (millimeters)





## Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.