


TRANSZORB[®] Transient Voltage Suppressors



DO-204AL (DO-41)

PRIMARY CHARACTERISTICS	
V _{BR} uni-directional	530 V, 550 V
P _{PPM}	300 W
P _D	1.0 W
V _{WM}	477 V, 495 V
V _C	760 V
T _J max.	150 °C

FEATURES

- Glass passivated chip junction
- Available in uni-directional only
- Excellent clamping capability
- Very fast response time
- Low incremental surge resistance
- Solder dip 260 °C, 40 s
- Component in accordance to RoHS 2002/95/EC and WEEE 2002/96/EC


RoHS
COMPLIANT

TYPICAL APPLICATIONS

Use in sensitive electronics protection against voltage transients induced by inductive load switching and lighting on ICs, MOSFET, signal lines of sensor units for consumer, computer, industrial and telecommunication.

MECHANICAL DATA

Case: DO-204AL, molded epoxy over passivated chip
Molding compound meets UL 94 V-0 flammability rating

Base P/N-E3 - RoHS compliant, commercial grade

Terminals: Matte tin plated leads, solderable per J-STD-002 and JESD22-B102

E3 suffix meets JESD 201 class 1A whisker test

Polarity: Color band denotes cathode end

MAXIMUM RATINGS (T _A = 25 °C unless otherwise noted)				
PARAMETER	SYMBOL	P4KE530	P4KE550	UNIT
Power dissipation on infinite heatsink at T _L = 75 °C (Fig. 4)	P _D	1.0		W
Peak pulse power dissipation ⁽¹⁾⁽²⁾ (Fig. 1)	P _{PPM}	300		W
Stand-off voltage	V _{WM}	477	495	V
Operating junction and storage temperature range	T _J , T _{STG}	- 55 to + 150		°C

Notes:

(1) Non repetitive current pulse per Fig. 3 and derated above 25 °C per Fig. 2

(2) Peak pulse power waveform is 10/1000 μs

ELECTRICAL CHARACTERISTICS ($T_A = 25\text{ }^\circ\text{C}$ unless otherwise noted)					
PARAMETER	TEST CONDITIONS	SYMBOL	P4KE530	P4KE550	UNIT
Minimum breakdown voltage	100 μA	V_{BR}	530	550	V
Max. clamping voltage	400 mA, 10/1000 μs waveform	V_C	760		V
Maximum DC reverse leakage current	at V_{WM}	I_D	1.0		μA
Typical temperature coefficient	of V_{BR}		650		mV/ $^\circ\text{C}$
Typical capacitance	1 MHz, $V_R = 0\text{ V}$	C_J	90		pF
	1 MHz, $V_R = 200\text{ V}$	C_J	7.5		pF

THERMAL CHARACTERISTICS ($T_A = 25\text{ }^\circ\text{C}$ unless otherwise noted)				
PARAMETER	SYMBOL	P4KE530	P4KE550	UNIT
Typical thermal resistance, junction to lead	$R_{\theta JL}$	75		$^\circ\text{C/W}$
Typical thermal resistance, junction to ambient	$R_{\theta JA}$	125		$^\circ\text{C/W}$

ORDERING INFORMATION (Example)				
PREFERRED P/N	UNIT WEIGHT (g)	PREFERRED PACKAGE CODE	BASE QUANTITY	DELIVERY MODE
P4KE530-E3/54	0.350	54	5500	13" diameter paper tape and reel
P4KE550-E3/54	0.350	54	5500	13" diameter paper tape and reel

RATINGS AND CHARACTERISTICS CURVES

($T_A = 25\text{ }^\circ\text{C}$ unless otherwise noted)




Figure 1. Peak Pulse Power Rating Curve




Figure 2. Pulse Power or Current vs. Initial Junction Temperature




Figure 3. Pulse Waveform





Figure 4. Pulse Derating Curve

PACKAGE OUTLINE DIMENSIONS in inches (millimeters)

DO-204AL (DO-41)



APPLICATION NOTES

- Respect Thermal Resistance (PCB Layout) - as the temperature coefficient also contributes to the clamping voltage
- Select minimum breakdown voltage, so you get acceptable power dissipation and PCB tie point temperature. Devices with higher breakdown voltage will have a shorter conduction time and will dissipate less power
- Clamping voltage is influenced by internal resistance - design approximation is 7 V per 100 mA slope
- Keep temperature of TVS lower than TOPSwitch® as a recommendation
- Maximum current is determined by the maximum T_J and can be higher than 300 mA. Contact supplier for different clamping voltage/current arrangements
- Minimum breakdown voltage can be customized for other applications. Contact supplier
- TOPSwitch is a registered trademark of Power Integrations, Inc.



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.