

TELUX™ LEDS





TELUX™ LEDS


For Automotive and Outdoor Applications

High-performance Vishay TELUX™ LEDs feature a full color range of devices with a wide viewing angle and high luminous flux.

TELUX LEDs are especially designed for rough applications that require a high luminous intensity. These include automotive applications such as brake lights, taillights, and turn signals, as well as outdoor applications such as traffic signals, message panels, and warning lights.

TELUX LEDs are offered in red, yellow, true green, blue-green, blue, and white versions, and with a choice of 30°, 45°, and 55° angles of half intensity or oval emission characteristics with 25° x 68° and 40° x 90° angles of half intensity.

With their excellent luminous flux performance and extended operating temperature range from -40 °C to +110 °C, TELUX LEDs are the premier solution for all exterior automotive and outdoor LED applications.





Vishay Intertechnology www.vishay.com



CHARACTERISTICS							
Туре	Color (wavelength) (nm)	$\Phi_{_{\!\scriptscriptstyle V}}$ (mlm)		I _F	V _F	I _F	φ
		Min.	Тур.	(mA)	(V)	(mA)	(degrees)
TLWR7600	Red (618)	1500	2100	70	2.2 (< 2.67)	70	± 30
TLWR7900	Red (618)	1500	2100	70	2.2 (< 2.67)	70	± 45
TLWR8600	Red (615)	2000	3000	70	2.2 (< 2.67)	70	± 30
TLWR8900	Red (615)	2000	3000	70	2.2 (< 2.67)	70	± 45
TLWR9000	Red (615)	2500	3200	70	2.2 (< 2.7)	70	± 55
VLWR9430	Red (615)	5000	6000	70	2.5 (< 3.03)	70	25 x 68
VLWR9530	Red (615)	5000	6000	70	2.5 (< 3.03)	70	40 x 90
TLWR9600	Red (615)	2500	3200	70	2.2 (< 2.7)	70	± 30
VLWR9630	Red (615)	4000	7000	70	2.5 (< 3.03)	70	± 30
VLWR9631	Red (615)	5000	7000	70	2.5 (< 3.03)	70	± 30
TLWR9900	Red (615)	2500	3200	70	2.2 (< 2.7)	70	± 45
VLWR9930	Red (615)	4000	7000	70	2.5 (< 3.03)	70	± 45
TLWO7600	Soft Orange (605)	1500	2100	70	2.2 (< 2.67)	70	± 30
TLWO7900	Soft Orange (605)	1500	2100	70	2.2 (< 2.67)	70	± 45
TLWY7600	Yellow (592)	1000	1400	70	2.2 (< 2.67)	70	± 30
TLWY7900	Yellow (592)	1000	1400	70	2.2 (< 2.67)	70	± 45
TLWY8600	Yellow (592)	2000	3000	70	2.2 (< 2.67)	70	± 30
TLWY8900	Yellow (592)	2000	3000	70	2.2 (< 2.67)	70	± 45
VLWY9630	Yellow (592)	4000	7000	70	2.5 (< 3.03)	70	± 30
VLWY9930	Yellow (592)	4000	7000	70	2.5 (< 3.03)	70	± 45
VLWTG9600	True Green (523)	2000	2500	50	3.9 (< 4.7)	50	± 30
VLWTG9900	True Green (523)	2000	2500	50	3.9 (< 4.7)	50	± 45
VLWB9600	Blue (470)	800	1200	50	3.9 (< 4.7)	50	± 30
VLWB9900	Blue (470)	800	1200	50	3.9 (< 4.7)	50	± 45
VLWW9600	White	1500	2200	50	4.3 (< 5.2)	50	± 30
VLWW9601	White	2000	2500	50	4.3 (< 5.2)	50	± 30
VLWW9900	White	1500	2200	50	4.3 (< 5.2)	50	± 45

For technical support, contact: LED@vishay.com

For further information: http://www.vishay.com/ref/telux

DISCLAIMER All product specifications and data are subject to change without notice. Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product. Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications. Product names and markings noted herein may be trademarks of their respective owners.

Vishay Intertechnology www.vishay.com

PASSIVE COMPONENTS:



One of the World's Largest Manufacturers of Discrete Semiconductors and Passive Components

WORLDWIDE SALES CONTACTS

THE AMERICAS

UNITED STATES

VISHAY AMERICAS ONE GREENWICH PLACE SHELTON, CT 06484 UNITED STATES PH: +1-402-563-6866 FAX: +1-402-563-6296

ASIA

SINGAPORE

VISHAY INTERTECHNOLOGY ASIA PTE LTD. 25 TAMPINES STREET 92 **KEPPEL BUILDING #02-00** SINGAPORE 528877 PH: +65-6788-6668 FAX: +65-6788-0988

P.R. CHINA

VISHAY TRADING (SHANGHAI) CO., LTD. 15D, SUN TONG INFOPORT PLAZA 55 HUAI HAI WEST ROAD SHANGHAI 200030 P.R. CHINA

PH: +86-21-5258 5000 FAX: +86-21-5258 7979

JAPAN

VISHAY JAPAN CO., LTD. MG IKENOHATA BLDG. 4F 1-2-18, IKENOHATA TAITO-KU TOKYO 110-0008 **JAPAN**

PH: +81-3-5832-6210 FAX: +81-3-5832-6260

EUROPE

GERMANY

VISHAY EUROPE SALES GMBH GEHEIMRAT-ROSENTHAL-STR. 100 95100 SELB **GERMANY**

PH: +49-9287-71-0 FAX: +49-9287-70435

FRANCE

VISHAY S.A. 199, BLVD DE LA MADELEINE 06003 NICE, CEDEX 1 **FRANCE** PH: +33-4-9337-2920

FAX: +33-4-9337-2997

UNITED KINGDOM

VISHAY LTD. PALLION INDUSTRIAL ESTATE SUNDERLAND SR4 6SU UNITED KINGDOM PH: +44-191-514-4155 FAX: +44-191-567-8262