



TANTALUM CAPACITORS

Solid Electrolyte

Solid Electrolyte Leaded

Gelled Electrolyte Leaded



Solid Electrolyte

Tantalum Chip Capacitors



Type	Capacitance Range (μF)	Voltage Range (V)	Temperature Range	Case Size	Standard or Specification	
MOLDED CHIPS						
TR3	0.47 - 680	4 - 50	-55 °C to +125 °C	A, B, C, D, E	Very Low ESR, 100 % Surged (B, C, D, E)	
298D	1 - 220	4 - 25	-55 °C to +125 °C	M, P	Lead-frameless, 0805, 0603 Face-Down Terminations	
292D	1.0 - 47	3 - 20	-55 °C to +125 °C	P, R	Lead-frameless, 0805 size	
293D	0.1 - 680	4 - 50	-55 °C to +125 °C	A, B, C, D, E	Standard Type 793DX = CECC 30801-005 CTC3 = CECC30801-009 CTC4 = CECC 30801-011 793DE = CECC 3080-801	
593D	0.47 - 680	4 - 50	-55 °C to +125 °C	A, B, C, D, E	Low ESR, 100 % Surged (B, C, D, E)	
TH3	0.33 - 100	10 - 50	-55 °C to +125 °C	A, B, C, D, E	Extreme Temperature	
COATED CHIPS						
595D	0.1 - 1500	4 - 50	-55 °C to +125 °C	A, B, C, D, G, H, M, R, S, T	Similar to EIA; Maximum CV; T case, 0805	
594D	1.0 - 1500	4 - 50	-55 °C to +125 °C	B, C, D, R	Low ESR	
592D	1.0 - 3300	4 - 35	-55 °C to +125 °C	A, B, C, D, R, S, X	Low profile; Maximum CV	
591D	1.0 - 1000	4 - 35	-55 °C to +125 °C	A, B, C, D, R	Low profile; Low ESR	
572D	4.7 - 220	4 - 35	-55 °C to +125 °C	A, B, P, Q, S, T	Low profile; Maximum CV; Single-sided anode	
597D	22 - 1500	4 - 50	-55 °C to +125 °C	E, F, R, V	Multi-anode; Ultra low ESR	
695D	0.1 - 270	4 - 50	-55 °C to +125 °C	A, B, D, E, F, G, H	MIL-C-556365/4	
CWR06	0.1 - 100	4 - 50	-55 °C to +125 °C	A, B, C, D, E, F, G, H	MIL-C-556365/4	
195D	0.1 - 330	2 - 50	-55 °C to +125 °C	A, B, C, D, E, F, G, H, R, S, V, X, Y, Z	CCEC, 3801/006/008-CTC2	
194D	0.1 - 150	4 - 50	-55 °C to +125 °C	A, B, C, D, E, F, G, H	Midget conformal	
CC/EC	0.1 - 220	4 - 35	-55 °C to +125 °C	A, B, C, D, E, F, G, H	CCEC, 3801/006/008-CTC2	
FUSED CHIPS						
893D	1.0 - 220	6.3 - 50	-55 °C to +125 °C	C, D, E	100 ms @ 5 Amps	
MAIN FEATURES						
MOLDED CHIPS		Standard, large volume, low cost applications. For switch mode power supplies and dc-to-dc converters.				
COATED CHIPS		Height and space constraints, higher capacitance, low ESR technology.				
FUSED CHIPS		Increased reliability, safety requirements.				



Solid Electrolyte

Leaded Tantalum Capacitors



Type	Capacitance Range (μF)	Voltage Range (V)	Temperature Range	Case Size	Standard or Specification		
RADIAL LEADS - RESIN COATED							
489D	0.1 - 680	3 - 50	-55 °C to +85 °C	A, B, C, D, E, F, H, M, N, R	General purpose		
499D	0.1 - 680	3 - 50	-55 °C to +125 °C	A, B, C, D, E, F, H, M, N, R	Low leakage current		
199D	0.1 - 680	3 - 50	-55 °C to +125 °C	A, B, C, D, E, F	Low leakage current		
299D	0.1 - 680	3 - 50	-55 °C to +125 °C	A, B, C, D, E, F	Triple lead		
ETPW	0.1 - 330	3 - 50	-55 °C to +125 °C	1A, 1B, 2C, 2D, 2E, 3F, 3G, 4H, 5J, 5K, 5L, 6M, 6N, 6P, 6R	Low leakage current		
ETQW	0.1 - 330	3 - 50	-55 °C to +125 °C	1A, 1B, 2C, 2D, 2E, 3F, 3G, 4H, 5J, 5K, 5L, 6M, 6N, 6P, 6R	Low leakage current Pre-aged		
RADIAL AND AXIAL LEADS - MOLDED CASE							
790D	0.1 - 330	6.3 - 50	-55 °C to +125 °C	A, B, C, D	Radial leads; DIN 44350; DIN 44352		
173D	0.1 - 330	2 - 50	-55 °C to +125 °C	U, V, W, X, Y	Axial leads, molded		
HA	0.001 - 68	2 - 50	-55 °C to +125 °C	C0, C1, C2, C3, C4, C5, C6, C7, N1, N2, N3, N4, N5	Cylindrical, polar Cylindrical, non-polar; subminiature		
SHA	0.22 - 68	2 - 35	-55 °C to +125 °C	C0, C1, C2, C3, C4, C5, C6, C7, N1, N2, N3, N4, N5	Cylindrical, polar Cylindrical, non-Polar		
TC	0.1 - 470	2 - 50	-55 °C to +125 °C	C0, C1, C2, C3, C4, C5, C6, N1, N2, N3, N4	Cylindrical, polar Cylindrical, non-polar; subminiature		
STC	0.1 - 470	2 - 35	-55 °C to +125 °C	C0, C1, C2, C3, C4, C5, C6, C7, N1, N2, N3, N4, N5	Cylindrical, polar Cylindrical, non-polar		
AXIAL LEADS - HERMETICALLY SEALED							
150D	0.0027 - 330	6 - 125	-55 °C to +125 °C	A, B, R, S	Standard range		
152D	1.2 - 1000	6 - 50	-55 °C to +125 °C	A, B, R, S	Extended range		
CSR13	0.0056 - 330	6 - 125	-55 °C to +125 °C	A, B, C, D	MIL-C-39003/01		
CSR21	5.6 - 330	6.3 - 50	-55 °C to +125 °C	C, D	MIL-C-39003/09		
CSR23	1.2 - 1000	6 - 50	-55 °C to +125 °C	A, B, C, D	MIL-C-39003/03		
CSR33	1.2 - 1000	6 - 50	-55 °C to +125 °C	A, B, C, D	MIL-C-39003/06		
CTS13	0.1 - 330	6.3 - 63	-55 °C to +85 °C	A, B, C, D	CECC 30201-005		
CTS1	0.1 - 330	6.3 - 125	-55 °C to +125 °C	A, B, C, D	CECC 30201-002 IECQ 300201-FR 001		
749DX	0.068 - 1000	6.3 - 63	-55 °C to +125 °C	A, B, C, D	CECC 30201-001 CECC 30201-011 CECC 30201-012 CECC 30201-029 BS 9073 N001		
CTS32	1 - 330	6.3 - 63	-55 °C to +85 °C	A, B, C, D	CECC 30201-019		
550D	5.6 - 330	6 - 50	-55 °C to +125 °C	R, S	High current capability		
MAIN FEATURES							
RADIAL LEADS (Resin Coated)		Low cost, general purpose for manual or automatic insertions. Various lead style configurations.					
RADIAL LEADS (Molded Case)		Specially designed for high density printed circuit boards.					
AXIAL LEADS (Hermetically Sealed)		Recommended for hostile environments.					



Gelled Electrolyte

Leaded Tantalum Capacitors



Type	Capacitance Range (μF)	Voltage Range (V)	Temperature Range	Case Size	Standard or Specification		
ELASTOMER SEALED							
109D	1.7 - 2200	6 - 150	-55 °C to +125 °C	T1, T2, T3, T4	Standard range		
CT4	3.3 - 1000	10 - 150	-55 °C to +125 °C	A, B, C, D	CECC 30202-003		
SUPERTAN							
ST	10 - 1800	25 - 125	-55 °C to +125 °C	T1, T2, T3, T4, L2	Very high capacitance		
STE	750 - 10,000	10 - 75	-55 °C to +85 °C	T1, T2, T3, T4	Very high capacitance-extended ratings		
EPOXY END-FILL							
769D	3.6 - 2200	6 - 125	-55 °C to +125 °C	A, B, C, D	CECC 30202-013 BS 9073 F008 BS 9073 F0032		
GLASS TO TANTALUM HERMETIC SEAL							
138D	1.7 - 2200	6 - 125	-55 °C to +125 °C	T1, T2, T3, T4	Standard range		
738D	3.3 - 1200	6.3 - 125	-55 °C to +175 °C	A, B, C, D	BS 9073 F018		
CT9	3.9 - 2200	6.3 - 125	-55 °C to +175 °C	A, B, C, D	CECC 30202-004		
CLR65	1.7 - 1200	6 - 125	-55 °C to +125 °C	T1, T2, T3, T4	MIL-C-39006/09		
TANTALUM CASE, GLASS TO TANTALUM HERMETIC SEAL							
134D	10 - 680	50 - 125	-55 °C to +200 °C	T1, T2, T3, T4	High Capacitance		
135D	1.7 - 2200	6 - 125	-55 °C to +200 °C	T1, T2, T3, T4	Standard range		
735D	2.7 - 2200	6 - 125	-55 °C to +200 °C	A, B, C, D	CECC 30202-001		
735DE	2.7 - 2200	6 - 125	-55 °C to +200 °C	A, B, C, D	CECC 30202-801		
CT79	3.9 - 2200	6 - 125	-55 °C to +200 °C	A, B, C, D	CECC 30202-005		
CLR79	1.7 - 1200	6 - 125	-55 °C to +125 °C	T1, T2, T3, T4	MIL-C-39006/22		
CLR81	6.8 - 2200	6 - 125	-55 °C to +125 °C	T1, T2, T3, T4	MIL-C-39006/25		
MAIN FEATURES							
ELASTOMER SEALED		Silver case, low leakage current, long shelf life.					
EPOXY END-FILL		Silver case, low leakage current, higher CV per unit volume than any other part.					
GLASS TO TANTALUM HERMETIC SEAL		Low pressure applications, self healing capability.					
TANTALUM CASE, GLASS TO TANTALUM HERMETIC SEAL		Space and aeronautical applications, very high reliability. High temperature and vibration capabilities.					



Ordering Information Example

572D	336	X0	6R3	S	2	T
------	-----	----	-----	---	---	---

REEL SIZE AND PACKAGE ORIENTATION
T = 7", 180 mm reel, cathode nearest sprocket hole (standard)
W = 13", 330 mm reel, cathode nearest sprocket hole (standard)

TERMINATION
2 = 100 % Tin
4 = Gold plated

CASE CODE
See ratings and case codes table

DC VOLTAGE RATING
At +85 °C, in Volts.
Preceded by zeros if needed to complete the 3-digit block.
A decimal point is indicated by an "R" (6R3 = 6.3 Volts).

CAPACITANCE TOLERANCE CODE
X0 = ±20 %
X9 = ±10 %

CAPACITANCE CODE
In picofarads.
The first two digits are significant.
The third is the number of zeros following.

SPRAGUE TYPE NUMBER
Identifies the basic capacitor design

**SEMICONDUCTORS:**

Rectifiers • High-Power Diodes and Thyristors • Small-Signal Diodes • Zener and Suppressor Diodes
• FETs • RF Transistors • Optoelectronics • ICs • Modules and Assemblies

PASSIVE COMPONENTS:

Resistive Products • Magnetics • Capacitors • Strain Gage Transducers and Stress Analysis Systems

One of the World's Largest **Manufacturers**

of Discrete Semiconductors and Passive Components

WORLDWIDE SALES CONTACTS**THE AMERICAS****UNITED STATES**

VISHAY AMERICAS
ONE GREENWICH PLACE
SHELTON, CT 06484
UNITED STATES
PH: +1-402-563-6866
FAX: +1-402-563-6296

ASIA**SINGAPORE**

VISHAY INTERTECHNOLOGY
ASIA PTE LTD.
25 TAMPINES STREET 92
KEPPEL BUILDING #02-00
SINGAPORE 528877
PH: +65-6788-6668
FAX: +65-6788-0988

P.R. CHINA

VISHAY TRADING (SHANGHAI) CO., LTD.
15D, SUN TONG INFOPORT PLAZA
55 HUAI HAI WEST ROAD
SHANGHAI 200030
P.R. CHINA
PH: +86-21-5258 5000
FAX: +86-21-5258 7979

JAPAN

VISHAY JAPAN CO., LTD.
MG IKENOHATA BLDG. 4F
1-2-18, IKENOHATA
TAITO-KU
TOKYO 110-0008
JAPAN
PH: +81-3-5832-6210
FAX: +81-3-5832-6260

EUROPE**GERMANY**

VISHAY EUROPE SALES GMBH
GEHEIMRAT-ROSENTHAL-STR. 100
95100 SELB
GERMANY
PH: +49-9287-71-0
FAX: +49-9287-70435

FRANCE

VISHAY S.A.
199, BLVD DE LA MADELEINE
06003 NICE, CEDEX 1
FRANCE
PH: +33-4-9337-2920
FAX: +33-4-9337-2997

UNITED KINGDOM

VISHAY LTD.
PALLION INDUSTRIAL ESTATE
SUNDERLAND SR4 6SU
UNITED KINGDOM
PH: +44-191-514-4155
FAX: +44-191-567-8262