


R-C Thermal Model Parameters

DESCRIPTION

The parametric values in the R-C thermal model have been derived using curve-fitting techniques. R-C values for the electrical circuit in the Foster/tank and Cauer/filter configurations are included. When implemented in P-SPICE, these values have matching characteristic curves to the single-pulse transient thermal impedance curves for the MOSFET.

These RC values can be used in the P-SPICE simulation to evaluate the thermal behavior of the MOSFET junction temperature under a defined power profile. These techniques are described in application note AN609, "Thermal Simulation of Power MOSFETs on the P-SPICE Platform".

R-C THERMAL MODEL FOR TANK CONFIGURATION



R-C VALUES FOR TANK CONFIGURATION			
THERMAL RESISTANCE (°C/W)			
Junction to	Ambient	Case	Foot
RT1	N/A	438.2323 m	N/A
RT2	N/A	575.3563 m	N/A
RT3	N/A	370.0901 m	N/A
RT4	N/A	716.3213 m	N/A
THERMAL CAPACITANCE (Joules/°C)			
Junction to	Ambient	Case	Foot
CT1	N/A	136.0451 m	N/A
CT2	N/A	545.3257 u	N/A
CT3	N/A	646.2782 m	N/A
CT4	N/A	9.8339 m	N/A


Note

N/A indicates not applicable

This document is intended as a SPICE modeling guideline and does not constitute a commercial product datasheet. Designers should refer to the appropriate datasheet of the same number for guaranteed specification limits.



R-C THERMAL MODEL FOR FILTER CONFIGURATION



R-C VALUES FOR FILTER CONFIGURATION			
THERMAL RESISTANCE (°C/W)			
Junction to	Ambient	Case	Foot
RF1	N/A	639.2091 m	N/A
RF2	N/A	557.5385 m	N/A
RF3	N/A	464.7311 m	N/A
RF4	N/A	438.5213 m	N/A
THERMAL CAPACITANCE (Joules/°C)			
Junction to	Ambient	Case	Foot
CF1	N/A	523.9553 u	N/A
CF2	N/A	7.3424 m	N/A
CF3	N/A	36.5263 m	N/A
CF4	N/A	315.3734 m	N/A

Note

N/A indicates not applicable

