


Low Capacitance, Single-Line ESD-Protection Diode

Features


- Ultra compact LLP1006-2L package
- Low package height < 0.4 mm
- 1-line ESD-protection
- Low leakage current < 0.1 μ A
- Low load capacitance $C_D = 0.6$ pF
- ESD-protection to IEC 61000-4-2
 ± 9 kV contact discharge
 ± 9 kV air discharge
- High surge current acc. IEC61000-4-5 $I_{PP} > 2$ A
- Soldering can be checked by standard vision inspection. No X-ray necessary
- Pin plating NiPdAu (e4) no whisker growth
- Compliant to RoHS directive 2002/95/EC and in accordance to WEEE 2002/96/EC



RoHS
COMPLIANT
GREEN
(5-2009)**



20855



20856

Marking (example only)



Bar = cathode marking
 X = date code
 Y = type code (see table below)

Ordering Information

Device name	Ordering code	Taped units per reel (8 mm tape on 7" reel)	Minimum order quantity
VBUS051CD-HD1	VBUS051CD-HD1-G-08	8000	8000

Package Data

Device name	Package name	Type code	Weight	Molding compound flammability rating	Moisture sensitivity level	Soldering conditions
VBUS051CD-HD1	LLP1006-2L	T	0.72 mg	UL 94 V-0	MSL level 1 (according J-STD-020)	260 °C/10 s at terminals

Absolute Maximum Ratings

Parameter	Test conditions	Symbol	Value	Unit
Peak pulse current	Acc. IEC 61000-4-5; $t_p = 8/20$ μ s; single shot	I_{PPM}	2	A
Peak pulse power	Acc. IEC 61000-4-5; $t_p = 8/20$ μ s; single shot	P_{PP}	28	W
ESD immunity	Contact discharge acc. IEC 61000-4-2; 10 pulses	V_{ESD}	± 9	kV
	Air discharge acc. IEC 61000-4-2; 10 pulses	V_{ESD}	± 9	kV
Operating temperature	Junction temperature	T_J	- 40 to + 125	°C
Storage temperature		T_{STG}	- 40 to + 150	°C

** Please see document "Vishay Material Category Policy" www.vishay.com/doc?99902

Electrical Characteristics

Ratings at 25 °C, ambient temperature unless otherwise specified

VBUS051CD-HD1

Parameter	Test conditions/remarks	Symbol	Min.	Typ.	Max.	Unit
Protection paths	Number of line which can be protected	N_{lines}			1	lines
Reverse stand-off voltage	at $I_R = 0.1 \mu A$; pin 2 to pin 1	V_{RWM}	5.5			V
Reverse current	at $V_R = V_{RWM} = 5.5 V$; pin 2 to pin 1	I_R		< 0.01	0.1	μA
Reverse breakdown voltage	at $I_R = 1 mA$ pin 2 to pin 1	V_{BR}	6.5	7.6	8.5	V
Reverse clamping voltage	at $I_{PP} = 2 A$; acc. IEC 61000-4-5; pin 2 to pin 1	V_C			14	V
Forward clamping voltage	at $I_F = 2 A$; acc. IEC 61000-4-5; pin 1 to pin 2	V_F		2.6	3.5	V
Capacitance	at $V_R = 0 V$; $f = 1 MHz$; pin 2 to pin 1	C_D		0.6	0.8	pF

Application Note

The **VBUS051CD-HD1** is an ESD-protection device with the characteristic of a Z-diode with a high ESD-immunity and a very low capacitance which makes it usable for high frequency applications like USB2.0 or HDMI

With the **VBUS051CD-HD1** one high speed data line can be protected against transient voltage signals like ESD (Electro Static Discharge). Connected to the data line (pin 2) and to ground (pin 1) negative transients will be clamped close below the ground level while positive transients will be clamped close above the 5.5 V working range. The clamping behaviour of the **VBUS051CD-HD1** is bidirectional but asymmetrical (**BiAs**) and so it offers the best protection for applications running up to 5 V.

Typical Characteristics

$T_{amb} = 25 \text{ }^\circ\text{C}$, unless otherwise specified




Figure 1. ESD Discharge Current Wave Form
acc. IEC 61000-4-2 (330 Ω /150 pF)




Figure 2. 8/20 μs Peak Pulse Current Wave Form
acc. IEC 61000-4-5




Figure 3. Typical Capacitance C_D vs. Reverse Voltage V_R




Figure 6. Typical Peak Clamping Voltage V_C vs. Peak Pulse Current I_{PP}




Figure 4. Typical Forward Current I_F vs. Forward Voltage V_F




Figure 7. Typical Clamping Performance at +8 kV Contact Discharge (acc. IEC 61000-4-2)




Figure 5. Typical Reverse Voltage V_R vs. Reverse Current I_R




Figure 8. Typical Clamping Performance at -8 kV Contact Discharge (acc. IEC 61000-4-2)







Figure 9. Typical Peak Clamping Voltage at ESD Contact Discharge (acc. IEC 61000-4-2)

Package Dimensions in millimeters (inches): LLP1006-2L



Foot print recommendation:



Created - Date: 13. July. 2007
 Rev. 4 - Date: 12. Sept. 2008
 Document no.: S8-V-3906.04-005 (4)
 20812



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.