


## 25 or 50 Mil Pitch, T-Filter Resistor/Capacitor Networks




Small Outline, Surface Mount, EMI/RFI Reduction, T-Filter Networks

Vishay Thin Film's schematic AD is designed as an 8 channel filter for use with personal computer and peripheral 110 ports such as SCSI ports. The use of single die technology for filtering minimizes space and allows for more freedom in routing. With a rugged molded case to protect the circuit from the environment and an integrated thin film network this product is your choice when reduced size, improved accuracy and surface mount capability are your goals.

Available packages SOIC, SSOP and TSSOP.

### SCHEMATIC AD



### FEATURES

- Lead (Pb)-free standard
- Resistors and capacitors on a single chip
- Saves board space
- Reduces total assembly costs
- Uniform performance characteristics
- Compatible with automatic surface mounting equipment
- UL 94V-0 flame resistant
- Rugged, molded case construction



**RoHS**  
COMPLIANT

### TYPICAL PERFORMANCE

	TCR	TOLERANCE
RESISTOR	200	10 %
	TCC	TOLERANCE
CAPACITOR	200	20 %

VSORC	MODELS			STANDARD VALUES	
	VSSRC	VTSRC	R ( $\Omega$ )	C (pF)	
	X		33	47	

### STANDARD ELECTRICAL SPECIFICATIONS


TEST	SPECIFICATIONS	CONDITIONS
Material	Tantalum Nitride on Silicon	
Resistance Range	10 $\Omega$ to 750 $\Omega$	
TCR:	Tracking	$\pm 10$ ppm/ $^{\circ}$ C
	Absolute	$\pm 200$ ppm/ $^{\circ}$ C
Tolerance:	Absolute	$\pm 10$ % Standard (R)
	Absolute	$\pm 20$ % Standard (C)
Power Rating:	Package	1 W - (T)SSOP. 1.2 W - SOIC
Capacitance Range	10 pF to 150 pF - TSSOP/10 pF to 250 pF - SOIC and SSOP	
Stability:	$\Delta R$ Ratio	$\pm 2$ %
ESD Protection	> 2 kV	MIL-STD-883, Method 3015
Breakdown Voltage	35 - 50 V	
Operating Temperature Range	0 $^{\circ}$ C to + 70 $^{\circ}$ C	
Storage Temperature Range	- 55 $^{\circ}$ C to + 125 $^{\circ}$ C	
Power Rating/Resistor	100 mW	

# VTSRC, VSSRC, VSORC-AD

Vishay Thin Film 25 or 50 Mil Pitch, T-Filter Resistor/Capacitor Networks



## DIMENSIONS AND IMPRINTING in inches and millimeters




MODEL	VTSRC20-AD		VSSRC20-AD		VSORC20-AD	
	INCHES	MILLIMETERS	INCHES	MILLIMETERS	INCHES	MILLIMETERS
A	0.256 ± 0.003	6.5 ± 0.08	0.344 max.	8.74 max.	0.500 ± 0.010	12.7 ± 0.25
B (Ref.)	0.025	0.65	0.025	0.64	0.050	1.27
C (Ref.)	0.0087	0.22	0.010	0.25	0.016	0.41
D	0.004	0.10	0.006	0.15	0.008	0.20
E (Typ.)	0.024	0.61	0.025	0.64	0.030	0.76
F	0.173 ± 0.003	4.39 ± 0.08	0.154 ± 0.003	3.9	0.293 ± 0.003	7.44
G	0.015 × 45°	0.38	0.015 × 45°	0.38	0.025 × 45°	0.64
H	0.252 ± 0.005	6.4 ± 0.13	0.236 ± 0.008	6.0 ± 0.20	0.406 ± 0.005	10.31
J (Ref.)	0.005	0.13	0.010	0.25	0.010	0.25
W	0.043 ± 0.005	1.09 ± 0.13	0.064 ± 0.005	1.6	0.100 ± 0.005	2.59

IMPRINTING						
VSORC, VSSRC, VTSRC	20	AD	XXX / XXX			
MODEL	PIN COUNT	SCHEMATIC	RESISTANCE Code: e.g. 100 = 10 Ω	/	CAPACITANCE Code: e.g. 101 = 100 pF	
		XXXX Date Code	* Optional marking			

MECHANICAL SPECIFICATIONS	
Resistive Element	Tantalum Nitride
Substrate Material	Silicon
Body	Molded Epoxy
Terminals	Copper Alloy
Plating	100 % Sn Matte
Lead Coplanarity	0.0005 Inches
Marking Resistance to Solvents	Permanency testing per MIL-STD-202, Method 215

### DERATING CURVE



PACKING INFORMATION			
MODEL	LEADS	TAPE AND REEL	TUBES
VTSRC (TSSOP)	20	2500	74
VSSRC (SSOP)	20	2500	55
VSORC (SOIC)	20	1000	38



<b>GLOBAL PART NUMBER INFORMATION</b>																
<b>New Global Part Numbering: VTSRC20AD330470TF (preferred part number format)</b>																
V	T	S	R	C	2	0	A	D	3	3	0	4	7	0	T	F
GLOBAL MODEL			NUMBER OF LEADS/ SCHEMATICS			RESISTANCE AND TOLERANCE/ CAPACITANCE AND TOLERANCE			PACKAGING							
<b>VTSRC</b> <b>VSSRC</b> <b>VSORC</b> (Lead (Pb)-free) (e1)			<b>20AD</b>			<b>xxxyyy</b>  First 2 digits are significant figures. Last digit specifies number of zeroes to follow.  K = 10 % Capacitor Tol. fixed M = 20 % Resistance Tol. fixed			<b>UF = TUBED</b>  <b>TAPE AND REEL</b> <b>TF = Full Reels</b>							
<b>Historical Part Number example: VTSRC20AD330K470MT/R (will continue to be accepted)</b>																
<b>VTSRC</b>	<b>20</b>	<b>AD</b>	<b>330K</b>	<b>470M</b>	<b>T/R</b>											
MODEL	NUMBER OF LEADS	SCHEMATIC	RESISTANCE	TOLERANCE	PACKAGING											



## Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.