




## Fast Acting, Molded Styles, Custom Designed For Your Application



### FEATURES

- Low temperature coefficient (down to 30 ppm/°C)
- High temperature silicone molded package (derated to 200 °C)
- Performs function of resistor and series fuse and provides predictable fusing times
- Complete welded construction
- No flaming or distortion of unit under fusing conditions
- Ideal for Squib circuit applications and protection of semi-conductor devices
- Negligible noise and voltage coefficient



### TYPICAL ELECTRICAL SPECIFICATIONS

The following are offered as examples of reliable designs. Hundreds of possible combinations are available for meeting your requirements. Contact factory by using email address in the footer of this page, for assistance. Higher wattages available.

| GLOBAL MODEL | HISTORICAL MODEL | FUSING PARAMETERS |                        | RESISTANCE RANGE $\Omega$<br>$\pm 5\%$ , $\pm 10\%$ AVAILABLE | 1.0 W CONTINUOUS POWER <sup>(1)</sup> |                          |
|--------------|------------------|-------------------|------------------------|---|---------------------------------------|--------------------------|
|              |                  | FUSING CURRENT A  | TYPICAL FUSING TIME ms |   | CONTINUOUS CURRENT A                  | CROSSOVER VALUE $\Omega$ |
| RS01A...209  | RS-1A-209        | 0.5               | 4                      | 49 - 500  | 0.10                                  | 100.0                    |
| RS01A...118  | RS-1A-118        | 1.0               | 9                      | 6.8 - 185   | 0.25                                  | 16.0                     |
| RS01A...212  | RS-1A-212        | 1.25              | 8                      | 4.7 - 107   | 0.30                                  | 11.11                    |
| RS01A...213  | RS-1A-213        | 1.5               | 15                     | 3.5 - 68  | 0.35                                  | 8.16                     |
| RS01A...143  | RS-1A-143        | 2.0               | 15                     | 2.2 - 35  | 0.40                                  | 6.25                     |
| RS01A...214  | RS-1A-214        | 2.5               | 23                     | 1.7 - 23  | 0.45                                  | 4.94                     |
| RS01A...162  | RS-1A-162        | 3.0               | 48                     | 1.1 - 12  | 0.55                                  | 3.31                     |
| RS01A...208  | RS-1A-208        | 4.0               | 47                     | 0.72 - 6.44   | 0.75                                  | 1.78                     |
| RS01A...207  | RS-1A-207        | 6.0               | 70                     | 0.35 - 2.17   | 1.0                                   | 1.0                      |
| RS01A...215  | RS-1A-215        | 8.0               | 48                     | 0.29 - 1.61   | 1.25                                  | 0.64                     |
| RS01A...173  | RS-1A-173        | 10.0              | 50                     | 0.23 - 1.16   | 1.50                                  | 0.44                     |
| RS01A...216  | RS-1A-216        | 15.0              | 35                     | 0.19 - 0.82   | 1.75                                  | 0.33                     |
| RS01A...217  | RS-1A-217        | 20.0              | 46                     | 0.12 - 0.42   | 2.0                                   | 0.25                     |

#### Note

- <sup>(1)</sup> The Continuous Current Rating applies only to values equal to or less than the Crossover Value. The Continuous Power Rating applies only to values equal to or higher than the Crossover Value.
- Be aware that the inherent compromise involved between resistive and fusing functions sometimes makes certain exact combinations unattainable. However, in nearly all cases, this does not prevent the production of a functional, reliable fuse resistor thoroughly capable of meeting application requirements.

### GLOBAL PART NUMBER INFORMATION

New Global Part Numbering: RS01A402R0JS70209 (preferred part number format)

R S 0 1 A 4 0 2 R 0 J S 7 0 2 0 9

| GLOBAL MODEL  | VALUE   | TOLERANCE                           | PACKAGING  | SPECIAL  |
|---|---|-------------------------------------|--|--|
| (See Typical Electrical Specifications Global Model column for options) | R = Decimal<br>K = Thousand<br>15R00 = 15 $\Omega$<br>10K00 = 10 k $\Omega$ | J = $\pm 5.0\%$<br>K = $\pm 10.0\%$ | E70 = Lead (Pb)-free, tape/reel<br>E12 = Lead (Pb)-free, bulk<br><br>S70 = Tin/lead, tape/reel<br>B12 = Tin/lead, bulk | (Dash Number)<br>(up to 3 digits)<br>From 1 - 999<br>as applicable |

Historical Part Number Example: RS-1A-209 402  $\Omega$  5% S70 (will continue to be accepted)

|                  |                  |                |           |
|------------------|------------------|----------------|-----------|
| RS-1A-209        | 402 $\Omega$     | 5%             | S70       |
| HISTORICAL MODEL | RESISTANCE VALUE | TOLERANCE CODE | PACKAGING |

If a MODEL listed in TYPICAL ELECTRICAL SPECIFICATIONS table does not meet your requirements, then please include the following information. It will enable us to choose the best design for your application.

1. Operating wattage or current, ambient temperature and required resistance stability. (%  $\Delta R/1000$  h)
2. Fusing wattage or current and maximum "blow" time. Also, minimum "blow" time, if applicable.
3. Nominal resistance and maximum allowable resistance tolerance, (5% to 10% preferred).
4. Maximum allowable physical size.
5. Voltage to be interrupted.
6. Frequency of power source, wave form and a brief description of your application.


# RS Style Wirewound Fuse Resistor



Vishay Dale

Fast Acting, Molded Styles, Custom  
Designed For Your Application

## DIMENSIONS in inches [millimeters]



| MODEL | A                             | B                            |
|-------|-------------------------------|------------------------------|
| 1.0 W | 0.422 ± 0.015 [10.72 ± 0.381] | 0.110 ± 0.015 [2.79 ± 0.381] |

| TECHNICAL SPECIFICATIONS |                 |  |
|--------------------------|-----------------|--|
| PARAMETER                | UNIT            | TYPICAL WIREWOUND FUSE RESISTOR CHARACTERISTICS  |
| Resistance Tolerance     | ± %             | 3, 5, 10   |
| Temperature Coefficient  | ppm/°C          | 90 for 0.1 Ω thru 0.99 Ω; 50 for 1.0 Ω thru 9.9 Ω; 30 for 10 Ω and above   |
| Power Rating             | W               | 1.0 standard, higher power ratings available   |
| Dielectric Strength      | V <sub>AC</sub> | 500  |
| Insulation Resistance    | MΩ              | 1000 minimum dry   |
| Fusing Times             | s               | 0.001 to 1.0   |
| Minimum Fusing Current   | A               | Approximately 4 times the continuous operating current obtainable on some designs. Larger ratios produce better designs. |
| Terminal Strength        | lb              | 5 minimum  |
| Solderability            | -               | Terminals are 60/40 electro tin plated to facilitate soldering   |

## MATERIAL SPECIFICATIONS

**Element:** Copper-nickel alloy or nickel-chrome alloy, depending on resistance value


**Core:** Alumina ceramic

**Encapsulant:** Thermoset silicone mold compound

**End Caps:** Stainless steel

**Terminals:** Tinned copperweld

**Part Marking:** DALE, model, value, tolerance, date code



**Derating**



## Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.