

Voltage-Regulator

GLOW-DISCHARGE TYPE


150 VOLTS

For Applications Requiring a Relatively
Constant DC Output Voltage, Independent
of Load and Supply-Voltage Variations

Mechanical:

Operating Position	Any
Type of Cathode	Cold
Maximum Overall Length	3-1/16"
Maximum Seated Length	2-1/2"
Maximum Diameter	1-9/32"
Dimensional Outline	See General Section
Bulb	T9
Base	Intermediate-Shell Octal 6-Pin, Arrangement 1 (JEDEC Group 1, No.86-8)
Basing Designation for BOTTOM VIEW	4AJ

- Pin 1 -No Internal Connection
- Pin 2 -Cathode
- Pin 3 -Jumper^a
- Pin 5 -Anode
- Pin 7 -Jumper^a
- Pin 8 -No Internal Connection



VOLTAGE REGULATOR

Maximum and Minimum Ratings, Absolute-Maximum Values:

Average Cathode			
Starting Current ^b	100 max.	ma	
DC Cathode Current	{ 40 max. 5 min.	ma	
DC or AC Jumper Current	2 max.	amp	
Ambient-Temperature Range	-55 to +90	°C	

Circuit Values:

Shunt Capacitor	0.1 max.	μf
Series Resistor	See Operating Considerations	

^a With suitable socket connections, the jumper within the tube base (between pins 3 and 7) provides for opening the power-supply circuit to protect circuit components when the voltage-regulator tube is removed from its socket.

^b Averaged over starting period not exceeding 10 seconds. When starting currents greatly in excess of the maximum dc-cathode-current rating of 40 milliamperes are encountered, it may be necessary to operate these tubes as much as 20 minutes under steady-state conditions to assure stable operation.



OD3A

CHARACTERISTICS RANGE VALUES

Values are initial unless otherwise specified

Note Min. Av. Max.

DC Anode Supply Voltage See Note 1

DC Anode Starting Voltage in:

Total darkness - - - 225 volts

Normal ambient light

(5 to 50 footcandles) - - 160 180 volts

Anode Voltage Drop

for dc cathode current of:

5 ma. - 145 - - volts

30 ma. - 145 149 160 volts

40 ma. - 145 150 162 volts

Regulation for dc-cathode-current range of:

5 to 30 ma. 2 - 2 4 volts

5 to 40 ma. 2 - 4 5.5 volts

Tube Noise for dc cathode current of

40 ma. - - - 15 rms mv

DC Leakage Current

for dc anode supply voltage

of 50 volts and anode resistor

of 3000 ohms - - - 10 μ a

Note 1: The minimum value to insure starting throughout useful tube life must be equal to the dc anode starting voltage plus the voltage drop across the series resistor at the maximum value of the load current.

Note 2: The maximum values for the specified regulation range apply throughout useful tube life.

OPERATING CONSIDERATIONS

shown under Type OA3A also apply to the OD3A

