


TUNG-SOL

PENTODE
MINIATURE TYPE

GLASS BULB
MINIATURE BUTTON
7 PIN BASE E7-1
OUTLINE DRAWING
JEDEC 5-2


COATED UNIPOTENTIAL CATHODE

HEATER

6.3±0.6 VOLTS 400 MA. ←

AC OR DC

ANY MOUNTING POSITION



BOTTOM VIEW

BASING DIAGRAM
JEDEC 7CM

THE 6EW6 IS A SHARP CUTOFF PENTODE IN THE 7-PIN MINIATURE CONSTRUCTION AND HAS BEEN DESIGNED FOR INTERMEDIATE AMPLIFIER SERVICE IN TELEVISION RECEIVERS.

DIRECT INTERELECTRODE CAPACITANCES

	WITH SHIELD ^A	WITHOUT SHIELD	
GRID #1 TO PLATE (MAX.)	0.03	0.04	pt
INPUT	10.0	10.0	pf
OUTPUT	3.4	2.4	pf

RATINGS

INTERPRETED ACCORDING TO DESIGN-MAXIMUM VALUES

MAXIMUM PLATE VOLTAGE	330	VOLTS
MAXIMUM SCREEN-SUPPLY VOLTAGE	330	VOLTS
MAXIMUM SCREEN VOLTAGE	SEE SCREEN RATING CHART	
MAXIMUM POSITIVE DC GRID #1 VOLTAGE	0	VOLTS
MAXIMUM PLATE DISSIPATION	3.1	WATTS
MAXIMUM SCREEN DISSIPATION	0.65	WATTS
MAXIMUM HEATER CATHODE VOLTAGE:		
HEATER POSITIVE WITH RESPECT TO CATHODE		
DC COMPONENT	100	VOLTS
TOTAL DC AND PEAK	200	VOLTS
HEATER NEGATIVE WITH RESPECT TO CATHODE		
TOTAL DC AND PEAK	200	VOLTS

DESIGN-MAXIMUM RATINGS ARE LIMITING VALUES OF OPERATING AND ENVIRONMENTAL CONDITIONS APPLICABLE TO A BOGEY ELECTRON DEVICE OF A SPECIFIED TYPE AS DEFINED BY ITS PUBLISHED DATA, AND SHOULD NOT BE EXCEEDED UNDER THE WORST PROBABLE CONDITIONS. THE DEVICE MANUFACTURER CHOOSES THESE VALUES TO PROVIDE ACCEPTABLE SERVICEABILITY OF THE DEVICE, TAKING RESPONSIBILITY FOR THE EFFECTS OF CHANGES IN OPERATING CONDITIONS DUE TO VARIATIONS IN DEVICE CHARACTERISTICS. THE EQUIPMENT MANUFACTURER SHOULD DESIGN SO THAT INITIALLY AND THROUGHOUT LIFE NO DESIGN-MAXIMUM VALUE FOR THE INTENDED SERVICE IS EXCEEDED WITH A BOGEY DEVICE UNDER THE WORST PROBABLE OPERATING CONDITIONS WITH RESPECT TO SUPPLY-VOLTAGE VARIATION, EQUIPMENT COMPONENT VARIATION, EQUIPMENT CONTROL ADJUSTMENT, LOAD VARIATION, SIGNAL VARIATION, AND ENVIRONMENTAL CONDITIONS.

^A WITH EXTERNAL SHIELD (EIA 316) CONNECTED TO CATHODE.

→ INDICATES A CHANGE.



CONTINUED ON FOLLOWING PAGE

TUNG-SOL



CONTINUED FROM PRECEDING PAGE



TYPICAL OPERATING CONDITIONS AND CHARACTERISTICSCLASS A_1 AMPLIFIER

PLATE VOLTAGE	125	VOLTS
SUPPRESSOR, CONNECTED TO CATHODE AT SOCKET		
SCREEN VOLTAGE	125	VOLTS
CATHODE-BIAS RESISTOR	56	OHMS
PLATE RESISTANCE (APPROX.)	0.2	MEGOHMS
TRANSCONDUCTANCE	14 000	μ MHOS
PLATE CURRENT	11	MA.
SCREEN CURRENT	3.2	MA.
GRID #1 VOLTAGE (APPROX.) $I_b = 20 \mu$ AMPS.	-3.5	VOLTS



PRINTED IN U. S. A.





PRINTED IN U. S. A.