


# Multimeter and Thermometer Accessories


## Test Leads



### TL20 63" Test Lead Set (w/TP20 & AC20)

**Versatile leads; interchangeable tips; work with other probe tips too.**


Suggested for automotive, electrical and HVAC applications. Set consists of silicone-insulated TL22 Flexible Test Leads (one red and one black), stainless-steel TP20 Industrial Test Probes (one red, one black), and AC20 Industrial Alligator Clips (one red, one black). 63" (1.6 m). 1000V (Heavy Industrial Rating), Overvoltage Category III per IEC 1010-1, 10A rating. Shrouded right-angle connectors. UL 1244 Listed. One year warranty



### TL26 60" 5-Way Test Lead Set

**5 ways to connect**

1) U-shaped nose for blade-shaped terminals; 2) Notched jaw for gripping screw heads, bare wire or terminals; 3) Serrated teeth for gripping threaded or wire-wrapped terminals; 4) Cluster of sharp needles for piercing small gauge (#22-#28 AWG) wires; 5) Large piercing needle for penetrating larger gauge wires. 60" (1.5m), silicone-insulated leads, useable from -80°C to +150°C (-112°F to +302°F). Rated for 250V, 10A. One red and one black, 63" (1.6 m). One year warranty



### TL22 63" Right Angle Silicone Test Leads

**Silicone-insulated; won't crack from cold, or melt from an exhaust manifold.**

Silicone rubber insulated leads stay flexible at -112°F (-80°C), won't melt at 302°F (150°C). 385 internal strands for flexibility prevent kinks and bends in test leads; superior strain relief is also provided. Compatible with all meters accepting safety-shrouded, standard-sized banana plugs. One red, one black, 63" (1.6 m).


Best suited for test clips with plunger-style jaws (AC20 Industrial Alligator Clips, AC80 Hook Style Clips, AC83 Pin Grabber Clips, AC89 Insulation Piercing Clip) 1000V (Heavy Industrial Rating), Overvoltage Category III per IEC 1010-1, 10A rating. Shrouded right-angle connectors on both ends. UL 1244 Listed. One year warranty



### TL28 63" Alligator Clip Test Lead Set

**Large jaws, long leads and a piercing probe**


Solid, spring-loaded copper clips with a wide .50" (12.7 mm) jaw opening and serrated teeth. Large piercing needle for penetrating larger gauge wires. 60" (1.5m), silicone-insulated leads, useable from -80°C to +150°C (-112°F to +302°F). Rated for 250V, 10A. One red and one black, 63" (1.6 m). One year warranty



### TL24 63" Right Angle/Straight Silicone Test Leads

**Same as TL22 except that one end has a shrouded, straight connector.**


Best suited for pointed end test probes (TP20 Industrial Test Probes) or standard jaw test clips (AC75 Banana Jack Alligator Clips, AC85A Large Jaw Alligator Clips). One red and one black, 63" (1.6 m). 1000V (Heavy Industrial Rating), Overvoltage Category III per IEC 1010-1, 10A rating. Shrouded right-angle connectors on both ends. UL 1244 Listed. One year warranty



### TL75 48" Hardpoint Test Lead Set

**Low cost, general purpose test leads.**

Super strong tips and integral strain relief provide extended service life. Safety-shrouded, right-angled inputs. Standard on all DMM models (except 88). Included with most Fluke DMMs. Rated for 1500V, 10A. UL 1244 Listed. One red and one black, 48" (1.2m). One year warranty



### Y8140A 48" Slim Flex Test Lead Set

**Flexible leads for hard to reach spaces**

Slim, retractable, insulated needle-point test leads adjust to desired length by extending probe up to 2.5" (63.5mm). Needle points easily pierce varnish and thin insulation. 48" (1.2m) with PVC insulation. Right-angle, shrouded banana plugs. 1000V, 2A rating. One red, one black, 48" (1.2m). One year warranty