

# Active Probe

▶ P7260



## P7260 Single-ended Active Probe

The P7260 is the fastest active probe in the world. It provides high-bandwidth, low circuit loading, low noise and accurate probing solutions for high-speed circuit designers. This probe has a small probe head for accessing connection points in tight physical constraints and with today's fine pitch circuitry.

The P7260 is the world's first probe to be developed with silicon germanium (SiGe). It features a toggle/switch that offers the choice of using the probe at either 1.5 V<sub>p-p</sub> or 6 V<sub>p-p</sub> dynamic range.

TekConnect® interface takes probe intelligence to the next level, providing probe power, automated signaling of scale factor and offset voltage. It also adds automatic bandwidth adjustment and voltage measurement. The TekConnect interface extends useful bandwidth and signal fidelity out to 18 GHz. A full complement of versatile probe tip accessories helps connect to the wide range of devices faced by digital designers.

## ▶ Features & Benefits

6 GHz Bandwidth

Switchable Attenuation  
Provides up to 6 V<sub>p-p</sub>  
Dynamic Range

Low Input Capacitance  
<0.5 pF

Provides 6 GHz System  
Bandwidth at Probe Tip  
with TDS6604 TekConnect®  
Oscilloscope

Connect and Adapt to  
Various Circuit Designs  
with Small Probe Head  
and Numerous Connection  
Accessories

TekConnect Interface

## ▶ Applications

High-speed Digital  
Systems Design

Component Design/  
Characterization

Manufacturing Engineering  
and Test

## ▶ Characteristics

Designed for use with the TDS6604 oscilloscope – the system bandwidth is typically 6 GHz.

Attribute	Specification 5x	Specification 25x
Type	TekConnect® Active, Single-ended	
Bandwidth (probe only, typical)	6 GHz	6 GHz
Rise Time (guaranteed)	<75 ps	<85 ps
Input Capacitance (pF)	<0.5 pF	<0.5 pF
Attenuation	5x	25x
Dynamic Range	±0.75 V (1.5 V <sub>p-p</sub> )	±3.0 V (6.0 V <sub>p-p</sub> )
DC Offset Range	±5 V	±5 V
Input Resistance	20 kΩ at DC	20 kΩ at DC
Maximum Nondestruct Voltage	30 V (DC plus peak AC)	
Compatible Oscilloscopes*1	TDS6604, TDS7404, all TekConnect oscilloscopes	

\*1 Requires firmware version 2.1 or higher for TDS/CSA7000 Series.

COMPUTING

COMMUNICATIONS

VIDEO

## Active Probe

▶ P7260

### ▶ Ordering Information

#### P7260

6.0 GHz Active Probe, TekConnect® interface.

**Includes:** Probe tip accessories (see list), user manual, storage case.

**Warranty:** One year.

#### Service

**Opt. C3** – Calibration Service 3 Years.

**Opt. C5** – Calibration Service 5 Years.

**Opt. D1** – Calibration Data Report.

**Opt. D3** – Calibration Data Report 3 Years (with Option C3).

**Opt. D5** – Calibration Data Report 5 Years (with Option C5).

**Opt. R3** – Repair Service 3 Years.

**Opt. R5** – Repair Service 5 Years.

#### Related Products

**80A03** – TekConnect Probe Interface Module for TDS/CSA8000 series oscilloscopes.

#### Contact Tektronix:

**ASEAN / Australasia / Pakistan** (65) 6356 3900

**Austria** +43 2236 8092 262

**Belgium** +32 (2) 715 89 70

**Brazil & South America** 55 (11) 3741-8360

**Canada** 1 (800) 661-5625

**Central Europe & Greece** +43 2236 8092 301

**Denmark** +45 44 850 700

**Finland** +358 (9) 4783 400

**France & North Africa** +33 (0) 1 69 86 80 34

**Germany** +49 (221) 94 77 400

**Hong Kong** (852) 2585-6688

**India** (91) 80-22275577

**Italy** +39 (02) 25086 1

**Japan** 81 (3) 6714-3010

**Mexico, Central America & Caribbean** 52 (55) 56666-333

**The Netherlands** +31 (0) 23 569 5555

**Norway** +47 22 07 07 00

**People's Republic of China** 86 (10) 6235 1230

**Poland** +48 (0) 22 521 53 40

**Republic of Korea** 82 (2) 528-5299

**Russia, CIS & The Baltics** +358 (9) 4783 400

**South Africa** +27 11 254 8360

**Spain** +34 (91) 372 6055

**Sweden** +46 8 477 6503/4

**Taiwan** 886 (2) 2722-9622

**United Kingdom & Eire** +44 (0) 1344 392400

**USA** 1 (800) 426-2200

**USA** (Export Sales) 1 (503) 627-1916

For other areas contact Tektronix, Inc. at: 1 (503) 627-7111

Last Update March 01, 2004

### ▶ P7260 Included Accessories

Description	Quantity	Part Number/Status
Instruction Manual	1 each	071-0922-xx
Probe Carry Case	1 each	016-1879-xx
Y Lead Adapter	2 each	196-3434-xx
3" Ground Lead	2 each	196-3437-10
SMT KlipChip™ Adapter	2 each	206-0364-xx
SureToe™	1 set	ST501 (Replacement Pkg of 12)
Accessory Reorder Sheet	1 each	001-1349
Short Ground Pogo Pin (set of 8)	1 set	016-1917-xx
Square Pin Adapter (set of 4) (adapt to .100" centered square pins)	1 set	016-1910-xx
Color Coding Bands, 5 Colors	1 set	016-1886-xx
"L" Adapter (set of 2)	1 set	016-1913-xx
Anti-static Wrist Strap	1 each	006-3415-xx
Customizable Grounded Lead (set of 5)	1 set	196-3482-xx

### ▶ Recommended Accessories

Description	Quantity	Part Number/Status
TekConnect® Calibration Adapter/Fixture/SW	1 each	067-0422-xx
Probe Arm	1 each	PPM100
High-speed Deskew Fixture	1 each	067-0484-xx
Probe Calibration Fixture	1 each	067-1456-xx
IC Grabber (set of 2)	1 set	013-0309-xx

Our most up-to-date product information is available at:  
[www.tektronix.com](http://www.tektronix.com)

Product(s) are manufactured  
in ISO registered facilities.



Copyright © 2004, Tektronix, Inc. All rights reserved. Tektronix products are covered by U.S. and foreign patents, issued and pending. Information in this publication supersedes that in all previously published material. Specification and price change privileges reserved. TEKTRONIX and TEK are registered trademarks of Tektronix, Inc. All other trade names referenced are the service marks, trademarks or registered trademarks of their respective companies.

04/04 HB/WWW

60W-14871-2