

INSTRUCTION MANUAL

TS 600 G



SOMMERKAMP®

TABLE OF CONTENTS

| | |
|---------|---|
| 1.1 | GENERAL |
| 1.2 | TROUBLESHOOTING TRANSISTORIZED TRANSCEIVERS |
| 1.3 | SERVICING EQUIPMENT |
| 1.4 | VOLTAGE MEASUREMENTS |
| 1.5 | SIGNAL TRACING |
| 1.6 | ALIGNMENT PROCEDURE |
| 1.6.1 | RECEIVER SECTION ALIGNMENT |
| 1.6.1.1 | IF ALIGNMENT |
| 1.6.1.2 | RF ALIGNMENT |
| 1.6.1.3 | SQUELCH ALIGNMENT |
| 1.6.1.4 | CALL SECTION ALIGNMENT (Receiver) |
| 1.6.2 | TRANSMITTER SECTION ALIGNMENT |
| 1.6.2.1 | RF ALIGNMENT |
| 1.6.2.2 | MODULATION CHECKING |
| 1.6.2.3 | CALL SECTION ALIGNMENT (Transmitter) |
| 1.7 | TROUBLESHOOTING |
| 1.8 | LOCATION OF ALIGNMENTS |
| 1.9 | PRINTED CIRCUIT BOARD DIAGRAM |
| 2.0 | SCHEMATIC DIAGRAM |
| 2.1 | PARTS LIST |



TS 600 G T R A N S C E I V E R

SERVICE AND MAINTENANCE

1.1 GENERAL

Your Model TS-600G Transceiver was carefully aligned at the factory for maximum output and sensitivity. Except for minor transmitter section and receiver section "peaking" adjustments, presented in the following paragraphs, servicing should be handled only by an authorized service agency. For In-Warranty service, send your transceiver prepaid to your nearest Sommerkamp Service Agency or to: Sommerkamp Electronic, Lugano 3, Box 176, Switzerland. For the name of your nearest Sommerkamp Service Agency, contact your Sommerkamp Field Sales Office. Unauthorized or improper field service may void the Warranty or be in violation of government regulations. Replacement transistors, crystals and certain other components should be obtained from Sommerkamp or Service Agencies.

1.2 TROUBLESHOOTING TRANSISTORIZED TRANSCEIVERS

The following general information will aid in troubleshooting transistorized transceivers.


If transistor emitter voltage is high or there is no difference between the base and emitter voltage, it is an indication of a shorted bypass capacitor or an open emitter resistor. A low emitter voltage indicates an open transformer or a defective resistor or transistor. If the collector voltage is low or equal to the emitter voltage, this indicates shorted or leaky transistor. A zero or close to zero collector voltage indicates an open transformer or decoupling resistor. In a defective stage, check for proper base and collector bias. If these are incorrect check the following.

1. Transformers
2. Capacitors
3. Transistors
4. Resistors

Another point to check in the case of incorrect bias on AGC stage is the AGC line and the detector which furnishes a portion of the voltage. Check the printed circuit board for cold or broken solder joints or no solder on component leads, wires, etc. In addition, inspect the printed circuit board for broken lands or delamination.

CAREFUL

While performing repair work or troubleshooting the TS-600G, care should be taken to avoid damaging components, especially transistors. Low wattage soldering irons should be used. Heat sinks should be used to prevent thermal damage to components. Place the heat sink on the component lead between the connection being soldered or unsoldered and the component. Carefully inspect all work for cold solder joints or solder splash shorts. Shorts could cause damage to semiconductors.



SOMMERKAMP

Replacement of defective components or repair of printed circuits should be made where incorrect voltage or resistance measurements indicate faulty circuitry. A break in a printed circuit land can easily be repaired with an insulated jumper wire across the break. The serviceman is reminded not to replace transistors before a thorough check is made. The Transistor is a dependable component and not subject to replacement as frequently as a vacuum tube.

1.3 SERVICING EQUIPMENT

To properly service the TS-600G the following servicing equipment is recommended:

- A. 20,000 ohm/volt Multimeter or VTVM (Hewlett-Packard Model 412 or equivalent). Either type of meter can be used to make all required voltage measurements.
- B. Audio Generator (Hewlett-Packard 200 series or equivalent). It is helpful in diagnosing and correcting problems in the audio section.
- C. 30% AM Modulated 27Mhz RF Signal Generator (Hewlett-Packard Model 606B or equivalent), with the output calibrated in microvolts and the output impedance of 50-ohm. It is used to aid in locating problems in the RF section of the receiver. The calibrated output will insure proper sensitivity after repair. If a calibrated output is not available, a signal from another station can be monitored to check whether incoming signal strength is normal.
- D. Modulated 455Khz Generator (Hewlett-Packard Model 606B or equivalent). It is used for adjustments of IF amplifiers.
- E. Oscilloscope covering audio frequencies. It is very helpful in looking at the detector output when troubleshooting the receiver section and also in locating problems in the audio-modulation section.
- F. R.F. wattmeter (0-5) watts (Bird Model 43 or equivalent). It is used to determine proper operation of the transmitter section. A wattmeter reading both forward and reflected power is recommended. For installation, it will also determine whether problems exist in the transmitter section or the antenna system.
- G. 50-ohm dummy load (Bird Model 80A or equivalent). The transmitter section should never be operated without a proper antenna or dummy load attached. To minimize interference while troubleshooting the transmitter section, a dummy load should be used. Two (2) 100 ohm two watt carbon resistor in parallel, soldered to a coaxial cable plug, may be used satisfactorily.
- H. Frequency meter or counter (Hewlett-Packard Model 524 or equivalent). If components are replaced in the transmitter oscillator section or frequency problems exist in the transmitter section, the frequency meter assures compliance with FTZ rules and regulations. The frequency meter should be accurate within 0.00050% which is one-tenth the allowable tolerance for this equipment.



SOMMERKAMP®

- I. DC power supply (13.8 ± 0.2 volts @1.5 amp). Since the majority of the equipment is used in vehicles, a power supply simulates mobile operation on the bench. There are many inexpensive battery eliminators on the market that are satisfactory.
- J. 8 ohm dummy load. It is used for measurement of the sensitivity and characteristics of the receiver. A carbon or wire-wound resistor of 8 ohm, 3 watts will do.
- K. Oscilloscope covering radio frequency at least up to 30Mhz (Hewlett-Packard Model 175A or equivalent). It is used to observe modulated and non-modulated carrier waves to determine there are parastic oscillations and also to set the modulation percentage of the call signal to 90 - 100%.

1.4 VOLTAGE MEASUREMENTS

See Table 1-1, which lists the typical voltage at each transistor and diode. Make all measurements under the following conditions:

- A. Unless otherwise noted, set the volume control at minimum and the channel selector at "A" position.
- B. Be sure to have a 50 ohm dummy load properly connected for measurements of the transmitter section.
- C. The voltage readings are measured between the indicated circuit lands to the chassis ground.

It is recommended that a VTVM be used for these measurements, as the voltage measurements made with a multimeter will yield lower readings in high impedance circuits such as in the base circuits.

1.5 SIGNAL TRACING (See Table 1-2, Signal Levels)

Appropriate test points and the normal receiving signal levels are listed in Table 1-2. The values listed are nominal. Signal levels in a receiver section may differ from those listed by a factor of plus or minus 20 percent without noticeable degradation in performance. A signal generator with an accurately calibrated output attenuator must be used to provide the RF signal voltages indicated. Measurements of injection voltages require the use of an RF VTVM such as the Boonton Electronics Model 91CA. Make RF and audio measurements under the following conditions:

- A. For audio measurements, use an audio oscillator as the signal source. Set VOLUME CONTROL at maximum, SQUELCH CONTROL minimum, and terminate the "SP2" output with a 8 ohm resistive load and a VTVM or calibrated oscilloscope.
- B. To check RF signal levels, connect the RF signal generator to the point indicated in the table, and rock the generator dial to produce maximum audio output. The generator modulation for 30 percent, 1000 Hz. Note the generator output voltage and compare with the value listed in the table.

1.6 ALIGNMENT PROCEDURE

See Figure 1-1, which indicates the locations of adjustments.



SOMMERKAMP®

1.6.1 RECEIVER SECTION ALIGNMENT

1.6.1.1 IF ALIGNMENT

- A. Set VOLUME CONTROL at maximum, SQUELCH CONTROL minimum and CHANNEL SELECTOR "A" position.
- B. Terminate the "SP2" output with a 8 ohm resistor and a VTVM or calibrated oscilloscope.
- C. Connect a signal generator to Q2 base through a 0.1uF capacitor, and adjust frequency to center of filter pass band (455Khz) with 30% modulation at 1,000 hz and the output about 17 microvolts.
- D. Adjust L5, L6 and L7 for maximum output on VTVM on oscilloscope.

1.6.1.2 RF ALIGNMENT

- A. Set VOLUME CONTROL maximum, SQUELCH CONTROL minimum and CHANNEL SELECTOR "A" position.
- B. Terminate the "SP2" output with a 8 ohm resistor and a VTVM or calibrated oscilloscope.
- C. Connect a 27Mhz AM signal generator to the antenna connector J3. Adjust its output for 1 microvolt with 30% modulation at 1,000 hz and correct receiving frequency carefully.
- D. Adjust L1, L2 and L3 for maximum output on VTVM or oscilloscope.
- E. Turn the core of L4 (Local oscillator) counterclockwise until the upper end of the core becomes flash with the coil case, by which the oscillation will cease. Then, turn the core clockwise carefully till the oscillation starts and make one more further turn from this point.

1.6.1.3 SQUELCH ALIGNMENT

- A. Follow the same procedures as A, B and C in 1.6.1.2.
- B. Set SQUELCH CONTROL at maximum.
- C. Adjust R6 so that the squelch is open with the signal generator input of 100 microvolts.

1.6.1.4 CALL SECTION ALIGNMENT (Receiver)

- A. Connect a frequency counter to "SP1" output.
- B. Adjust L8 so as to set the call tone at $1,080 \pm 5\text{Hz}$ while depressing the call switch, S2. Do not tamper with R4, which is for factory adjustment.
- C. Turn the power switch off to put the call lamp off.
- D. Follow the same procedures as A, B and C in 1.6.1.2.
- E. Connect an audio generator to the External AM terminal of the 27Mhz signal generator, and adjust its modulation to 90% at $1,080 \pm 5\text{Hz}$.



SOMMERKAMP®

- F. Adjust R3 (Call sensitivity adjustment) so as to get the call lamp lighted at the signal input of 1 - 2 microvolts.

1.6.2 TRANSMITTER SECTION ALIGNMENT

1.6.2.1 RF ALIGNMENT

- A. Set CHANNEL SELECTOR at "A" position.
- B. Remove the shorting test point wire (TP) beside L14.
- C. Connect a 0-500 mA DC meter with the positive lead on the circuit land and the negative lead on the collector Q16.
- D. Transmit with no load. Adjust L17 for collector current dip.
- E. Connector an RF wattmeter (0-5 watts) with 50 ohm dummy load.
- F. Turn the core of L12 clockwise to furthestmost position, when oscillation ceases. Then turn the core counterclockwise until the oscillation starts and further turn the core for three more turns.
- G. Transmit and adjust L14, L16 and L18 for maximum output on the wattmeter. The DC meter should indicate 390mA maximum for 5 watt input to final stage, Q16, with a collector voltage of 12.6 volts DC at TP.
- H. Adjust R7 (meter sensitivity adjustment) so as to read the RF power indicator of the set at the center of the black zone on its meter face.

1.6.2.2 MODULATION CHECKING

- A. Connect a dummy load with an RF oscilloscope.
- B. Check and see if the modulation is normal when spoken into the microphone at transmitting.
- C. Check and see if the wave form is normal when the call button is depress at transmitting.

1.6.2.3 CALL SECTION ALIGNMENT

- A. Follow the same procedures as A and C in 1.6.2.2.
- B. Set R5 (call mod. adj.) for 90 - 100 percent modulation level.

1.7 TROUBLESHOOTING

See Table 1-3-1 for receiver section and Table 1-3-2 for transmitter section.



SOMMERKAMP®

TABLE 1-1 Voltage Measurements (in DC)

| Transistor or Diode | Transistor, Diode Electrodes | | |
|---------------------------|------------------------------|-------------------|----------------------|
| | Collector (Anode) | Base (Gate) | Emitter (Cathode) |
| Q1 Redeive Transmit | 8.5 0 | 3.0 0 | 2.3 0 |
| Q2 R T | 8.8 0 | 3.0 0 | 2.4 0 |
| Q3 R T | 5.3 0 | 2.1 0 | 1.5 0 |
| Q4 R T | 8.3 0 | 3.0 0 | 2.4 0 |
| Q5 R T | 8.0 0 | 2.0 0 | 1.4 0 |
| Q6 R T | 3.0 0 | 0 0 | 0 0 |
| Q7 R (1) R (2) T | 9.0 0.1 0 | 0.28 0.64 0 | 0 0 0 |
| Q8 R T | 9.2 9.2 | 1.4 1.4 | 0.85 0.85 |
| Q9 R T | 13.6 13.6 | 3.2 3.2 | 3.2 3.2 |
| Q10 R T | 2.2 2.2 | 0.7 0.7 | 0.1 1.1 |
| Q11 R T | 13.6 13.6 | 3.2 2.2 | 1.6 1.6 |
| Q12 & 13 R T | 13.6 13.6 | 0.65 0.65 | - - |
| Q14 R T | 13.6 12.0 | 13.6 1.4 | 13.6 2.6 |
| Q15 R T | 0 6.2 | 0 -0.15 ~ -0.2 | 0 0 |
| Q16 R T | 13.8 12.6 | 0 - | 0 - |
| D5 R T | 0 0 | | 9.2 0 |
| D8 R T | 0 0 | | 9.2 9.2 |
| D9 R T | 0.6 0.6 | | 0 0 |
| D11 R T | 0 0 | | 13.8 13.8 |
| D12 R T | 13.6 13.6 | 0 0 | 0 0 |

Remarks: (1) Squelch control set at minimum.
 (2) Squelch control set at maximum.



SOMMERKAMP®

TABLE 1-2 Signal Levels


| Signal injection point | Generator output frequency | Generator output voltage | Normal indication |
|------------------------|----------------------------|--------------------------|-------------------|
| Q10 - Base | 1,000Hz | 1.2mV | 0.5W audio out |
| D1 - cathode | 1,000Hz | 27mV | - ditto - |
| Q5 - base | 455Khz | 2.3mV | - ditto - |
| Q4 - base | 455Khz | 90mV | - ditto - |
| Q2 - base | 27Mhz | 14uV | - ditto - |
| Q2 - emitter | Local oscillator injection | | 40-100mV RF |
| Q1 - base | 27Mhz | 0.6uV | 0.5W audio out |
| J3 (antenna) | 27Mhz | 0.6uV | 0.5W audio out |



TABLE 1-3-1

Receiver Section General Troubleshooting Procedures

| Fault | Test Procedures | Designation | Nominal voltage (in DC) | | | Sympton | Check-up procedures | Remarks |
|-----------------|--|-------------|----------------------------|------|---------|-------------------------|---|---|
| | | | Collector | Base | Emitter | | | |
| No audio output | See 1.5 Signal tracing A. | | | | | No B+ | 1) Check shorted (+) and (-) lands. 2) Check D8, D5. | |
| | | Q10 | 2.2 | 0.7 | 0.1 | | Check Q10 level. | 1.2mV at base of Q10. 13.5mV at collector. |
| | | Q11 | 13.6 | 2.2 | 1.6 | | Check Q11 level. | 13.5mV at base of Q11. 0.65V at collector. |
| | | Q12, 13 | 13.6 | 0.65 | - | | Check Q12 & Q13 levels. | 0.53V at base or base. 6.6V at collector to collector. |
| | See 1.6.1.2 RF alignment A. B. & C. | | | | | No detect- or output | 1) Check D1, 2 & 4. 2) Check relay | |
| | | Q3 | 5.3 | 2.1 | 1.5 | - ditto - | 1) Check Osc. bias voltage. 2) Align I4. | At Channel "A" position. |
| | | Crystal Y1 | | | | - ditto - | 1) Replace with known good crystal. 2) Align I4 again. | Check Channel Selector S-1-1 and switch wiring. |




SOMMERKAMP®

TABLE 1-3-1


Receiver Section General Troubleshooting Procedures (cont'd)


| Fault | Test procedures | Designation | Nominal voltage (in DC) | | Sympton | Check-up procedures | Remarks |
|--|-------------------------------------|-------------|----------------------------|------|---------------------|---|-------------------------------|
| | | | Collector | Base | | | |
| Low sensitivity (after proper alignment) w/squelch at min. | See 1.6.1.2 RF alignment A. B. & C. | Q2 emitter | | | - ditto - | Check Osc. injection voltage. | 40 - 100 mV rms. |
| | | Q1 | 8.5 | 3.0 | | | No signal. |
| | | AGC line | | | | Check Q6 | 3.0V typical, with no signal. |
| | See 1.6.1.1. IF alignment A.B. & C. | Q2 | 8.8 | 3.0 | | | With crystal. |
| | | Q4 | 8.3 | 3.0 | | | With no signal. |
| | | Q5 | 8.0 | 2.0 | | | |
| Mal-function of Squelch | See 1.6.1.3 Squelch alignment | Q2, 4, 5 | | | Low detector output | Check IF sensitivity at 455Khz for Q2, 4 & 5. | See Table 1-2 |
| | | Q7 | 9.0 | 0.28 | | | Squelch at Min. |
| | | Q7 | 0.1 | 0.64 | | | Squelch at Max. |
| | | | | | | Check Q7 & D4. | |



SOMMERKAMP®

| Fault | Test procedures | Designation | Nominal voltage (in DC) | | | Symptom | Check-up procedures | Remarks |
|---|---|----------------------|----------------------------|---------------|---------|-----------------------------|---|--|
| | | | Collector | Base | Emitter | | | |
| No output or low output | See 1.6.2 Trans- mitter Align- ment A.B. & C. | | | | | No voltage on land on | Check microphone cable, wiring, shorted lands, relay | |
| | | Q14 | 12.0 | 1.4 | 2.6 | No out- put at Q14 | | Ic of Q14: 15- 20mA. |
| | | Q14 | | | | - ditto - | Measure self bias voltage of Q15 on VTVM | Must be -0.15- -0.2Vdc across R70. |
| | | Q15 | 6.2 | -0.15 -0.2 | 0 | No out- put at Q15 | 1) Check Ic of Q15 2) Check insulator of Q15 | Must be 50-60mA |
| | | Q16 | 12.6 | - | - | No output | 1) Check Ic of Q16 2) Check insulator of Q16. | Must be 390mA, typical. |
| | | Bypass capacitors | | | | No output | 1) Check C57 2) Check relay | |
| | | | | | | | Individually shunt all bypass capa- citors | To see they are not open. |
| | | | | | | | Check microphone and its cable. Check T2 | |
| No modu- lation or shallow modula- tion | See 1.6.2.2 Modulation checking A. | | | | | | | |


SOMMERKAMP®


LOCATION OF ALIGNMENTS

PARTS LIST

| <u>Description</u> | <u>Schematic symbol</u> | <u>Part No.</u> |
|------------------------------|--|-----------------|
| <u>Capacitors</u> | | |
| 0.001uF, 50V, ceramic | C39, 45, 46 | 0315 102 516 |
| 0.002uF, " " | C21 | 0315 202 516 |
| 0.01uF, " " | C7, 8 | 0315 103 516 |
| 0.01uF, 25V, " " | C2, 5, 12 | 0312 103 317 |
| 0.02uF, " " | C47, 48 | 0312 203 317 |
| 0.05uF, " " | C4, 6, 9, 16, 17, 18, 19, 35, 52, 57, 63 | 0312 503 317 |
| 0.1uF, " " | C13, 14, 15, 65 | 0312 104 317 |
| 0.1uF, 12V, " " | C23, 26 | 0318 104 117 |
| 0.2uF, " " | C22 | 0318 204 117 |
| 1uF, 50V, Electrolytic | C25 | 0321 010 510 |
| 4.7uF, 16V " " | C3, 38 | 0321 479 210 |
| 10uF, " " | C27, 28 | 0321 100 210 |
| 22uF, " " | C37 | 0321 220 210 |
| 33uF, 10V " " | C10 | 0321 330 110 |
| 47uF, 6V " " | C30, 41 | 0321 470 110 |
| 220uF, 10V " " | C42 | 0321 221 110 |
| 1000uF, 16V " " | C64 | 0321 103 210 |
| 0.5uF, 10V " (solid alum.) | C36 | 0324 059 110 |
| 1uF, " " " " | C24 | 0324 010 110 |
| 0.01uF, 50V, polyester | C20, 34 | 0331 103 516 |
| 0.015uF, " " " | C40, 43, 44 | 0331 153 515 |
| 0.03uF, " " " | C33 | 0331 303 516 |
| 0.1uF, " Styrol | C32 | 0341 104 514 |
| 5pF, " Mica | C62 | 0351 050 514 |
| 30pF, " " | C49 | 0351 300 514 |
| 50pF, " " | C50 | 0351 500 514 |
| 62pF, " " | C58, 61 | 0351 620 514 |
| 75pF, " " | C54 | 0351 750 514 |
| 90pF, " " | C55 | 0351 900 514 |
| 100pF, " " | C11, 31 | 0351 101 514 |
| 200pF, " " | C51 | 0351 201 514 |
| 380pF, " " | C60 | 0351 381 514 |
| 470pF, " " | C56, 59 | 0351 471 514 |
| 1000pF, " " | C29 | 0351 102 515 |
| 1pF, 500V, Fixed composition | C1 | 0372 010 525 |
| <u>Resistors</u> | | |
| 10 ohm, 10%, 1/2W, Compos. | R73 | 1802 100 125 |
| 47 ohm, " " " | R27, 77 | 1802 470 125 |
| 100 ohm, " " " | R69, 70, 74 | 1802 101 125 |
| 150 ohm, " " " | R58, 60, 63, 68 | 1802 151 125 |
| 270 ohm, " " " | R49, 61, 72 | 1802 271 125 |
| 330 ohm, " " " | R71 | 1802 331 125 |
| 470 ohm, " " " | R28, 29, 38, 75 | 1802 471 125 |
| 560 ohm, " " " | R48, 52 | 1802 561 125 |
| 1K " " " | R10, 14, 24, 39, 55, 62 | 1802 102 125 |
| 1.5K " " " | R19 | 1802 152 125 |
| 2.2K " " " | R8, 20, 30 | 1802 222 125 |
| 2.7K " " " | R22 | 1802 272 125 |
| 3.3K " " " | R9, 17, 67 | 1802 332 125 |
| 3.9K " " " | R37 | 1802 392 125 |
| 4.7K " " " | R11, 18, 21, 25 | 1802 472 125 |
| 6.8K " " " | R12, 15 | 1802 682 125 |
| 10K " " " | R16, 23, 45, 56, 59, 66 | 1802 103 125 |
| 15K " " " | R26, 76 | 1802 153 125 |


SOMMERKAMP®

| | | | | |
|-----------------------------|--------------|------|-----|-----|
| 22K, 10%, 1/2W, Compos. | R36,42,46 | 1802 | 223 | 125 |
| 33K, " " " | R32,33 | 1802 | 333 | 125 |
| 82K, " " " | R40 | 1802 | 823 | 125 |
| 100K, " " " | R31,47 | 1802 | 104 | 125 |
| 150K, " " " | R13,35,41,51 | 1802 | 154 | 125 |
| 220K, " " " | R57 | 1802 | 224 | 125 |
| 270K, " " " | R34 | 1802 | 274 | 125 |
| 330K, " " " | R43,50 | 1802 | 334 | 125 |
| 470K, " " " | R44,53,54 | 1802 | 474 | 125 |
| 4.7ohm, 2W, wire-wound | R65 | 1803 | 479 | 025 |
| 1 ohm, 1W, Metal film | R64 | 1806 | 010 | 015 |
| 2K, variable, semi-fixed | R6 | 5807 | 016 | 000 |
| 50K, " " " | R3,7 | 5807 | 015 | 000 |
| 100K, " " (2-P) | R4 | 5807 | 017 | 000 |
| 100K, " " " | R5 | 5807 | 014 | 000 |
| 50K + 5K (ganged, variable) | R1,2 | 4808 | 005 | 001 |
| <u>Transformers</u> | | | | |
| Driver | T1 | 2002 | 019 | 000 |
| Output | T2 | 2002 | 020 | 000 |
| <u>IFT</u> | | | | |
| 1st | L5 | 1214 | 005 | 000 |
| 2nd | L6 | 1214 | 006 | 000 |
| 3rd | L7 | 1214 | 007 | 000 |
| <u>Ceramic Filter</u> | | | | |
| LF-A8 | CF1 | 0610 | 005 | 000 |
| <u>Coils</u> | | | | |
| Antenna, 1st | L1 | 1215 | 015 | 000 |
| Antenna, 2nd | L2 | 1215 | 016 | 000 |
| RF | L3 | 1215 | 017 | 000 |
| Local | L4 | 1215 | 018 | 000 |
| AF tuning | L8 | 1211 | 002 | 000 |
| 22 uH (fixed inductor) | L9 | 1202 | 021 | 000 |
| 1.7mH (choke) | L10 | 2003 | 006 | 000 |
| Osc. X'mit | L12 | 1205 | 027 | 000 |
| 10 uH (fixed inductor) | L11 | 1202 | 020 | 000 |
| 6.6 uH, RF choke | L13 | 1202 | 017 | 000 |
| Driver, X'mit | L14 | 1205 | 028 | 000 |
| 2.2 uH, RF choke | L15,16,17,18 | 1202 | 018 | 000 |
| <u>Transistors</u> | | | | |
| 2SC945Q | Q6,7,10 | 1730 | 945 | 170 |
| 2SC945R | Q8,9,11 | 1730 | 945 | 180 |
| 2SC838F | Q4 | 1730 | 838 | 060 |
| 2SC838H | Q5 | 1730 | 838 | 080 |
| 2SC838J | Q3 | 1730 | 838 | 100 |
| 2SC839F | Q2 | 1730 | 838 | 060 |
| 2SC839H | Q1 | 1730 | 839 | 060 |
| 2SD142M | Q12,13 | 1740 | 142 | 130 |
| 2SC815 | Q14 | 1730 | 815 | 000 |
| 2SC781 | Q15 | 1730 | 781 | 000 |
| 2SC799 | Q16 | 1730 | 799 | 000 |
| 2SF656 (thyristor) | D12 | 0411 | 011 | 000 |
| <u>Diodes</u> | | | | |
| SD46 | D1,6,7,10 | 0401 | 007 | 000 |
| 1N34A | D2 | 0401 | 004 | 001 |
| SG9150 | D3,4, | 0402 | 006 | 000 |
| F-14B | D11 | 0402 | 009 | 000 |
| 1S1209 | D9 | 0403 | 005 | 000 |
| RD-9A | D5,8 | 0405 | 005 | 000 |



SOMMERKAMP

Miscellaneous

| | | | | |
|-----------------------------|-------|------|-----|-----|
| Printed circuit board, main | | 1601 | 021 | 001 |
| " " " sub | | 1601 | 022 | 000 |
| Lamp, pilot, 18V/110mA | PL2 | 3220 | 012 | 000 |
| " call, 14V/80mA | PL1 | 3220 | 013 | 000 |
| Meter | | 1301 | 004 | 000 |
| Microphone, 600 ohm | | 5303 | 001 | 000 |
| Hanger, microphone | | 5303 | 001 | 100 |
| Plug, 3.5mm | | 4613 | 001 | 001 |
| Crystal, HC25/U | Y1, 2 | | | |
| Switch, channel selector | S1 | 1903 | 003 | 000 |
| " push | S2 | 1907 | 004 | 000 |
| Speaker, 3.2 ohm, 1.25W | | 3910 | 007 | 000 |
| Holder, crystal | | 4920 | 002 | 000 |
| Stopper, cord | | 0812 | 001 | 000 |
| Cover, lamp | | 0811 | 002 | 000 |
| Jack, antenna | | 4330 | 006 | 000 |
| Jack, speaker | J1,2 | 1003 | 002 | 000 |
| Relay, 4P-2T | | 1102 | 001 | 000 |
| Fuse | F1 | 3601 | 001 | 000 |

