

programmable micro-ohmmeter

OM 21



OM21 micro-ohmmeter is used for four-wire resistance measurement of very low values (with a resolution of 0.1 $\mu\Omega$) up to 20 k Ω , with an excellent accuracy.

It can be powered from mains or from rechargeable batteries.

The instrument is calibrated electronically, with no internal adjustment needed.

- High resolution: 0.1 $\mu\Omega$
- Programmable by RS232 or IEEE 488 link
- High accuracy: 0.03%
- Choice of current waveforms
- Storage and analysis of 1 000 measurements

Applications.....

- Cable resistance and resistivity measurements
- High resolution (0.1 $\mu\Omega$),
- Compensation for sample temperature and thermal emfs,
- Display in Ω/km .
- Metallisation and ground continuity measurements
- GAM-EG13 standards,
- Pulsed or alternate current (10 A),

- Automatic compensation for thermal emfs.

- Contact resistance measurements (connectors, switches, relays)
- Standard NFC 93050, DIN/IEC,
- Maximum measurement Voltage limited to 20 or 50 mV,
- Automatic compensation for thermal emfs.
- Inductive resistance measurement (motors, transformers, etc.)

- Total protection against overvoltages

- Direct current,
- Compensation for thermal emfs and for sample temperature,
- Automatic calculation of winding heating.
- Measurement of heat-sensitive devices (thermistors, temperature-sensitive components)
- Single-shot, pulsed current, very low power delivered.

general specifications

Display

26 000 counts, 16-segment illuminated LCD, 11.5 mm high, alphanumeric characters for messages, measurement indication includes value and unit of measurement. Incorrect connections or measurements going beyond range are indicated by an error message.

Manual or automatic range change.

Manual or automatic measurement triggering, with measurement rate programmable from one measurement per second to one per hour.

Four-wire measurement.

Measurement current

- Amplitude selection (from 100 μA to 10 A,
- Waveform selection
 - continuous,
 - alternate pulses,
 - positive pulses,
- With each type of current, measurements can be single-shot or repetitive (pos-

sibility to select the repetition rate),
 • Current may also be supplied from an external source.

Measurement time
 < 1 second in continuous mode,
 < 1.5 second in pulsed mode,
 < 2 seconds in alternating pulsed mode.

Protection
 • Electronic protection against break-off

currents when measuring an inductive resistance,
 • Possibility of limiting the voltage across the resistor terminals to 20 or 50 mV.

Environment
 Nominal operating range: 0 to 50°C, 20 to 75% relative humidity.
 Operating range limits: -10 to 55°C, 10 to 80% relative humidity.

Power supply
 • 110/220 VAC \pm 10%, 50/60 Hz,
 • optional battery with built-in charger.

Presentation
 Bench unit with optional rack mounting kit.
 Dimensions: 225 x 88 x 300 mm.
 Weight: 2 to 3 kg depending on options.

functions

The instrument measures very low value resistances in a four-wire terminal. It has eight measurement ranges. For the same current, the range can be changed manually or automatically. The user has a choice of three current values for each measurement range, except for the extreme ranges.

Temperature coefficient < 10% of the accuracy per degree Celsius.

Automatic compensation for thermal electromotive forces (emfs)

Range	Resolution	Measurement current	Voltage drop	Accuracy (1)
2 m	0.1 μ	10 A	20 mV	0.05% + 0.3 μ
20 m	1 μ	10 A	200 mV	0.05% + 2 μ
20 m	1 μ	1 A	20 mV	0.05% + 3 μ
200 m	10 μ	10 A	2 V	0.05% + 10 μ
200 m	10 μ	1 A	200 mV	0.05% + 20 μ
200 m	10 μ	100 mA	20 mV	0.03% + 30 μ
2	100 μ	1 A	2 V	0.05% + 100 μ
2	100 μ	100 mA	200 mV	0.03% + 200 μ
2	100 μ	10 mA	20 mV	0.03% + 300 μ
20	1 m	100 mA	2 V	0.03% + 1 m
20	1 m	10 mA	200 mV	0.03% + 2 m
20	1 m	1 mA	20 mV	0.03% + 3 m
200	10 m	10 mA	2 V	0.03% + 10 m
200	10 m	1 mA	200 mV	0.03% + 20 m
200	10 m	100 μ A	20 mV	0.03% + 30 m
2 k	100 m	1 mA	2 V	0.03% + 100 m
	100 m	100 μ A	200 mV	0.03% + 200 m
20 k	1	100 μ A	2 V	0.03% + 1

(1) The accuracy is given as \pm (% of the reading + counts). The count corresponds to the value of the last figure displayed, i.e. to the resolution on this range. The accuracy is given over 90 days at 23 \pm 1°C.

additional functions

Automatic temperature compensation of the element measured for temperatures between 0°C and 100°C
 The instrument calculates the resistance value at 20°C.
 Element temperature is:
 - either programmed,
 - or is measured by a platinum resistance probe (Pt100).
 Metal type, or its temperature coefficient, is indicated on the OM.

Relative measurements
 The instrument can display:
 • either $D = M/R$,
 • or $D = (M-R)/R$ (i.e. direct read-out in %)
 (D = reading display, M = value measured, R = stored reference value).

Memory
 Up to 1 000 measurements can be stored, along with their mean, minimum or maximum, and can be read back on the read-out or through digital or analog interfaces.

Two programmable thresholds
 With output on two relays (1 A/220 V AC).

Floating analog output
 0 to 2.5 V (load 2.5 k Ω , 10 mV resolution).
 An image can be constructed of all or part of the measured values: the origin and extent of the measurements can be programmed to get a "zoom" effect. The measurement values stored in the memory can be extracted and output in the form of analog voltages.

Calculations
 OM21 can calculate automatically the heat-up of a motor or transformer. Similarly it can calculate the resistance per km of single core or multi-core cables.

RS 232C and IEEE 488-2 interfaces
 The standard RS 232C and optional IEEE 488-2 interfaces make it possible, by computer, to:
 • program the instrument completely,
 • analyse the measurements (curve plot, printout, etc.)
 • calibrate the instrument.

software

The PC software allows programming of the OM21 or 22 from a compatible PC. It is menu-driven, with the operator completely guided by a question and answer system.

A second function of the software is to ma-

nipulate the stored readings; transfer into the PC memory or onto a disk in a file which can be used for spreadsheets; presentation of the readings in the form of tables or graphs.

Labview driver

This driver, delivered, on request, free of charge with IEEE version, allows to connect OM with Labview, to command the microhmmeter (OM 21 or 22 with IEEE) from a PC and to process the data.

accessories

KELVIN lead set - AN 5806

A pair of measurement leads, each with a KELVIN clip, 1.20 m of wire and two 4 mm plugs. The KELVIN clip can be used for four-wire measurement because there is a perfect galvanic isolation between the current input and the voltage connector. Gold-plated contacts.
Maximum opening: 1.2 cm.
Maximum current: 10 A.




Large Kelvin clip - AMT 004

One measurement lead with a large Kelvin clip.
Length of wire: 3 m.
Equipped of two 4 mm security banana plugs.
Maximum opening of clip: 3 cm.
Maximum current: 10 A.



Kelvin test probe - AMT 003

One measurement lead with a dual probe (concentric).
Length of rod: 85 mm.
Diameter of rod: 8 mm.
Length of wire: 3 m.
Equipped of two 4 mm security banana plugs.
Maximum current: 10 A.



Carrying case - AN 6901

A soft carrying case designed for storage and transport of all bench type instruments (OM 21, 22).
Dimensions: 31 x 26 x 14 mm.

Clamping device - 2381

With the help of the clamping device type 2381 and a microhmmeter, the ohmic resistances of test cables and samples of materials in the shape of cords or strips can be measured. Fields of application include production monitoring, quality assurance and general test measurements. The 2381 consists of a robust, warp-resistant, light-metal rail with one movable and one rig clamping device. It allows the measurement of samples 1000 mm long. The clamping device is designed to accommodate cable cross-sections of 0.1 mm² to approx. 100 mm². It is equipped with a wire guide 2388.
Dimensions: 170 x 2100 x 250 mm.
Weight: 25 kg.

Rack mounting kit - AN 5884

This kit allows rack mounting of bench instruments. It includes 2 brackets (AN 5883) and a 19" rack panel (3 U).

ordering instructions

RS 232 programmable micro-ohmmeter

Basic instrument 10 A	OM 21-1
Basic instrument 10 A + battery and charger	OM 21-2
Basic instrument 10 A + IEEE 488-2	OM 21-3
Basic instrument 10 A + IEEE 488-2 + battery	OM 21-4

Accessories

Kelvin lead set	AN 5806
Large Kelvin clip	AMT004
Kelvin micro-probe	AMT003
Clamping device	2381
Wire guide	2388
Carrying case	AN 6901
Brackets for panel mounting	AN 5883
Rack mounting	AN 5884
RS 232 cable (9-25 pin, female) (1)	AN 5874
RS 232 cable (9-9 pin, female) (1)	AN 5875
RS 232 cable (9-25 pin, male) (1)	AN 5876
IEEE 488 cable	AN 5836
PC 9/25 pin converter	AN 5894
Labview driver	OM2-LABV-DRIV
For OM21-1 and 21-3: power supply 3 V/10 A	AMT002



AOIP
BP 182
91133 Ris Orangis CEDEX
FRANCE
+33 169 028 900
www.aoip.com

(1) The RS 232 connector is a 9 pin female